

OIL ANALYSIS REPORT

Sample Rating Trend



Machine Id 40-99 Component Swing Drive Fluid TDTO FLUID SAE 30 (--- GAL)

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.


Fluid Condition

The condition of the oil is suitable for further service.

SAMPLE INFORM	NATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0936956	WC0619834	
Sample Date		Client Info		25 Jan 2024	11 Apr 2023	
Machine Age	hrs	Client Info		5965	5697	
Oil Age	hrs	Client Info		0	0	
Oil Changed		Client Info		Changed	Not Changd	
Sample Status				NORMAL	NORMAL	
CONTAMINATIO	N	method	limit/base	current	history1	history2
Water		WC Method	>0.2	NEG	NEG	
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>400	172	156	
Chromium	ppm	ASTM D5185m	>10	1	2	
Nickel	ppm	ASTM D5185m	>10	0	0	
Titanium	ppm	ASTM D5185m		0	<1	
Silver	ppm	ASTM D5185m		0	0	
Aluminum	ppm	ASTM D5185m	>25	1	2	
Lead	ppm	ASTM D5185m	>50	<1	0	
Copper	ppm	ASTM D5185m	>200	3	3	
Tin	ppm	ASTM D5185m	>10	0	0	
Vanadium	ppm	ASTM D5185m		0	0	
Cadmium	ppm	ASTM D5185m		0	0	
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	37	<1	1	
Barium	ppm	ASTM D5185m	7	0	0	
Molybdenum	ppm	ASTM D5185m	5	<1	<1	
Manganese	ppm	ASTM D5185m		2	2	
Magnesium	ppm	ASTM D5185m	40	9	12	
Calcium	ppm	ASTM D5185m	2650	2729	2749	
Phosphorus	ppm	ASTM D5185m	1050	797	738	
Zinc	ppm	ASTM D5185m	1075	721	705	
Sulfur	ppm	ASTM D5185m	5750	9720	9509	
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>50	12	15	
Sodium	ppm	ASTM D5185m		1	1	
Potassium	ppm	ASTM D5185m	>20	<1	0	
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	
Precipitate	scalar	*Visual	NONE	NONE	NONE	
Silt	scalar	*Visual	NONE	NONE	NONE	
Debris	scalar	*Visual	NONE	NONE	NONE	
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	
Appearance	scalar	*Visual	NORML	NORML	NORML	
Odor	scalar	*Visual	NORML	NORML	NORML	
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	
Free Water	scalar	*Visual		NEG	NEG	
03:55) Rev: 1 Contact/Location: BEN CALDWELL - MA						



OIL ANALYSIS REPORT



FLUID PROF	PERTIES	method	limit/base	current	history1	history2	
Visc @ 40°C	cSt	ASTM D445	101	118	118		
SAMPLE IMA	AGES	method	limit/base	current	history1	history2	
Color				no image	no image	no image	
Bottom				no image	no image	no image	
GRAPHS							
Ferrous Alloy:	s		,-				
160 - iron 140 - nickel							
120							
E 80							
60-							
40 -							
20							
Apr11/23			Jan 25/24				
₹ Non-ferrous I	Metals		Jai				
10 9 copper							
8 - tin							
6							
Ed 5-							
3							
2							
Apr11/23			Jan 25/24				
Viscosity @ 4	0°C						
125 120							
115							
105 Base							
Base 100 − 5 95 −							
90 - 85 -							
80 - 75 - <mark>Abnormal</mark>							
70			24				
Apr11/23			Jan 25/24				
: WearCheck USA : WC0936956 : 06174329				MAN	MANHATTAN ROAD AND BRIDG 5601 S 122ND E AV TULSA, C US 7414		



Unique Numb Test Package : CONST Certificate L2367 To discuss this sample report, contact Customer Service at 1-800-237-1369. kevin.marson@wearcheck.com * - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Report Id: MANTUL [WUSCAR] 06174329 (Generated: 05/13/2024 16:03:55) Rev: 1

Contact/Location: BEN CALDWELL - MANTUL

F:

T: (918)728-5749

Contact: BEN CALDWELL