

FUEL REPORT

Sample Rating Trend



Machine Id **ZDC AST 2 6 IN** Component **Diesel Fuel** Fluid **DIESEL FUEL No. 2 (--- GAL)**

DIAGNOSIS

Recommendation

No corrective action is recommended at this time. All laboratory tests indicate that this sample meets specifications for No.2 ultra-low-sulfur diesel fuel. Please note that this is a corrected copy for diagnostic comment updates.

Corrosion

All metal levels are normal indicating no corrosion in the system.

Contaminants

There is a moderate amount of particulates present in the fuel. The water content is negligible. There is no bacteria or fungus (yeast and/or mold) present in the sample.

Fuel Condition

Sulfur value derived by ASTM D5453 method for ULSD validation. Sulfur level is acceptable for ULSD specification.


SAMPLE INFORM	1ATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0929970		
Sample Date		Client Info		08 May 2024		
Machine Age	hrs	Client Info		0		
Sample Status				NORMAL		
PHYSICAL PROP	ERTIES	method	limit/base	current	history1	history2
Fuel Color	text	*Visual Screen		Red		
ASTM Color	scalar	*ASTM D1500		L4.5		
Visc @ 40°C	cSt	ASTM D445	4.1	2.57		
Pensky-Martens Flash Point	°C	*PMCC Calculated		60.8		
SULFUR CONTER	NT	method	limit/base	current	history1	history2
Sulfur	ppm	ASTM D5185m		0		
Sulfur (UVF)	ppm	ASTM D5453		9		
DISTILLATION		method	limit/base	current	history1	history2
Initial Boiling Point	°C	ASTM D86		172		
5% Distillation Point	°C	ASTM D86		195		
10% Distill Point	°C	ASTM D86		206		
15% Distillation Point	°C	ASTM D86		214		
20% Distill Point	°C	ASTM D86		222		
30% Distill Point	°C	ASTM D86		237		
40% Distill Point	°C	ASTM D86		250		
50% Distill Point	°C	ASTM D86		263		
60% Distill Point	°C	ASTM D86		277		
70% Distill Point	°C	ASTM D86		291		
80% Distill Point	°C	ASTM D86		307		
85% Distillation Point		ASTM D86		318		
90% Distill Point	°C	ASTM D86		328		
95% Distillation Point		ASTM D86		343		
Final Boiling Point	°C	ASTM D86		356		
IGNITION QUALIT	ΓY	method	limit/base	current	history1	history2
API Gravity		ASTM D7777		36		
Cetane Index		ASTM D4737	<40.0	48		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	<1.0	0		
Sodium	ppm	ASTM D5185m	<0.1	<1		
Potassium	ppm	ASTM D5185m	<0.1	0		
Water	%	ASTM D6304	< 0.05	0.003		
ppm Water	ppm	ASTM D6304	<500	38		
% Gasoline	%	*In-House	<0.50	0.0		
% Biodiesel	%	*In-House	<20.0	1.7		




FUEL REPORT

	ticle Cou	int			20
491,520					I ²⁶ 24
					Contraction of Contract
7 680					-22 [S0 4406:1999 Cleanliness Code -18 -19 -16 -14 -12 st Code -10 -10 -12 -10 -10 -10 -10 -10 -10 -10 -10 -10 -10
1,920 Abnor	mal				18 19
480		244			16 0
120-					14
30-			-		-12 s
8-					10 8
2-				1	-8
0 4µ	6µ	14µ	21µ	38µ	71µ
1000 - Sever (m. 800	ormal				
					_
May8/24					May8/24 -
Vis	cosity @	1000			
6 T	cosity @	40°C			






FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>2500	3165		
Particles >6µm		ASTM D7647	>640	615		
Particles >14µm		ASTM D7647	>80	88		
Particles >21µm		ASTM D7647	>20	33		
Particles >38µm		ASTM D7647	>4	2		
Particles >71µm		ASTM D7647	>3	0		
Oil Cleanliness		ISO 4406 (c)	>18/16/13	19/16/14		
HEAVY METALS		method	limit/base	current	history1	history2
Aluminum	ppm	ASTM D5185m	<0.1	0		
Nickel	ppm	ASTM D5185m	<0.1	0		
_ead	ppm	ASTM D5185m	<0.1	0		
/anadium	ppm	ASTM D5185m	<0.1	0		
ron	ppm	ASTM D5185m	<0.1	0		
Calcium	ppm	ASTM D5185m	<0.1	0		
Magnesium	ppm	ASTM D5185m	<0.1	0		
Phosphorus	ppm	ASTM D5185m	<0.1	0		
Zinc	ppm	ASTM D5185m	<0.1	0		
SAMPLE IMAGES	6	method	limit/base	current	history1	history2
Color					no image	no image
Bottom					no image	no image
GRAPHS						
Fuel Distillation Cu	rvo			Doneky-Marto	ns Flash Point (°C)





GCD Spectrum





VITAL FUEL SYSTEMS Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513 Sample No. : WC0929970 Received :09 May 2024 1076 CLASSIC RD Lab Number : 06174987 Tested : 17 May 2024 APEX, NC Unique Number : 11021040 Diagnosed : 11 Jun 2024 - Doug Bogart US 27539 Test Package : DF-2 (Additional Tests: Fuel, Screen) Contact: SERVICE Certificate 12367 To discuss this sample report, contact Customer Service at 1-800-237-1369. service@vitalfuelsystems.com * - Denotes test methods that are outside of the ISO 17025 scope of accreditation. T: (919)629-8180 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012) F: (919)303-7399

Report Id: VITAPE [WUSCAR] 06174987 (Generated: 06/11/2024 11:01:36) Rev: 2

Contact/Location: SERVICE ? - VITAPE

Page 2 of 2