

## **OIL ANALYSIS REPORT**

### Area CS-46 [SR33395186] QUINCY CAI794535 - CAMBLIN STEEL

Component Compressor

#### DIAGNOSIS

#### Recommendation

Resample at the next service interval to monitor.

#### Wear


All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil.

#### Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.




| SAMPLE INFORM    | IATION   | method      | limit/base | current     | history1    | history2 |
|------------------|----------|-------------|------------|-------------|-------------|----------|
| Sample Number    |          | Client Info |            | UCH06175601 | UCH05514330 |          |
| Sample Date      |          | Client Info |            | 23 Apr 2024 | 30 Mar 2022 |          |
| Machine Age      | hrs      | Client Info |            | 73190       | 55690       |          |
| Oil Age          | hrs      | Client Info |            | 0           | 3950        |          |
| Oil Changed      |          | Client Info |            | Changed     | Not Changd  |          |
| Sample Status    |          |             |            | NORMAL      | NORMAL      |          |
| CONTAMINATION    | ۷        | method      | limit/base | current     | history1    | history2 |
| Water            |          | WC Method   | >0.1       | NEG         | NEG         |          |
| WEAR METALS      |          | method      | limit/base | current     | history1    | history2 |
| Iron             | ppm      | ASTM D5185m | >50        | 0           | 0           |          |
| Chromium         | ppm      | ASTM D5185m | >10        | 0           | 0           |          |
| Nickel           | ppm      | ASTM D5185m |            | 0           | 0           |          |
| Titanium         | ppm      | ASTM D5185m |            | 0           | 0           |          |
| Silver           | ppm      | ASTM D5185m |            | 0           | 0           |          |
| Aluminum         | ppm      | ASTM D5185m | >25        | 0           | 0           |          |
| Lead             | ppm      | ASTM D5185m | >25        | 0           | 0           |          |
| Copper           | ppm      | ASTM D5185m | >50        | 0           | 0           |          |
| Tin              | ppm      | ASTM D5185m | >15        | 0           | 0           |          |
| Vanadium         | ppm      | ASTM D5185m |            | 0           | 0           |          |
| Cadmium          | ppm      | ASTM D5185m |            | 0           | 0           |          |
| ADDITIVES        |          | method      | limit/base | current     | history1    | history2 |
| Boron            | ppm      | ASTM D5185m | 1.5        | 0           | 0           |          |
| Barium           | ppm      | ASTM D5185m | 0          | <1          | 0           |          |
| Molybdenum       | ppm      | ASTM D5185m | 0          | 0           | 0           |          |
| Manganese        | ppm      | ASTM D5185m | 0.3        | 0           | 0           |          |
| Magnesium        | ppm      | ASTM D5185m | 0          | <1          | 0           |          |
| Calcium          | ppm      | ASTM D5185m | 0          | 0           | 0           |          |
| Phosphorus       | ppm      | ASTM D5185m | 406        | 140         | 193         |          |
| Zinc             | ppm      | ASTM D5185m | 0          | 8           | 0           |          |
| Sulfur           | ppm      | ASTM D5185m | 1283       | 576         | 907         |          |
| CONTAMINANTS     |          | method      | limit/base | current     | history1    | history2 |
| Silicon          | ppm      | ASTM D5185m | >25        | <1          | <1          |          |
| Sodium           | ppm      | ASTM D5185m |            | <1          | 0           |          |
| Potassium        | ppm      | ASTM D5185m | >20        | 0           | <1          |          |
| FLUID DEGRADA    | TION     | method      | limit/base | current     | history1    | history2 |
| Acid Number (AN) | mg KOH/g | ASTM D8045  | 0.463      | 0.30        | 0.061       |          |



# **OIL ANALYSIS REPORT**

VISUAL



|  | White Metal               | scalar | *Visual  | NONE  | NONE        | NONE     |          |
|--|---------------------------|--------|--|---|-------------|----------|----------|
|  | Yellow Metal              | scalar | *Visual  | NONE  | NONE        | NONE     |          |
| - the second | Precipitate               | scalar | *Visual  | NONE  | NONE        | NONE     |          |
|  | Silt                      | scalar | *Visual  | NONE  | NONE        | NONE     |          |
|  | Debris                    | scalar | *Visual  | NONE  | NONE        | NONE     |          |
|  | Sand/Dirt                 | scalar | *Visual  | NONE  | NONE        | NONE     |          |
| Apr23/24   | Appearance                | scalar | *Visual  | NORML   | NORML       | NORML    |          |
| Apr2   | Odor                      | scalar | *Visual  | NORML   | NORML       | NORML    |          |
|  | Emulsified Water          | scalar | *Visual  | >0.1  | NEG         | NEG      |          |
|  | Free Water                | scalar | *Visual  |   | NEG         | NEG      |          |
|  | FLUID PROPERT             | IES    | method   | limit/base  | current     | history1 | history2 |
|  | Visc @ 40°C               | cSt    | ASTM D445  | 47.9  | 46.1        | 46.7     |          |
|  | SAMPLE IMAGES             | S      | method   | limit/base  | current     | history1 | history2 |
| Apr23/24   | Color                     |        |  |   |             |          | no image |
|  | Bottom                    |        |  |   |             |          | no image |
|  | Non-ferrous Metal         | S      |  | Api23/24 Api23/24   |             |          |          |
|  |                           |        |  | Apr2  |             |          |          |
|  | Viscosity @ 40°C          |        |  |   | Acid Number |          |          |
|  | Abnormal                  |        |  | (B) 0.50<br>HO 0.40<br>E 0.30<br>mag 0.20<br>V 0.10<br>V 0.10 | Base        |          |          |
|  | C 50<br>Base              |        |  | Ē 0.30  |             |          |          |
|  | (3 50<br>Base<br>83<br>45 |        |  | e 0.20  | ).          |          |          |
|  | Abnormal                  |        |  | 2 0.10  |             |          |          |
|  | 40                        |        |  | 0.00  |             |          |          |
|  | Mar30/22                  |        |  | Apr23/24  | Mar30/22    |          |          |
|  | _                         |        |  |   | Marô        |          |          |
| Laboratory   | : WearCheck USA - 50      | CISCO  | CISCO AIR SYSTEM<br>214 27TH S<br>SACRAMENTO, C<br>US 9581<br>uct: BARRY FRKOVIC<br>yfrkovich@ciscoair.co<br>T: (916)444-252<br>F: |   |             |          |          |

Contact/Location: BARRY FRKOVICH - UCCISSAC