

OIL ANALYSIS REPORT

Sample Rating Trend





Machine Id VOLVO EC350E 314739 Component Right Travel

VOLVO PREMIUM GEAR OIL 85W-140 GL-5 (2 GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.


Fluid Condition

The condition of the oil is acceptable for the time in service.

SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		ML0001326		
Sample Date		Client Info		01 May 2024		
Machine Age	hrs	Client Info		1006		
Oil Age	hrs	Client Info		1006		
Oil Changed		Client Info		Changed		
Sample Status				NORMAL		
CONTAMINATION	1	method	limit/base	current	history1	history2
Water		WC Method	>0.25	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>1200	43		
Chromium	ppm	ASTM D5185m	>20	1		
Nickel	ppm	ASTM D5185m	>5	0		
Titanium	ppm	ASTM D5185m		<1		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>100	2		
Lead	ppm	ASTM D5185m	>50	<1		
Copper	ppm	ASTM D5185m	>50	<1		
Tin	ppm	ASTM D5185m	>5	<1		
Vanadium	ppm	ASTM D5185m		<1		
Cadmium	ppm	ASTM D5185m		<1		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	111	191		
Barium	ppm	ASTM D5185m	0.0	3		
Molybdenum	ppm	ASTM D5185m	0.9	<1		
Manganese	ppm	ASTM D5185m	0.0	<1		
Magnesium	ppm	ASTM D5185m	39	1		
Calcium	ppm	ASTM D5185m	93	11		
Phosphorus	ppm	ASTM D5185m	920	994		
Zinc	ppm	ASTM D5185m	104	27		
Sulfur	ppm	ASTM D5185m	20179	20973		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>100	2		
Sodium	ppm	ASTM D5185m		<1		
Potassium	ppm	ASTM D5185m	>20	6		
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE		
Yellow Metal	scalar	*Visual	NONE	NONE		
Precipitate	scalar	*Visual	NONE	NONE		
Silt	scalar	*Visual	NONE	NONE		
Debris	scalar	*Visual	NONE	NONE		
Sand/Dirt	scalar	*Visual	NONE	NONE		
Appearance	scalar	*Visual	NORML	NORML		
Odor	scalar	*Visual	NORML	NORML		
Emulsified Water	scalar	*Visual	>0.25	NEG		
Free Water	scalar	*Visual		NEG		
8:10:40) Rev: 1					Submitted By	: Emylio Pineda



OIL ANALYSIS REPORT



	FLUID PROPER	RTIES	method	limit/base	current	history1	history2
	Visc @ 40°C	cSt	ASTM D445	333	289		
	SAMPLE IMAGI	ES	method	limit/base	current	history1	history2
	Color				no image	no image	no image
	Bottom				no image	no image	no image
	GRAPHS						
	Ferrous Alloys	als		421/veW			
ť.	250						
	150 - Abnormal						



To discuss this sample report, contact Customer Service at 1-800-237-1369. * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Certificate L2367

mdesjarkins@wbwaste.com

T:

F: