

# **OIL ANALYSIS REPORT**

Sample Rating Trend





#### Machine Id VOLVO EC350E 314739 Component Left Travel

Fluid VOLVO PREMIUM GEAR OIL 85W-140 GL-5 (2 GAL)

### DIAGNOSIS

#### Recommendation

Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil.


### Fluid Condition

The condition of the oil is acceptable for the time in service.

Sample Number Sample Date Machine Age Oil Age Oil Changed Sample Status	hrs	Client Info Client Info		ML0001196		
Machine Age Oil Age Oil Changed	hrs	Client Info		WILUUU1196		-
Oil Age Oil Changed	hrs			01 May 2024		
Oil Changed		Client Info		1006		
•	hrs	Client Info		1006		
Comple Status		Client Info		Changed		
Sample Status				NORMAL		
CONTAMINATION		method	limit/base	current	history1	history2
Water		WC Method	>0.25	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>1200	30		
Chromium	ppm	ASTM D5185m	>20	<1		
Nickel	ppm	ASTM D5185m	>5	0		
Titanium	ppm	ASTM D5185m		<1		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>100	2		
Lead	ppm	ASTM D5185m	>50	<1		
Copper	ppm	ASTM D5185m	>50	<1		
Tin	ppm	ASTM D5185m	>5	<1		
Vanadium	ppm	ASTM D5185m		<1		
Cadmium	ppm	ASTM D5185m		<1		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	111	186		
Barium	ppm	ASTM D5185m	0.0	2		
Molybdenum	ppm	ASTM D5185m	0.9	<1		
Manganese	ppm	ASTM D5185m	0.0	<1		
Magnesium	ppm	ASTM D5185m	39	<1		
Calcium	ppm	ASTM D5185m	93	10		
Phosphorus	ppm	ASTM D5185m	920	969		
Zinc	ppm	ASTM D5185m	104	9		
Sulfur	ppm	ASTM D5185m	20179	21372		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>100	3		
Sodium	ppm	ASTM D5185m		<1		
Potassium	ppm	ASTM D5185m	>20	6		
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE		
Yellow Metal	scalar	*Visual	NONE	NONE		
Precipitate	scalar	*Visual	NONE	NONE		
Silt	scalar	*Visual	NONE	NONE		
Debris	scalar	*Visual	NONE	NONE		
Sand/Dirt	scalar	*Visual	NONE	NONE		
Appearance	scalar	*Visual	NORML	NORML		
Odor	scalar	*Visual	NORML	NORML		
Emulsified Water	scalar	*Visual	>0.25	NEG		
Free Water	scalar	*Visual		NEG	 Submitted By	



## **OIL ANALYSIS REPORT**



FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 40°C cSt	ASTM D445	333	302		
SAMPLE IMAGES	method	limit/base	current	history1	history2
Color			no image	no image	no image
Bottom			no image	no image	no image
GRAPHS					
Ferrous Alloys					
25					
20					
ڦِ 15-					
10+					
5					
0					
May1/24		May1/24			
Non-ferrous Metals		2			
9 copper					
8					
6					
Ed 5					
3					
1-					
May1/24 10		May1/24			
		Ma			
Viscosity @ 40°C					
400 - Abnormal		-			
350 Base					
() 300 - 9€ 〒 250 -					
200					
150 - Abnormal					
100					
May1/24		May1/24			
5		-			
: WearCheck USA - 501 Madi				4700 1	RECYCLE
: 06175917 Tes	sted : 13	) May 2024 3 May 2024			AWRENCE & TTSVILLE, M
: 11021970 Dia : CONST	-	May 2024 - S	ean Felton	Contact: MIKE	

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Certificate L2367

mdesjarkins@wbwaste.com

Т:

F: