


OIL ANALYSIS REPORT

Sample Rating Trend



Machine Id

KAESER BSD 50 6859199 (S/N 2097)

Compressor

KAESER SIGMA (OEM) S-460 (--- QTS)

DIAGNOSIS

Recommendation

No corrective action is recommended at this time. The filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is a high amount of particulates present in the oil. Silicon noted.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

		Oct2019 Dec2	020 Jun2021 Mar2022 May2	022 Oct2022 Apr2023 Jul2023 Jan2	024 Apr2024	
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		KC128426	KC122659	KC120607
Sample Date		Client Info		22 Apr 2024	30 Jan 2024	31 Jul 2023
Machine Age	hrs	Client Info		30401	27752	24742
Oil Age	hrs	Client Info		5659	0	0
Oil Changed		Client Info		Not Changd	N/A	N/A
Sample Status				ABNORMAL	ABNORMAL	ABNORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0	0	<1
Chromium	ppm	ASTM D5185m	>10	0	0	0
Nickel	ppm	ASTM D5185m	>3	0	0	0
Titanium	ppm	ASTM D5185m	>3	0	0	0
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum	ppm	ASTM D5185m	>10	0	<1	3
Lead	ppm	ASTM D5185m	>10	0	0	0
Copper	ppm	ASTM D5185m	>50	4	7	7
Tin	ppm	ASTM D5185m	>10	<1	<1	0
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	0
Barium	ppm	ASTM D5185m	90	1	0	0
Molybdenum	ppm	ASTM D5185m		0	0	0
Manganese	ppm	ASTM D5185m		0	<1	0
Magnesium	ppm	ASTM D5185m	90	2	7	<1
Calcium	ppm	ASTM D5185m	2	0	6	0
Phosphorus	ppm	ASTM D5185m		11	18	198
Zinc	ppm	ASTM D5185m		13	0	7
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	<u> </u>	22	△ 61
Sodium	ppm	ASTM D5185m		2	6	<1
Potassium	ppm	ASTM D5185m	>20	0	3	2
Water	%	ASTM D6304	>0.05	0.006	0.012	0.003
ppm Water	ppm	ASTM D6304	>500	66	120	38.1
FLUID CLEANLIN	ESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647		25357	33870	1871
Particles >6µm		ASTM D7647	>1300	△ 6088	<u>▲</u> 10062	606
Particles >14µm		ASTM D7647	>80	▲ 374	△ 365	58
Particles >21µm		ASTM D7647	>20	<u>^</u> 90	4 7	19
Particles >38µm		ASTM D7647	>4	2	3	1
Particles >71µm		ASTM D7647	>3	0	0	0
Oil Cleanliness		ISO 4406 (c)	>/17/13	<u>22/20/16</u>	<u>^</u> 22/21/16	18/16/13
FLUID DEGRADA	TION	method	limit/base	current	history1	history2

Acid Number (AN)

mg KOH/g ASTM D8045 0.4

0.33

0.37

0.26



OIL ANALYSIS REPORT







Certificate 12367

Report Id: TRELAK [WUSCAR] 06176116 (Generated: 05/14/2024 16:00:29) Rev: 1

Laboratory Sample No. Lab Number

: 06176116 Unique Number : 11022169 Test Package : IND 2

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 : KC128426

Received : 10 May 2024 **Tested** : 14 May 2024 Diagnosed

: 14 May 2024 - Doug Bogart

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Contact/Location: Service Manager - TRELAK

TREMRON GROUP

1030 AIRPORT RD

Contact: Service Manager

LAKELAND, FL

US 33802

T:

F: