

OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL

Area Machine fo 003-53775 Component Air Compressor Fluid SULLAIR SULLUBE (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable.


Fluid Condition


The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		SFA0000240		
Sample Date		Client Info		11 Mar 2024		
Machine Age	hrs	Client Info		9127		
Oil Age	hrs	Client Info		1127		
Oil Changed		Client Info		N/A		
Sample Status				NORMAL		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0		
Chromium	ppm	ASTM D5185m	>4	0		
Nickel	ppm	ASTM D5185m	>4	0		
Titanium	ppm	ASTM D5185m		0		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>10	0		
Lead	ppm	ASTM D5185m	>20	0		
Copper	ppm	ASTM D5185m	>40	0		
Tin	ppm	ASTM D5185m	>5	<1		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		<1		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0		
Barium	ppm	ASTM D5185m	745	528		
Molybdenum	ppm	ASTM D5185m	0.0	0		
Manganese	ppm	ASTM D5185m		0		
Magnesium	ppm	ASTM D5185m	0.0	1		
Calcium	ppm	ASTM D5185m	1	2		
Phosphorus	ppm	ASTM D5185m	3	0		
Zinc	ppm	ASTM D5185m	0.1	<1		
Sulfur	ppm	ASTM D5185m	240	270		
CONTAMINANTS	i i	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	<1		
Sodium	ppm	ASTM D5185m		12		
Potassium	ppm	ASTM D5185m	>20	<1		
Water	%	ASTM D6304	>0.6	0.379		
ppm Water	ppm	ASTM D6304	>6000	3790		
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>10000	2241		
Particles >6µm		ASTM D7647	>2500	167		
Particles >14µm		ASTM D7647	>320	15		
Particles >21µm		ASTM D7647	>80	4		
Particles >38µm		ASTM D7647	>20	0		
Particles >71µm		ASTM D7647	>4	0		
Oil Cleanliness		ISO 4406 (c)	>20/18/15	18/15/11		
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	.06	0.40		

SULLAIR.

OIL ANALYSIS REPORT





* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Report Id: SFA604630 [WUSCAR] 06176140 (Generated: 05/16/2024 18:12:17) Rev: 1

Contact/Location: Service Manager - SFA604630

T:

F: