




OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Area

Lumberton NC

Machine Id

KENWORTH TRUCK 135

Component

Diesel Engine

Fluid

GUARD PLUS 15W40 CK9 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION		method	limit/base	current	history1	history2
Sample Number	Client Info			WC0917089	WC0917083	---
Sample Date	Client Info			08 May 2024	08 May 2024	---
Machine Age	mls	Client Info		107131	156971	---
Oil Age	mls	Client Info		20000	6383	---
Oil Changed	Client Info			Changed	Changed	---
Sample Status				NORMAL	NORMAL	---

CONTAMINATION		method	limit/base	current	history1	history2
Fuel	WC Method	>5		<1.0	<1.0	---
Water	WC Method	>0.2		NEG	NEG	---
Glycol	WC Method			NEG	NEG	---

WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>100	21	19	---
Chromium	ppm	ASTM D5185m	>20	<1	<1	---
Nickel	ppm	ASTM D5185m	>4	<1	<1	---
Titanium	ppm	ASTM D5185m		<1	<1	---
Silver	ppm	ASTM D5185m	>3	<1	0	---
Aluminum	ppm	ASTM D5185m	>20	8	5	---
Lead	ppm	ASTM D5185m	>40	<1	<1	---
Copper	ppm	ASTM D5185m	>330	4	3	---
Tin	ppm	ASTM D5185m	>15	1	1	---
Vanadium	ppm	ASTM D5185m		<1	<1	---
Cadmium	ppm	ASTM D5185m		<1	<1	---

ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		21	13	---
Barium	ppm	ASTM D5185m		2	2	---
Molybdenum	ppm	ASTM D5185m		118	94	---
Manganese	ppm	ASTM D5185m		<1	<1	---
Magnesium	ppm	ASTM D5185m		361	148	---
Calcium	ppm	ASTM D5185m		2813	2217	---
Phosphorus	ppm	ASTM D5185m		1621	1179	---
Zinc	ppm	ASTM D5185m		1784	1300	---
Sulfur	ppm	ASTM D5185m		5378	4037	---




CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	16	13	---
Sodium	ppm	ASTM D5185m		2	0	---
Potassium	ppm	ASTM D5185m	>20	12	6	---

INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>3	0.5	0.5	---
Nitration	Abs/cm	*ASTM D7624	>20	11.1	11.8	---
Sulfation	Abs/.1mm	*ASTM D7415	>30	23.6	25.5	---

FLUID DEGRADATION		method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	19.2	20.9	---
Base Number (BN)	mg KOH/g	ASTM D2896		5.8	5.0	---











OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	---
Yellow Metal	scalar	*Visual	NONE	NONE	---
Precipitate	scalar	*Visual	NONE	NONE	---
Silt	scalar	*Visual	NONE	NONE	---
Debris	scalar	*Visual	NONE	NONE	---
Sand/Dirt	scalar	*Visual	NONE	NONE	---
Appearance	scalar	*Visual	NORML	NORML	---
Odor	scalar	*Visual	NORML	NORML	---
Emulsified Water	scalar	*Visual	>0.2	NEG	---
Free Water	scalar	*Visual		NEG	---

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	14.6	14.7	---

GRAPHS



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : WC0917089 **Received** : 10 May 2024
Lab Number : **06176573** **Tested** : 13 May 2024
Unique Number : 11022626 **Diagnosed** : 14 May 2024 - Sean Felton
Test Package : MOB 1 (Additional Tests: TBN)

WOLFPACK TRANSPORTATION
 664 BEN GREEN INDUSTRIAL PARK DRIVE
 ELIZABETHTOWN, NC
 US 28337

To discuss this sample report, contact Customer Service at 1-800-237-1369.

Contact: WESLEY SASSER
wesley.sasser@wolfpacktransportation.com

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

T: (910)874-4046

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: