

OIL ANALYSIS REPORT

Sample Rating Trend

ISO

Machine Id

7402397 (S/N 1579) Component Compressor

Compressor Fluid KAESER SIGMA (OEM) S-460 (--- GAL)

DIAGNOSIS

Recommendation

No corrective action is recommended at this time. The filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is a high amount of particulates present in the oil.


Fluid Condition


The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.


SAMPLE INFORM	ATION	method	limit/base	current	history1	history2
Sample Number		Client Info		KC129199	KC110952	KC107779
Sample Date		Client Info		01 May 2024	23 Nov 2023	04 May 2023
Machine Age	hrs	Client Info		12611	10798	8475
Oil Age	hrs	Client Info		1813	4123	1800
Oil Changed		Client Info		Not Changd	Changed	Not Changd
Sample Status				ABNORMAL	NORMAL	ABNORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0	0	0
Chromium	ppm	ASTM D5185m	>10	0	0	0
Nickel	ppm	ASTM D5185m	>3	0	0	0
Titanium	ppm	ASTM D5185m	>3	0	0	0
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum	ppm	ASTM D5185m	>10	0	0	0
Lead	ppm	ASTM D5185m	>10	0	0	0
Copper	ppm	ASTM D5185m	>50	12	11	5
Tin	ppm	ASTM D5185m	>10	<1	0	0
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	0
Barium	ppm	ASTM D5185m	90	26	0	51
Molybdenum	ppm	ASTM D5185m	50	0	0	0
Manganese	ppm	ASTM D5185m		1	0	0
Magnesium	ppm	ASTM D5185m	90	30	0	53
Calcium	ppm	ASTM D5185m		0	0	<1
Phosphorus	ppm	ASTM D5185m	2	7	0	<1
Zinc	ppm	ASTM D5185m		0	0	3
-				Ū		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	<1	0	0
Sodium	ppm	ASTM D5185m		9	<1	17
Potassium	ppm	ASTM D5185m		1	0	8
Water	%	ASTM D6304		0.018	0.006	0.015
ppm Water	ppm	ASTM D6304	>500	183	70	152.8
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647		69352	1160	12018
Particles >6µm		ASTM D7647	>1300	<u> </u>	323	4467
Particles >14µm		ASTM D7647	>80	<u> </u>	17	4 327
Particles >21µm		ASTM D7647	>20	🔺 158	5	4 6
Particles >38µm		ASTM D7647	>4	1	0	3
Particles >71µm		ASTM D7647	>3	0	0	0
Oil Cleanliness		ISO 4406 (c)	>/17/13	A 23/22/17	17/16/11	1 /19/16
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	0.4	0.36	0.32	0.32





OIL ANALYSIS REPORT














VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.05	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
FLUID PROPERT	IES	method	limit/base	current	history1	history2
	IES cSt	method ASTM D445	limit/base 46	current 44.7	history1 45.1	history2 43.9
FLUID PROPERT	cSt					
FLUID PROPERT Visc @ 40°C	cSt	ASTM D445	46	44.7	45.1	43.9



Report Id: CONMARKC [WUSCAR] 06177153 (Generated: 05/14/2024 19:41:05) Rev: 1

Contact/Location: SERVICE MANAGER - CONMARKC

Page 2 of 2