


OIL ANALYSIS REPORT

Sample Rating Trend



Machine Id

KAESER 8842899

Component Compressor

KAESER SIGMA (OEM) S-460 (--- QTS)

DIAGNOSIS

Recommendation

No corrective action is recommended at this time. The filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is a high amount of particulates present in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

		L	0et2023	Apr2024		
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		KC122182	KC111640	
Sample Date		Client Info		16 Apr 2024	16 Oct 2023	
Machine Age	hrs	Client Info		4673	2300	
Oil Age	hrs	Client Info		0	2300	
Oil Changed		Client Info		N/A	Changed	
Sample Status				ABNORMAL	ABNORMAL	
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0	0	
Chromium	ppm	ASTM D5185m	>10	0	0	
Nickel	ppm	ASTM D5185m	>3	0	<1	
Titanium	ppm	ASTM D5185m	>3	0	0	
Silver	ppm	ASTM D5185m	>2	0	0	
Aluminum	ppm	ASTM D5185m	>10	0	0	
Lead	ppm	ASTM D5185m	>10	0	<1	
Copper	ppm	ASTM D5185m	>50	9	9	
Tin	ppm	ASTM D5185m	>10	<1	0	
Vanadium	ppm	ASTM D5185m		0	0	
Cadmium	ppm	ASTM D5185m		0	0	
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	
Barium	ppm	ASTM D5185m	90	8	0	
Molybdenum	ppm	ASTM D5185m		0	0	
Manganese	ppm	ASTM D5185m		1	0	
Magnesium	ppm	ASTM D5185m	90	22	0	
Calcium	ppm	ASTM D5185m	2	0	0	
Phosphorus	ppm	ASTM D5185m		0	2	
Zinc	ppm	ASTM D5185m		0	0	
CONTAMINANTS	1	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	2	<1	
Sodium	ppm	ASTM D5185m		4	1	
Potassium	ppm	ASTM D5185m	>20	0	<1	
Water	%	ASTM D6304	>0.05	0.012	0.005	
ppm Water	ppm	ASTM D6304	>500	129	56.3	
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647		21452	31620	
Particles >6µm		ASTM D7647	>1300	<u>▲</u> 3705	<u>▲</u> 10756	
Particles >14µm		ASTM D7647	>80	<u>^</u> 202	△ 971	
Particles >21µm		ASTM D7647	>20	<u>^</u> 61	1 99	
Particles >38μm		ASTM D7647	>4	2	4	
Particles >71μm		ASTM D7647		0	0	
Oil Cleanliness		ISO 4406 (c)	>/17/13	<u>22/19/15</u>	<u>22/21/17</u>	
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	0.4	0.36	0.33	



OIL ANALYSIS REPORT





Certificate 12367

Laboratory Sample No.

: KC122182 Lab Number : 06177161 Unique Number : 11023214 Test Package : IND 2

: WearCheck USA - 501 Madison Ave., Cary, NC 27513

Received : 13 May 2024 Tested : 14 May 2024

Diagnosed : 14 May 2024 - Don Baldridge

PE HONDA - PHILLIPSBURG-EASTON HONDA 400 COUNTY RD 519 PHILLIPSBURG, NJ

US 08865

Contact: Service Manager

To discuss this sample report, contact Customer Service at 1-800-237-1369.

 st - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Report Id: PEHPHI [WUSCAR] 06177161 (Generated: 05/14/2024 19:44:06) Rev: 1

Contact/Location: Service Manager - PEHPHI

T:

F: