

## **OIL ANALYSIS REPORT**

AURORA PO-6030 **INGERSOLL RAND PX4930U05101 - INTERGRATED SYSTEMS** 

Component

### Recommendation

Resample at the next service interval to monitor.

#### Wear

Area


All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil.

#### Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.





NORMAL


SAMPLE INFORM	<b>MATION</b>	method	limit/base	current	history1	history2
Sample Number		Client Info		UCP06178913		
Sample Date		Client Info		13 May 2024		
Machine Age	hrs	Client Info		23217		
Oil Age	hrs	Client Info		5000		
Oil Changed		Client Info		Changed		
Sample Status				NORMAL		
CONTAMINATIO	N	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	1		
Chromium	ppm	ASTM D5185m	>10	<1		
Nickel	ppm	ASTM D5185m		<1		
Titanium	ppm	ASTM D5185m		<1		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>25	2		
Lead	ppm	ASTM D5185m	>25	<1		
Copper	ppm	ASTM D5185m	>50	6		
Tin	ppm	ASTM D5185m	>15	<1		
Vanadium	ppm	ASTM D5185m		<1		
Cadmium	ppm	ASTM D5185m		<1		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	1	0		
Barium	ppm	ASTM D5185m	730	183		
Molybdenum	ppm	ASTM D5185m	0	<1		
Manganese	ppm	ASTM D5185m	0.0	<1		
Magnesium	ppm	ASTM D5185m	0	5		
Calcium	ppm	ASTM D5185m	0	9		
Phosphorus	ppm	ASTM D5185m	0	9		
Zinc	ppm	ASTM D5185m	0	12		
Sulfur	ppm	ASTM D5185m	590	884		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	3		
Sodium	ppm	ASTM D5185m		35		
Potassium	ppm	ASTM D5185m	>20	4		
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	0.14	0.144		

Sample Rating Trend



# **OIL ANALYSIS REPORT**

VISUAL



	VISUAL		method	limit/base	current	history1	history2		
	White Metal	scalar	*Visual	NONE	NONE				
	Yellow Metal	scalar	*Visual	NONE	NONE				
	Precipitate	scalar	*Visual	NONE	NONE				
1	Silt	scalar	*Visual	NONE	NONE				
	Debris	scalar	*Visual	NONE	NONE				
1	Sand/Dirt	scalar	*Visual	NONE	NONE				
3/24	Appearance	scalar	*Visual	NORML	NORML				
May13/24	Odor	scalar	*Visual	NORML	NORML				
	Emulsified Water	scalar	*Visual	>0.1	NEG				
	Free Water	scalar	*Visual		NEG				
	FLUID PROPER	TIFS	method	limit/base	current	history1	history2		
	Visc @ 40°C	cSt	ASTM D445	42.8	50.9				
	-								
	SAMPLE IMAGE	S	method	limit/base	current	history1	history2		
May13/24 +	Color				a	no image	no image		
	Bottom					no image	no image		
	Non-ferrous Meta			May13/24					
	Viscosity @ 40°C			May13/24	Acid Number				
Laboratory Sample No. Lab Number Unique Number	: WearCheck USA - 50 : UCP06178913 : 06178913 : 11030239	Rece Teste	ived : 14 ed : 16	7, NC 27513 May 2024 May 2024	Patton:	СН	SOUTH BLV ARLOTTE, N US 2820		
ntificate L2367 Test Package discuss this sample report, Denotes test methods that	<b>o</b> , o								

Report Id: UCPATCHA [WUSCAR] 06178913 (Generated: 05/16/2024 17:25:58) Rev: 1

Đũ

Contact/Location: STEVEN HOUSER - UCPATCHA