

OIL ANALYSIS REPORT

Sample Rating Trend





Machine Id VOLVO A30G 752004 Component Transmission (Auto)

Fluid ATF (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the fluid.


Fluid Condition

The condition of the fluid is acceptable for the time in service.


| SAMPLE INFORMA | | method | limit/base | current | history1 | history2 |
|------------------|------------|----------------------------|------------|---------------------|-------------|---------------|
| | | | innivoase | | , | |
| Sample Number | | Client Info | | ML0001958 | | |
| Sample Date | ara | Client Info Client Info | | 09 May 2024 4233 | | |
| | nrs nrs | Client Info | | 4233 | | |
| - | 115 | Client Info | | 0 Not Changd | | |
| Oil Changed | | Client into | | NORMAL | | |
| Sample Status | | | | NORMAL | | |
| CONTAMINATION | | method | limit/base | current | history1 | history2 |
| Water | | WC Method | >0.1 | NEG | | |
| WEAR METALS | | method | limit/base | current | history1 | history2 |
| lron p | opm | ASTM D5185m | >160 | 75 | | |
| Chromium p | opm | ASTM D5185m | >5 | <1 | | |
| Nickel ß | opm | ASTM D5185m | >5 | 5 | | |
| Titanium ß | opm | ASTM D5185m | | 0 | | |
| Silver p | opm | ASTM D5185m | >5 | 0 | | |
| Aluminum p | opm | ASTM D5185m | >50 | 34 | | |
| Lead p | opm | ASTM D5185m | >50 | <1 | | |
| Copper p | opm | ASTM D5185m | >225 | 40 | | |
| Tin ß | opm | ASTM D5185m | >10 | 8 | | |
| Vanadium p | opm | ASTM D5185m | | 0 | | |
| Cadmium ß | opm | ASTM D5185m | | 0 | | |
| ADDITIVES | | method | limit/base | current | history1 | history2 |
| Boron p | opm | ASTM D5185m | | 32 | | |
| Barium ß | opm | ASTM D5185m | | <1 | | |
| Molybdenum | opm | ASTM D5185m | | <1 | | |
| Manganese p | opm | ASTM D5185m | | 5 | | |
| Magnesium p | opm | ASTM D5185m | | 5 | | |
| Calcium p | opm | ASTM D5185m | | 148 | | |
| Phosphorus | opm | ASTM D5185m | | 253 | | |
| Zinc | opm | ASTM D5185m | | 196 | | |
| Sulfur F | opm | ASTM D5185m | | 1446 | | |
| CONTAMINANTS | | method | limit/base | current | history1 | history2 |
| Silicon | opm | ASTM D5185m | >20 | 12 | | |
| Sodium p | opm | ASTM D5185m | | 11 | | |
| Potassium p | opm | ASTM D5185m | >20 | 2 | | |
| VISUAL | | method | limit/base | current | history1 | history2 |
| White Metal | scalar | *Visual | NONE | NONE | | |
| Yellow Metal | scalar | *Visual | NONE | NONE | | |
| Precipitate | scalar | *Visual | NONE | NONE | | |
| Silt | scalar | *Visual | NONE | NONE | | |
| Debris | scalar | *Visual | NONE | NONE | | |
| Sand/Dirt s | scalar | *Visual | NONE | NONE | | |
| Appearance | scalar | *Visual | NORML | NORML | | |
| Odor | scalar | *Visual | NORML | NORML | | |
| Emulsified Water | scalar | *Visual | >0.1 | NEG | | |
| | scalar | *Visual | | NEG | | |
| :52:46) Rev: 1 | | | Conta | ct/Location: DA | KOTA HARTLE | Y - VOLVO4589 |



OIL ANALYSIS REPORT



| Visc @ 40°C SAMPLE IMAGE Color Bottom GRAPHS Ferrous Alloys | cSt S | ASTM D445 method | 35.0 limit/base | 27.4 current no image | history1 no image | history: no image |
|----------------------------------------------------------------------------|----------|---------------------|--------------------|-----------------------------|----------------------|----------------------|
| Color Bottom GRAPHS Ferrous Alloys | S | method | limit/base | | | |
| Bottom GRAPHS Ferrous Alloys | | | | no image | no image | no image |
| Bottom GRAPHS Ferrous Alloys | | | | no image | no image | no image |
| GRAPHS Ferrous Alloys | | | | | | |
| GRAPHS Ferrous Alloys | | | | no image | no image | no image |
| | | | | no image | no image | no image |
| | | | | | | |
| iron | | | | | | |
| 0 - chromium | | | | | | |
| 0- | | | | | | |
| 0- | | | | | | |
| 0 | | | | | | |
| 0- | | | | | | |
| 0 | | | | | | |
| May9/24 | | | May9/24 | | | |
| | | | Ma | | | |
| Non-ferrous Meta | lls | | _ | | | |
| 5 - copper lead | | | | | | |
| 0 | | | | | | |
| 5 | | | | | | |
| 0 | | | | | | |
| 0- | | | | | | |
| 5 | | | | | | |
| | | ***** | | | | |
| May9/24 | | | May9/24 | | | |
| – Viscosity @ 40°C | | | ~ | | | |
| ⁵ T | | | | | | |
| 0 - Abnormal | | | - | | | |
| 5 - Base | | ***** | | | | |
| 0- | | | | | | |
| | | | | | | |
| 5- | | | | | | |
| 0 - Abnormal | | | - | | | |
| 5 | | | | | | |
| May9/24 | | | May9/24 | | | |
| N | | | × | | | |
| VearCheck USA - 50 | | | NO 07716 | | -LOGAN EQUIPMEN | |



Report Id: VOLVO4589 [WUSCAR] 06179257 (Generated: 05/16/2024 16:52:46) Rev: 1

Contact/Location: DAKOTA HARTLEY - VOLVO4589