


OIL ANALYSIS REPORT

NORMAL

HOTLINE/120 MILL 120 STAND 1A GEN EAST BRG 1415-033-0081

Bearing

ROYAL PURPLE SYNFILM GT 68 (25 GAL)





DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

All component wear rates are normal.

Contamination

The amount and size of particulates present in the system are acceptable. There is no indication of any contamination in the oil.


Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

)		0ct2023	. Apr2023	Dec2023 M	ay2024	
SAMPLE INFORM	1ATION	method	limit/base	current	history1	history2
Sample Number		Client Info		KFS0005153	KFS0002499	KFS0003478
Sample Date		Client Info		10 May 2024	20 Dec 2023	17 Apr 2023
Machine Age	hrs	Client Info		0	0	0
Oil Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	NORMAL	NORMAL
CONTAMINATION	J	method	limit/base	current	history1	history2
Water		WC Method	>2	NEG	NEG	NEG
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>20	3	<1	0
Chromium	ppm	ASTM D5185m	>20	0	<1	0
Nickel	ppm	ASTM D5185m	>20	<1	0	0
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>20	<1	2	0
Lead	ppm	ASTM D5185m	>20	15	15	10
Copper	ppm	ASTM D5185m	>20	<1	<1	<1
Tin	ppm	ASTM D5185m	>20	<1	0	0
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	0
Barium	ppm	ASTM D5185m		<1	0	0
Molybdenum	ppm	ASTM D5185m		0	0	0
Manganese	ppm	ASTM D5185m		<1	0	<1
Magnesium	ppm	ASTM D5185m	90	77	86	88
Calcium	ppm	ASTM D5185m		3	2	2
Phosphorus	ppm	ASTM D5185m		3	31	4
Zinc	ppm	ASTM D5185m		0	0	<1
Sulfur	ppm	ASTM D5185m		22086	20553	22445
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>15	<1	1	0
Sodium	ppm	ASTM D5185m		2	2	2
Potassium	ppm	ASTM D5185m	>20	2	2	<1
FLUID CLEANLIN	ESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>10000	1137	2739	4223
Particles >6µm		ASTM D7647	>2500	149	500	864
Particles >14μm		ASTM D7647	>160	18	43	34
Particles >21µm		ASTM D7647	>40	5	14	9
Particles >38μm		ASTM D7647	>10	1	0	0
Particles >71μm		ASTM D7647	>3	0	0	0
Oil Cleanliness		ISO 4406 (c)	>20/18/14	17/14/11	19/16/13	19/17/12
FLUID DEGRADA	TION	method	limit/base	current	history1	history2



OIL ANALYSIS REPORT







Certificate 12367

Laboratory Sample No.

Lab Number : 06179323

GΩ

55

: KFS0005153 Unique Number : 11030649

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 14 May 2024 Tested : 16 May 2024

Ĕ0.30 흗 0.20 ≥ 0.10

0.00 kg

Diagnosed : 16 May 2024 - Angela Borella Test Package : IND 2 (Additional Tests: PrtCount)

To discuss this sample report, contact Customer Service at 1-800-237-1369. st - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

4805 SECOND STREET MUSCLE SHOALS, AL US 35661

Contact: Joel Even joel.even@constellium.com

T: (256)740-7490

CONSTELLIUM