

FUEL REPORT

Area Bon Secours St Francis East Side [Bon Secours St Francis East Side] DAY 2

Diesel Fuel

No.2 DIESEL FUEL (ULTRALOW SULPHUR) (200 GAL)

DIAGNOSIS

Recommendation

All laboratory tests indicate that this sample meets specifications for No.2 low-sulfur diesel fuel. Please note that this is a corrected copy for diagnostic comment updates.

Corrosion


All metal levels are normal indicating no corrosion in the system.

Contaminants

The water content is negligible. There is no bacteria or fungus (yeast and/or mold) indicated in the sample. The amount and size of particulates present in the system are acceptable.

Fuel Condition

Sulfur value derived by ASTM D5453 method for ULSD validation.



Sample Rating Trend




NORMAL


SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC06179658		
Sample Date		Client Info		06 May 2024		
Machine Age	hrs	Client Info		0		
Sample Status				NORMAL		
PHYSICAL PROP	ERTIES	method	limit/base	current	history1	history2
Fuel Color	text	*Visual Screen	Yllow	Red		
ASTM Color	scalar	*ASTM D1500		L4.5		
Visc @ 40°C	cSt	ASTM D445	3.0	2.53		
Pensky-Martens Flash Point	°C	*PMCC Calculated	52	69.5		
SULFUR CONTE	NT	method	limit/base	current	history1	history2
Sulfur	ppm	ASTM D5185m	10	511		
Sulfur (UVF)	ppm	ASTM D5453		412		
DISTILLATION		method	limit/base	current	history1	history2
Initial Boiling Point	°C	ASTM D86	165	181		
5% Distillation Point	°C	ASTM D86		201		
10% Distill Point	°C	ASTM D86	201	209		
15% Distillation Point	°C	ASTM D86		217		
20% Distill Point	°C	ASTM D86	216	224		
30% Distill Point	°C	ASTM D86	230	237		
40% Distill Point	°C	ASTM D86	243	250		
50% Distill Point	°C	ASTM D86	255	262		
60% Distill Point	°C	ASTM D86	267	275		
70% Distill Point	°C	ASTM D86	280	288		
80% Distill Point	°C	ASTM D86	295	303		
85% Distillation Point	°C	ASTM D86		313		
90% Distill Point	°C	ASTM D86	310	323		
95% Distillation Point	°C	ASTM D86		341		
Final Boiling Point	°C	ASTM D86	341	356		
IGNITION QUALI	ΓY	method	limit/base	current	history1	history2
API Gravity		ASTM D7777	37.7	35		
Cetane Index		ASTM D4737	<40.0	46		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	<1.0	0		
Sodium	ppm	ASTM D5185m	<0.1	<1		
Potassium	ppm	ASTM D5185m	<0.1	0		
Water	%	ASTM D6304	<0.05	0.004		
ppm Water	ppm	ASTM D6304	<500	48		
% Gasoline	%	*In-House	<0.50	0.0		
% Biodiesel	%	*In-House	<20.0	0.0		




FUEL REPORT


	ticle Cou	nt			
491,520 T					T ²⁶
122,880 -					-24
30,720 Severe					-22 8
7,680 Abnom	nal				-20 ह
7,680 480 120 30 8					-22 0 70 -20 70 -18 22 -16 0 -14 11 -12 25 -10 00
480 -					-16 5
120-					-14
30-					-12 %
8 -					-10 a
2					+8
2 -					
0 _{4µ}	^{6μ} ter (KF)	14μ	21µ	38µ	71µ
₀ ₄µ Wa	ter (KF)	14µ	21µ	38µ	71µ
04µ Wa 1200 1000 - Seve	ter (KF)	14μ	21µ	38µ	71µ
04µ Wa 1200 1000 - Seve	ter (KF) ne	14µ	21µ	38µ	71µ
04/4/2 1200 1000 - Seve 1000 - Seve 1000 - Seve 1000 - Seve 1000 - Seve	ter (KF) ne	14μ	21µ	38µ	71µ
04µµ 1200 1000 800 600 400 400	ter (KF) ne	14µ	21μ	38µ	
04/4/2 1200 1000 - Seve 1000 - Seve 1000 - Seve 1000 - Seve 1000 - Seve	ter (KF) ne	14µ	21μ	38µ	
04 Wa 1200 1000 800 800 400 200 0 400 0 0 0 0 0 0 0 0 0 0 0 0	ter (KF) ne	14µ	21µ	38µ	πμ
04 Wa 1200 1000 800 600 400 200	ter (KF) ne	14μ	21µ	38µ	6 71µ +229beW





FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2	
Particles >4µm		ASTM D7647	>2500	1341			
Particles >6µm		ASTM D7647	>640	400			
Particles >14µm		ASTM D7647	>80	49			
Particles >21µm		ASTM D7647	>20	15			
Particles >38µm		ASTM D7647	>4	1			
Particles >71µm		ASTM D7647	>3	0			
Oil Cleanliness		ISO 4406 (c)	>18/16/13	18/16/13			
HEAVY METALS		method	limit/base	current	history1	history2	
Aluminum	ppm	ASTM D5185m	<0.1	0			
Nickel	ppm	ASTM D5185m	<0.1	0			
Lead	ppm	ASTM D5185m	<0.1	0			
Vanadium	ppm	ASTM D5185m	<0.1	0			
Iron	ppm	ASTM D5185m	<0.1	0			
Calcium	ppm	ASTM D5185m	<0.1	<1			
Magnesium	ppm	ASTM D5185m	<0.1	0			
Phosphorus	ppm	ASTM D5185m	<0.1	<1			
Zinc	ppm	ASTM D5185m	<0.1	0			
SAMPLE IMAGES	6	method	limit/base	current	history1	history2	
Color					no image	no image	
Bottom					no image	no image	
GRAPHS							
Fuel Distillation Curve Pensky-Martens Flash Point (°C)							
80-							







PETROLEUM RECOVERY SERVICES Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513 Sample No. : WC06179658 Received 210 POWELL DR : 14 May 2024 Lab Number : 06179658 Tested : 20 May 2024 SUMMERVILLE, SC Unique Number : 11030984 Diagnosed : 20 May 2024 - Doug Bogart US 29483 Test Package : DF-2 (Additional Tests: Fuel, Screen) Contact: AJAY EL Certificate 12367 To discuss this sample report, contact Customer Service at 1-800-237-1369. Ajay@prsfuel.com * - Denotes test methods that are outside of the ISO 17025 scope of accreditation. T: (843)225-1777 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Report Id: PETSUM [WUSCAR] 06179658 (Generated: 05/27/2024 12:57:50) Rev: 1

Contact/Location: AJAY EL - PETSUM

Page 2 of 2

F: