

FUEL REPORT

Area **Prisma Heath Baptist Property Services** [Prisma Heath Baptist Property Services] FIRE PUMP

Diesel Fuel

Fluid No.2 DIESEL FUEL (ULTRALOW SULPHUR) (150 GAL)

DIAGNOSIS

Recommendation

All laboratory tests indicate that this sample meets specifications for No.2 ultra-low-sulfur diesel fuel. Please note that this is a corrected copy for diagnostic comment updates.

Corrosion


All metal levels are normal indicating no corrosion in the system.

Contaminants

The water content is negligible. There is no bacteria or fungus (yeast and/or mold) indicated in the sample. The amount and size of particulates present in the system are acceptable.

Fuel Condition

Sulfur value derived by ASTM D5453 method for ULSD validation. Sulfur level is acceptable for ULSD specification.



Sample Rating Trend



SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC06179661		
Sample Date		Client Info		08 May 2024		
Machine Age	hrs	Client Info		0		
Sample Status				NORMAL		
PHYSICAL PROP	ERTIES	method	limit/base	current	history1	history2
Fuel Color	text	*Visual Screen	Yllow	Red		
ASTM Color	scalar	*ASTM D1500		L4.0		
Visc @ 40°C	cSt	ASTM D445	3.0	2.42		
Pensky-Martens Flash Point	°C	*PMCC Calculated	52	59.5		
SULFUR CONTEI	NT	method	limit/base	current	history1	history2
Sulfur	ppm	ASTM D5185m	10	0		
Sulfur (UVF)	ppm	ASTM D5453		9		
DISTILLATION		method	limit/base	current	history1	history2
Initial Boiling Point	°C	ASTM D86	165	170		
5% Distillation Point	°C	ASTM D86		192		
10% Distill Point	°C	ASTM D86	201	202		
15% Distillation Point	°C	ASTM D86		210		
20% Distill Point	°C	ASTM D86	216	217		
30% Distill Point	°C	ASTM D86	230	232		
40% Distill Point	°C	ASTM D86	243	246		
50% Distill Point	°C	ASTM D86	255	259		
60% Distill Point	°C	ASTM D86	267	273		
70% Distill Point	°C	ASTM D86	280	288		
80% Distill Point	°C	ASTM D86	295	304		
85% Distillation Point	°C	ASTM D86		315		
90% Distill Point	°C	ASTM D86	310	326		
95% Distillation Point	°C	ASTM D86		345		
Final Boiling Point	°C	ASTM D86	341	359		
IGNITION QUALI	ΓY	method	limit/base	current	history1	history2
API Gravity		ASTM D7777	37.7	37		
Cetane Index		ASTM D4737	<40.0	48		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	<1.0	0		
Sodium	ppm	ASTM D5185m	<0.1	<1		
Potassium	ppm	ASTM D5185m	<0.1	0		
Water	%	ASTM D6304	< 0.05	0.004		
ppm Water	ppm	ASTM D6304	<500	45		
% Gasoline	%	*In-House	<0.50	0.0		
% Biodiesel	%	*In-House	<20.0	0.0		



FUEL REPORT

ppm

ppm

ppm

ppm

ppm

ppm

ppm

ppm

ppm

ASTM D7647

ASTM D7647 >640

ASTM D7647 >80

ASTM D7647 >20

ASTM D7647 >4

ASTM D7647 >3

ASTM D5185m

ASTM D5185m

ASTM D5185m

ASTM D5185m

ASTM D5185m

ASTM D5185m

ASTM D5185m <0.1

ASTM D5185m <0.1

ASTM D5185m <0.1

ISO 4406 (c) >18/16/13

< 0.1

< 0.1

< 0.1

<0.1

< 0.1

< 0.1

>2500

FLUID CLEANLINESS

Particles >4µm Particles >6um

Particles >14µm

Particles >21µm

Particles >38µm

Particles >71µm

Oil Cleanliness

Aluminum

Vanadium

Calcium

Magnesium

Phosphorus

SAMPLE IMAGES

Nickel

Lead

Iron

Zinc


Color


Bottom

HEAVY METALS

$\begin{array}{c} 22,880\\ 30,720\\ \\ 30,720\\ \\ 480\\ \\ 1,920\\ \\ 480\\ \\ 1,920\\ \\ 480\\ \\ 1,920\\ \\ 480\\ \\ 0\\ \\ 4\mu\\ \\ 6\mu\\ \\ 1,920\\ \\ 480\\ \\ 0\\ \\ 4\mu\\ \\ 6\mu\\ \\ 1,920\\ \\ 4\mu\\ \\ 6\mu\\ \\ 1,920\\ \\ 4\mu\\ \\ 1,920\\ \\ 6\mu\\ \\ 1,920\\ \\ 1$		ticle Cou	unt			
$ \frac{1}{200} \frac{1}{400} \frac{1}{40} \frac{1}{400} \frac{1}{40} \frac{1}{400} \frac{1}{40} \frac{1}{400} \frac{1}{40} \frac$	191,520					T ²⁶
7.680 1.920 480 1.920 1.920 480 1.9200 1.920 1.920 1.920 1.920 1.9200 1.9200 1.920 1.9200	Section 2. Section 2.					
$Water (KF)$ $\frac{1200}{400} - \frac{14\mu}{14\mu} - \frac{14\mu}{21\mu} - \frac{16}{38\mu} - \frac{16}{71\mu}$ $Water (KF)$ $\frac{1200}{400} - \frac{16}{14\mu} - \frac{16}{14\mu}$	T					
$Water (KF)$ $\frac{1200}{400} - \frac{14\mu}{14\mu} - \frac{14\mu}{21\mu} - \frac{16}{38\mu} - \frac{16}{71\mu}$ $Water (KF)$ $\frac{1200}{400} - \frac{16}{14\mu} - \frac{16}{14\mu}$	Abnor	mal				+20 g
$Water (KF)$ $\frac{1200}{400} - \frac{14\mu}{14\mu} - \frac{14\mu}{21\mu} - \frac{16}{38\mu} - \frac{16}{71\mu}$ $Water (KF)$ $\frac{1200}{400} - \frac{16}{14\mu} - \frac{16}{14\mu}$			1.1			18 2
$Water (KF)$ $\frac{1200}{400} - \frac{14\mu}{14\mu} - \frac{14\mu}{21\mu} - \frac{16}{38\mu} - \frac{16}{71\mu}$ $Water (KF)$ $\frac{1200}{400} - \frac{16}{14\mu} - \frac{16}{14\mu}$		1				+16 Cea
$Water (KF)$ $\frac{1200}{400} - \frac{14\mu}{14\mu} - \frac{14\mu}{21\mu} - \frac{16}{38\mu} - \frac{16}{71\mu}$ $Water (KF)$ $\frac{1200}{400} - \frac{16}{14\mu} - \frac{16}{14\mu}$			1			14 8
$\frac{2}{4} \underbrace{\frac{1}{4\mu}}_{0} \underbrace{\frac{1}{4\mu}}_{0} \underbrace{\frac{1}{4\mu}}_{1} \underbrace{\frac{1}{2}}_{1} \underbrace{\frac{1}{3}}_{3} \underbrace{\frac{1}{4\mu}}_{1} \underbrace{\frac{1}{4\mu}}_{1} \underbrace{\frac{1}{4\mu}}_{3} \underbrace{\frac{1}{4\mu}}_{1} \underbrace{\frac{1}$	100 A 100 A					12 %
Water (KF) Water (KF) 1200 400 400 400 400 400 400 400 400 400 400 400 400 400 500	22		-			
Water (KF)						
Water (KF)	0. 4μ	6µ	14µ	21µ	38µ	71µ
^{52 gylew} Viscosity @ 40°C	600 - Abn 400 -	ormal				
Viscosity @ 40°C						4
6 T	May8/2					May8/2
6 T	Vis	cosity @	40°C			
5		,				
	6 T					







no image no image Pensky-Martens Flash Point (°C)

no image

no image

691

95

9

2

0

0

0

0

0

0

0


0

0

<1

0

17/14/10





Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513 PETROLEUM RECOVERY SERVICES Sample No. : WC06179661 Received : 14 May 2024 210 POWELL DR Lab Number : 06179661 Tested : 20 May 2024 SUMMERVILLE, SC Unique Number : 11030987 Diagnosed : 20 May 2024 - Doug Bogart US 29483 Test Package : DF-2 (Additional Tests: Fuel, Screen) Contact: AJAY EL Certificate 12367 To discuss this sample report, contact Customer Service at 1-800-237-1369. Ajay@prsfuel.com * - Denotes test methods that are outside of the ISO 17025 scope of accreditation. T: (843)225-1777 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Report Id: PETSUM [WUSCAR] 06179661 (Generated: 05/27/2024 14:25:03) Rev: 1

Contact/Location: AJAY EL - PETSUM

Page 2 of 2

E: