


OIL ANALYSIS REPORT

Sample Rating Trend



Machine Id

7608232 (S/N 1141)

Compressor

KAESER SIGMA (OEM) S-460 (--- GAL)

Recommendation

No corrective action is recommended at this time. The filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is a moderate amount of particulates present in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

		Mar202	3 Aug2023	Feb 2024 Ma	y2024	
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		KCPA017804	KCP36776	KCPA003843
Sample Date		Client Info		09 May 2024	09 Feb 2024	10 Aug 2023
Machine Age	hrs	Client Info		10992	9161	6745
Oil Age	hrs	Client Info		4064	2416	0
Oil Changed		Client Info		Not Changd	Not Changd	N/A
Sample Status				ATTENTION	ATTENTION	NORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	<1	0	0
Chromium	ppm	ASTM D5185m	>10	<1	<1	0
Nickel	ppm	ASTM D5185m	>3	<1	0	0
Titanium	ppm	ASTM D5185m	>3	<1	0	0
Silver	ppm	ASTM D5185m	>2	<1	0	0
Aluminum	ppm	ASTM D5185m	>10	2	1	0
Lead	ppm	ASTM D5185m	>10	<1	0	0
Copper	ppm	ASTM D5185m	>50	8	3	10
Tin	ppm	ASTM D5185m	>10	<1	0	<1
Vanadium	ppm	ASTM D5185m		<1	0	0
Cadmium	ppm	ASTM D5185m		<1	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	0
Barium	ppm	ASTM D5185m	90	0	3	2
Molybdenum	ppm	ASTM D5185m		<1	0	0
Manganese	ppm	ASTM D5185m		0	0	0
Magnesium	ppm	ASTM D5185m	90	<1	4	<1
Calcium	ppm	ASTM D5185m	2	<1	0	0
Phosphorus	ppm	ASTM D5185m		2	<1	4
Zinc	ppm	ASTM D5185m		0	0	0
Sulfur	ppm	ASTM D5185m		25354	17233	17638
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	1	0	<1
Sodium	ppm	ASTM D5185m		2	0	0
Potassium	ppm	ASTM D5185m	>20	2	2	0
Water	%	ASTM D6304	>0.05	0.007	0.005	0.008
ppm Water	ppm	ASTM D6304	>500	73	53	83.8
FLUID CLEANLIN	ESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647		6664	2640	182
Particles >6µm		ASTM D7647	>1300	<u>2127</u>	760	67
Particles >14µm		ASTM D7647	>80	111	87	16
Particles >21µm		ASTM D7647	>20	19	22	3
Particles >38µm		ASTM D7647	>4	0	1	0
Particles >71µm		ASTM D7647	>3	0	0	0
Oil Cleanliness		ISO 4406 (c)	>/17/13	20/18/14	19/17/14	15/13/11
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	0.4	0.45	0.46	0.47



OIL ANALYSIS REPORT







Certificate 12367

Laboratory Sample No.

: KCPA017804 Lab Number : 06180701 Unique Number : 11032027

Test Package : IND 2 (Additional Tests: KF, PrtCount)

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 15 May 2024 **Tested** : 18 May 2024

Diagnosed

: 18 May 2024 - Jonathan Hester

US 43701 Contact: Service Manager

3400 E POINTE DR

ZANESVILLE, OH

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:

F: