

## **OIL ANALYSIS REPORT**

Sample Rating Trend



Machine Id

# 8661337 (S/N 2899) Compressor

### Fluid KAESER SIGMA (OEM) M-460 (--- GAL)

#### Recommendation

Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable.


#### Fluid Condition


The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.


SAMPLE INFORM	<b>MATION</b>	method	limit/base	current	history1	history2
Sample Number		Client Info		KCPA017207		
Sample Date		Client Info		03 May 2024		
Machine Age	hrs	Client Info		3557		
Oil Age	hrs	Client Info		3557		
Oil Changed		Client Info		Changed		
Sample Status				NORMAL		
					_	_
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	1		
Chromium	ppm	ASTM D5185m	>10	<1		
Nickel	ppm	ASTM D5185m	>3	<1		
Titanium	ppm	ASTM D5185m	>3	<1		
Silver	ppm	ASTM D5185m	>2	<1		
Aluminum	ppm	ASTM D5185m	>10	2		
Lead	ppm	ASTM D5185m	>10	- <1		
Copper	ppm	ASTM D5185m		9		
Tin	ppm		>10	ء <1		
Vanadium	ppm	ASTM D5185m	- 10	<1		
Cadmium	ppm	ASTM D5185m		<1		
	ррпі	ASTIVI DUTOJIII				
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	0		
Barium	ppm	ASTM D5185m	90	<1		
Molybdenum	ppm	ASTM D5185m	0	<1		
Manganese	ppm	ASTM D5185m		0		
Magnesium	ppm	ASTM D5185m	100	10		
Calcium	ppm	ASTM D5185m	0	<1		
Phosphorus	ppm	ASTM D5185m	0	2		
Zinc	ppm	ASTM D5185m	0	20		
Sulfur	ppm	ASTM D5185m	23500	21431		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	7		
Sodium	ppm	ASTM D5185m		23		
Potassium	ppm	ASTM D5185m	>20	16		
Water	%	ASTM D6304	>0.05	0.012		
ppm Water	ppm	ASTM D6304	>500	126		
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647		812		
Particles >6µm		ASTM D7647	>1300	183		
Particles >14µm		ASTM D7647	>80	3		
Particles >21µm		ASTM D7647	>20	2		
Particles >38µm		ASTM D7647	>4	0		
Particles >71µm		ASTM D7647	>3	0		
Oil Cleanliness		ISO 4406 (c)	>/17/13	17/15/9		
FLUID DEGRADA		method	limit/base	current	history1	history2
					- matory i	
Acid Number (AN)	mg KOH/g	ASTM D8045	1.0	0.35		




## **OIL ANALYSIS REPORT**









To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Certificate 12367

Laboratory

Sample No.

Contact/Location: J. MORALES - VERNEWOH

jmorales@axiumplastics.com

T:

F: