

OIL ANALYSIS REPORT

Area ENGINE ROOM 2 Machine to ER2 BO106 (S/N F0066ZFMCTHGA03)

Refrigeration Compressor

USPI 1009-68 SC (130 GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear


All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.



SAMPLE INFORM	1ATION	method	limit/base	current	history1	history2
Sample Number		Client Info		USP0011815	USP0006860	USP0004065
Sample Date		Client Info		14 May 2024	15 Feb 2024	22 Nov 2023
Machine Age	hrs	Client Info		62809	62129	61520
Oil Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	NORMAL	NORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>8	0	0	0
Chromium	ppm	ASTM D5185m	>2	<1	0	<1
Nickel	ppm	ASTM D5185m		0	<1	0
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum	ppm	ASTM D5185m	>3	0	0	<1
Lead	ppm	ASTM D5185m	>2	0	0	0
Copper	ppm	ASTM D5185m	>8	<1	0	0
Tin	ppm	ASTM D5185m	>4	0	<1	0
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	0
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		0	0	0
Manganese	ppm	ASTM D5185m		0	0	0
Magnesium	ppm	ASTM D5185m		0	0	0
Calcium	ppm	ASTM D5185m		0	0	<1
Phosphorus	ppm	ASTM D5185m		0	0	0
Zinc	ppm	ASTM D5185m		0	0	0
Sulfur	ppm	ASTM D5185m	50	0	24	<1
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>15	0	0	<1
Sodium	ppm	ASTM D5185m		<1	<1	0
Potassium	ppm	ASTM D5185m	>20	0	0	<1
Water	%	ASTM D6304		0.003	0.003	0.001
ppm Water	ppm	ASTM D6304	>100	29	26	0
FLUID CLEANLIN	ESS	method	limit/base		history1	history2
Particles >4µm		ASTM D7647	>10000	1889	5953	3274
Particles >6µm		ASTM D7647	>2500	487	1687	1188
Particles >14µm		ASTM D7647	>320	14	58	52
Particles >21µm		ASTM D7647	>80	4	9	11
Particles >38µm		ASTM D7647	>20	0	0	1
Particles >71µm		ASTM D7647	>4	0	0	0
Oil Cleanliness		ISO 4406 (c)	>20/18/15	18/16/11	20/18/13	19/17/13
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
	m = 1/011/=		0.005	0.014	0.014	0.014

Acid Number (AN)

mg KOH/g ASTM D974 0.005

Contact/Location: MIKE WEAVER - CONTROUSP Page 1 of 2


0.014


0.014


0.014





OIL ANALYSIS REPORT












VISUAL		method				history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	LIGHT	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.01	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
FLUID PROPERTIES		method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	67	68.6	68.2	67.6
SAMPLE IMAGES me		method	limit/base	current	history1	history2
Color				0		
						101

Bottom



Test Package : IND 2

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Report Id: CONTROUSP [WUSCAR] 06181399 (Generated: 05/20/2024 11:47:14) Rev: 1

Certificate 12367

Contact/Location: MIKE WEAVER - CONTROUSP

Т:

F:

Contact: MIKE WEAVER

mike.weaver@conagrafoods.com