

# **OIL ANALYSIS REPORT**

Sample Rating Trend





Machine Id VOLVO A25G 752910

Component Front Left Final Drive

Fluid VOLVO SUPER GEAR OIL 75W-80-GO102 (--- GAL)

### DIAGNOSIS

#### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil.


## Fluid Condition

The condition of the oil is acceptable for the time in service.


SAMPLE INFORM	IATION	method	limit/base	current	history1	history2				
Sample Number		Client Info		ML0001777						
Sample Date		Client Info		13 May 2024						
Machine Age	hrs	Client Info		496						
Oil Age	hrs	Client Info		496						
Oil Changed		Client Info		Changed						
Sample Status				NORMAL						
CONTAMINATION	J	method	limit/base	current	history1	history2				
Water	v	WC Method	>0.2	NEG						
WEAR METALS		method	limit/base	current	history1	history2				
Iron	ppm	ASTM D5185m	>900	146						
Chromium	ppm	ASTM D5185m	>20	4						
Nickel	ppm	ASTM D5185m	>10	2						
Titanium	ppm	ASTM D5185m		<1						
Silver	ppm	ASTM D5185m		<1						
Aluminum	ppm	ASTM D5185m	>30	2						
Lead	ppm	ASTM D5185m	>50	- <1						
Copper	ppm	ASTM D5185m	>150	17						
Tin	ppm	ASTM D5185m	>20	1						
Vanadium	ppm	ASTM D5185m		<1						
Cadmium	ppm	ASTM D5185m		<1						
ADDITIVES		method	limit/base	current	history1	history2				
Boron	ppm	ASTM D5185m		316						
Barium	ppm	ASTM D5185m		3						
Molybdenum	ppm	ASTM D5185m		7						
Manganese	ppm	ASTM D5185m		12						
Magnesium	ppm	ASTM D5185m		3						
Calcium	ppm	ASTM D5185m		179						
Phosphorus	ppm	ASTM D5185m		1611						
Zinc	ppm	ASTM D5185m		87						
Sulfur	ppm	ASTM D5185m		29998						
CONTAMINANTS		method	limit/base	current	history1	history2				
Silicon	ppm	ASTM D5185m	>50	6						
Sodium	ppm	ASTM D5185m		0						
Potassium	ppm	ASTM D5185m	>20	5						
VISUAL		method	limit/base	current	history1	history2				
White Metal	scalar	*Visual	NONE	NONE						
Yellow Metal	scalar	*Visual	NONE	NONE						
Precipitate	scalar	*Visual	NONE	NONE						
Silt	scalar	*Visual	NONE	LIGHT						
Debris	scalar	*Visual	NONE	NONE						
Sand/Dirt	scalar	*Visual	NONE	NONE						
Appearance	scalar	*Visual	NORML	NORML						
Odor	scalar	*Visual	NORML	NORML						
Emulsified Water	scalar	*Visual	>0.2	NEG						
Free Water	scalar	*Visual		NEG						
				0.1	Submitted By: Service - Alex Anderson					



# **OIL ANALYSIS REPORT**



FLUID PROPERTIE	S method	limit/base	current	history1	history
Visc @ 40°C	St ASTM D445		102		
SAMPLE IMAGES	method	limit/base	current	history1	history
Color			no image	no image	no image
Bottom			no image	no image	no image
GRAPHS					
Ferrous Alloys					
140 - iron chromium					
120-					
100-					
E 80 − 60 −					
40					
20 -					
24 0					
May13/24		May13/24			
Non-ferrous Metals		2			
18 16					
14					
12					
6					
4					
2					
May13/24		May13/24			
≝ Viscosity @ 40°C		Mar			
95					
90 - Abnormal		-			
(J. 85					
(2) 05 (1) 05 (					
70					
65 60 <b>Abnormal</b>					
55 4		24			
May13/24		May13/24			
_		_			
: WearCheck USA - 501 M : ML0001777 : 06181762	Received : 16 Tested : 17	May 2024 May 2024			JNTAIN RO EN ALLEN
: 11033088 : CONST	Diagnosed : 20	May 2024 - Se	ean Felton	Contact:	US 23 Alex Ander
contact Customer Service	at 1-800-237-1369		a	anderson@mccl	



\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012) F: (804)266-1611

Certificate L2367

Submitted By: Service - Alex Anderson Page 2 of 2

aanderson@mcclung-logan.com

Т: