

VIS DEBRIS



OIL ANALYSIS REPORT

Machine Id

KAESER SK 15T 8368276 (S/N 1443)

Component Compressor Fluid

KAESER SIGMA (OEM) S-460 (--- GAL)

DIAGNOSIS

Recommendation

No corrective action is recommended at this time. The filter change at the time of sampling has been noted. Resample at the next service interval to monitor. We were unable to perform a particle count due to a high concentration of particles present in this sample.

Wear

All component wear rates are normal.

Contamination

Moderate concentration of visible dirt/debris present in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORM		method	limit/base	current	history1	history2
Sample Number		Client Info		KC06182030	KC125274	
Sample Date		Client Info		25 Apr 2024	24 Aug 2023	
Machine Age	hrs	Client Info		8471	5677	
Oil Age	hrs	Client Info		0	0	
Oil Changed		Client Info		N/A	N/A	
Sample Status				ABNORMAL	ATTENTION	
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0	0	
Chromium	ppm	ASTM D5185m	>10	<1	0	
Nickel	ppm	ASTM D5185m	>3	0	0	
Titanium	ppm	ASTM D5185m	>3	0	0	
Silver	ppm	ASTM D5185m	>2	<1	0	
Aluminum	ppm	ASTM D5185m	>10	<1	<1	
Lead	ppm	ASTM D5185m	>10	<1	0	
Copper	ppm	ASTM D5185m	>50	9	2	
Tin	ppm	ASTM D5185m	>10	0	0	
Vanadium	ppm	ASTM D5185m		<1	0	
Cadmium	ppm	ASTM D5185m		0	0	
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	
Barium	ppm	ASTM D5185m	90	0	0	
Molybdenum	ppm	ASTM D5185m		0	0	
Manganese	ppm	ASTM D5185m		0	0	
Magnesium	ppm	ASTM D5185m	90	15	64	
Calcium	ppm	ASTM D5185m	2	0	<1	
Phosphorus	ppm	ASTM D5185m		0	0	
Zinc	ppm	ASTM D5185m		0	0	
CONTAMINANTS	;	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	<1	0	
Sodium	ppm	ASTM D5185m		6	13	
Potassium	ppm	ASTM D5185m	>20	3	4	
Water	%	ASTM D6304	>0.05	0.013	0.025	
ppm Water	ppm	ASTM D6304	>500	139	251.4	
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647			3233	
Particles >6µm		ASTM D7647	>1300		1043	
Particles >14µm		ASTM D7647	>80		96	
Particles >21µm		ASTM D7647	>20		33	
Particles >38µm		ASTM D7647	>4		1	
Particles >71µm		ASTM D7647	>3		0	
Oil Cleanliness		ISO 4406 (c)	>/17/13		9/17/14	
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	0.4	0.34	0.34	



12000 Se

10000

8000 Water (ppm)

4000

2000

10000.

8000 Water (ppm)

50 48 cSt (40°C)

W 12000

OIL ANALYSIS REPORT

Water (KF)		VISUAL		method	limit/base	current	history1
0000 - Severe		White Metal	scalar	*Visual	NONE	NONE	NONE
8000 -		Yellow Metal	scalar	*Visual	NONE	NONE	NONE
6000		Precipitate	scalar	*Visual	NONE	NONE	NONE
4000 -		Silt	scalar	*Visual	NONE	NONE	NONE
2000 -		Debris	scalar	*Visual	NONE	A MODER	NONE
Abnormal		Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Аиg24/23	Apr25/24	Appearance	scalar	*Visual	NORML	NORML	NORML
Aug	Apı	Odor	scalar	*Visual	NORML	NORML	NORML
Water (KF)		Emulsified Water	scalar	*Visual	>0.05	NEG	NEG
2000		Free Water	scalar	*Visual		NEG	NEG
0000 - G		FLUID PROPER	TIES	method	limit/base	current	history1
8000		Visc @ 40°C	cSt	ASTM D445	46	44.2	43.9
4000-		SAMPLE IMAGE	S	method	limit/base	current	history1
2000							
O Abnormal	Apr25/24	Color					•
Viscosity @ 40°C		Bottom					
() 46 - Base 37 44		GRAPHS					
경 ⁴⁴		Ferrous Alloys					
40 - Abnormal		10					
38		o - chromium					
Aug24/23	1 J C~~						
A	~	2					
					4		
		Aug24/23			Apr25/24		
		Non-ferrous Meta	le		A		
		8 - copper					
		E 6					
		4					
		0					
		Aug24/23			Apr25/24		
					Api		
		Viscosity @ 40°C				Acid Number	
		Abnormal			(B)HO	Base	
					<u><u></u><u></u><u></u><u></u><u></u><u></u><u></u><u></u><u></u><u></u><u></u><u></u><u></u><u></u><u></u><u></u><u></u><u></u><u></u></u>		
		G 0 0 0 0 0 0 0 0 0 0 0 0 0				0	
		40 -			0.5 (0)H004 (0)H004 (0.2 (0.0 (0.0 (0.0 (0.0 (0.0)) (0.0)) (0.0) (0.0) (0.0) (0.0) (0.0) (0.0) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0.1) (0-	
		35			0.0 V 0.0		
		Aug24/23			Apr25/24	Aug24/23	
	Sample No. Lab Number		Rece Teste	ived : 16 ed : 20	6 May 2024 9 May 2024	n Baldridge	PDQ - E
AND NAMES AND	Unique Number Test Package		Diagr	nosed : 20	May 2024 - Do	n Baldridge	Contact: SI

Report Id: PDQDAY [WUSCAR] 06182030 (Generated: 05/20/2024 13:17:18) Rev: 1

Certificate L2367

Test Package : IND 2

To discuss this sample report, contact Customer Service at 1-800-237-1369. * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Contact/Location: SERVICE MANAGER ? - PDQDAY

Apr25/24

T:

F:

history2

history2

history2

no image

no image