

OIL ANALYSIS REPORT



Machine Id

FREIGHTLINER 530

Diesel Engine Fluid DIESEL ENGINE OIL SAE 15W40 (--- GAL)

DIAGNOSIS

Recommendation

We advise that you check the fuel injection system. The oil is near the end of it's useful service life, recommend schedule an oil change. We recommend an early resample to monitor this condition.

Wear

All component wear rates are normal.

Contamination

There is a high amount of fuel present in the oil. Tests confirm the presence of fuel in the oil.

Fluid Condition

Calcium ppm levels are abnormally low. Visc @ 100°C is abnormally low. The BN result indicates that there is suitable alkalinity remaining in the oil. Fuel is present in the oil and is lowering the viscosity. The oil is no longer serviceable due to the presence of contaminants.

SAMPLE INFORM	1ATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0905973		
Sample Date		Client Info		10 May 2024		
Machine Age	mls	Client Info		284007		
Oil Age	mls	Client Info		0		
Oil Changed		Client Info		Not Changd		
Sample Status				SEVERE		
CONTAMINATION	J	method	limit/base	current	history1	history2
Water		WC Method	>0.2	NEG		
Glycol		WC Method	20.L	NEG		
,				NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>80	61		
Chromium	ppm	ASTM D5185m	>5	3		
Nickel	ppm	ASTM D5185m	>2	0		
Titanium	ppm	ASTM D5185m		0		
Silver	ppm	ASTM D5185m	>3	0		
Aluminum	ppm	ASTM D5185m	>30	4		
Lead	ppm	ASTM D5185m	>30	0		
Copper	ppm	ASTM D5185m	>150	2		
Tin	ppm	ASTM D5185m	>5	<1		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	250	5		
Boron Barium	ppm ppm	ASTM D5185m ASTM D5185m	250 10	5 0		
Barium	ppm	ASTM D5185m	10	0		
Barium Molybdenum	ppm ppm	ASTM D5185m ASTM D5185m	10	0 51		
Barium Molybdenum Manganese	ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m	10 100	0 51 1		
Barium Molybdenum Manganese Magnesium	ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	10 100 450	0 51 1 757 ▲ 853 826	 	
Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc	ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	10 100 450 3000	0 51 1 757 ▲ 853	 	
Barium Molybdenum Manganese Magnesium Calcium Phosphorus	ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	10 100 450 3000 1150	0 51 1 757 ▲ 853 826	 	
Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc	ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	10 100 450 3000 1150 1350	0 51 1 757 ▲ 853 826 976	 	
Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur	ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	10 100 450 3000 1150 1350 4250 limit/base	0 51 1 757 ▲ 853 826 976 2447		
Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS	ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	10 100 450 3000 1150 1350 4250 limit/base	0 51 1 757 ▲ 853 826 976 2447 ∠urrent	 history1	 history2
Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon	ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m method ASTM D5185m	10 100 450 3000 1150 1350 4250 limit/base >20	0 51 1 757 ▲ 853 826 976 2447 ∠447 ∠urrent	 history1	 history2
Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium	ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m method ASTM D5185m	10 100 450 3000 1150 1350 4250 limit/base >20 >158	0 51 1 757 ▲ 853 826 976 2447 2447 <u>current</u> 5 4	 history1	 history2
Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m	10 100 450 3000 1150 1350 4250 limit/base >20 >158 >20	0 51 1 757 ▲ 853 826 976 2447 2447 <u>current</u> 5 4 2	 history1	 history2
Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium Fuel	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m	10 100 450 3000 1150 1350 4250 limit/base >20 >158 >20 >5	0 51 1 757 ▲ 853 826 976 2447 <u>current</u> 5 4 2 4 2 ▲ 44.5	 history1	 history2
Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium Fuel INFRA-RED	ppm	ASTM D5185m ASTM D5185m	10 100 450 3000 1150 1350 4250 limit/base >20 >158 >20 >5 limit/base	0 51 1 757 ▲ 853 826 976 2447 Current 5 4 2 ▲ 44.5 Current	 history1 history1	 history2 history2
Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium Fuel INFRA-RED Soot %	ppm ppm ppm	ASTM D5185m ASTM D5185m	10 100 450 3000 1150 1350 4250 limit/base >20 >5 limit/base >3	0 51 1 757 ▲ 853 826 976 2447 Current 5 4 2 4 2 ▲ 44.5 Current 1.2	 history1 history1	 history2 history2
Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium Fuel INFRA-RED Soot % Nitration Sulfation	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D3524 method *ASTM D7844	10 100 450 3000 1150 1350 4250 imit/base >20 >158 >20 >5 imit/base >3 >20	0 51 1 757 ▲ 853 826 976 2447 Current 5 4 2 4 2 ▲ 44.5 Current 1.2 13.1	 history1 history1	 history2 history2
Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium Fuel INFRA-RED Soot % Nitration Sulfation FLUID DEGRADA	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D3524 method *ASTM D7844 *ASTM D7624 *ASTM D7615	10 100 450 3000 1150 1350 4250 limit/base >20 >5 limit/base >3 >20 >30 limit/base	0 51 1 757 ▲ 853 826 976 2447 Current 5 4 2 4 2 4 2 4 1.2 1.2 1.3.1 24.5 Current	 history1 history1	 history2 history2
Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium Fuel INFRA-RED Soot % Nitration Sulfation	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m	10 100 450 3000 1150 1350 4250 imit/base >20 >158 >20 >5 imit/base >3 >20	0 51 1 757 ▲ 853 826 976 2447 Current 5 4 2 4 2 ▲ 44.5 Current 1.2 13.1 24.5	history1 history1 history1	 history2 history2 history2



OIL ANALYSIS REPORT



JAL		method	limit/base	current	history1	history2
Metal	scalar	*Visual	NONE	NONE		
Metal	scalar	*Visual	NONE	NONE		
ate	scalar	*Visual	NONE	NONE		
	scalar	*Visual	NONE	NONE		
	scalar	*Visual	NONE	NONE		
irt	scalar	*Visual	NONE	NONE		
ance	scalar	*Visual	NORML	NORML		
	scalar	*Visual	NORML	NORML		
ied Water	scalar	*Visual	>0.2	NEG		
ater	scalar	*Visual		NEG		
PROPER1	TIES	method	limit/base	current	history1	history2
100°C	cSt	ASTM D445	14.4	10.6		
PHS						
ppm)				Lead (ppm)		
				⁸⁰		
				60 - Severe		
			udd	40		
				Ganonina		
				20 -		
			124	10/24		
			May10/24	/lay10		
num (ppm)			2	≥ Chromium (p	nm)	
				12 T	piny	
				10 - Severe		
			udd	6 Abnormal		
			đ	6 Abnormal		
				2		
			4	0		
			May10/24	ay10/2		
(Ma	≊ C'l'		4
er (ppm)				Silicon (ppm)		
				Severe		
al				30 - Abnormal		
			udd	20 - Abnormal		
				10		
				0		
			May10/24	May10/24		
			May	May		
sity @ 100°C				Base Number	-	
d			(PH	Abnormal		
			Dy p10).0 Base		
I			ber (n	Abac		****
			Base Number (mg KOH/g)			
			Base).0		
			0/24			5
			May10/24	May10/24		
			_	_		
eck USA - 50	1 Madisc	on Ave., Cary	NC 27513	WΔVN	E CO SCHOOL	BUS GARAG
973	Rece		6 May 2024			I CHURCH R
5	Teste	ed : 21	May 2024			LDSBORO, N
1		nosed : 21	May 2024 -			US 2753
		IDilution, Per		BN)	Contact: BRAN	
		300-237-1369 one of accreo			brandonbri	iggs@wcps.oi T

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Report Id: WAYGOL [WUSCAR] 06182215 (Generated: 05/21/2024 09:29:21) Rev: 1

Contact/Location: BRANDON BRIGGS - WAYGOL

Т:

F: