




OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id
FREIGHTLINER 474

Component
Diesel Engine

Fluid
PETRO CANADA DURON HP 15W40 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		WC0905978	WC0727263	---
Sample Date	Client Info		10 May 2024	22 Feb 2023	---
Machine Age	mls	Client Info	107993	101704	---
Oil Age	mls	Client Info	0	101704	---
Oil Changed	Client Info		Not Changed	Not Changed	---
Sample Status			NORMAL	ABNORMAL	---

CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>5	<1.0	<1.0	---
Water	WC Method	>0.2	NEG	NEG	---
Glycol	WC Method		NEG	0.0	---

WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>80	18	71
Chromium	ppm	ASTM D5185m	>5	<1	1
Nickel	ppm	ASTM D5185m	>2	0	0
Titanium	ppm	ASTM D5185m		0	0
Silver	ppm	ASTM D5185m	>3	0	0
Aluminum	ppm	ASTM D5185m	>30	8	8
Lead	ppm	ASTM D5185m	>30	0	3
Copper	ppm	ASTM D5185m	>150	2	5
Tin	ppm	ASTM D5185m	>5	<1	<1
Vanadium	ppm	ASTM D5185m		0	0
Cadmium	ppm	ASTM D5185m		0	0

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		12	15
Barium	ppm	ASTM D5185m		0	<1
Molybdenum	ppm	ASTM D5185m		57	75
Manganese	ppm	ASTM D5185m		<1	<1
Magnesium	ppm	ASTM D5185m		807	711
Calcium	ppm	ASTM D5185m		1173	1412
Phosphorus	ppm	ASTM D5185m		1012	955
Zinc	ppm	ASTM D5185m		1153	1204
Sulfur	ppm	ASTM D5185m		3339	3532

CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>20	3	7
Sodium	ppm	ASTM D5185m		38	195
Potassium	ppm	ASTM D5185m	>20	15	80

INFRA-RED




	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>3	0.4	1.5
Nitration	Abs/cm	*ASTM D7624	>20	6.6	9.5
Sulfation	Abs/.1mm	*ASTM D7415	>30	18.4	21.9

FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	13.2	14.6
Base Number (BN)	mg KOH/g	ASTM D2896	9.8	8.4	8.6











OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	---
Yellow Metal	scalar	*Visual	NONE	NONE	---
Precipitate	scalar	*Visual	NONE	NONE	---
Silt	scalar	*Visual	NONE	NONE	---
Debris	scalar	*Visual	NONE	NONE	---
Sand/Dirt	scalar	*Visual	NONE	NONE	---
Appearance	scalar	*Visual	NORML	NORML	---
Odor	scalar	*Visual	NORML	NORML	---
Emulsified Water	scalar	*Visual	>0.2	NEG	---
Free Water	scalar	*Visual		NEG	---

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	15.6	13.2	13.2

GRAPHS



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : WC0905978 **Received** : 16 May 2024
Lab Number : **06182220** **Tested** : 18 May 2024
Unique Number : 11033546 **Diagnosed** : 18 May 2024 - Wes Davis
Test Package : MOB 1 (Additional Tests: TBN)

WAYNE CO SCHOOL BUS GARAGE
 1603 SALEM CHURCH RD
 GOLDSBORO, NC
 US 27530
 Contact: BRANDON BRIGGS
 brandonbriggs@wcps.org

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)