

Sample Rating Trend

Machine Id

IROCK RVS-20 ARTESIA CRUSHER

Diesel Engine Fluid

{not provided} (--- GAL)

Recommendation

No corrective action is recommended at this time. Resample at the next service interval to monitor. Please specify the brand, type, and viscosity of the oil on your next sample.

Wear

All component wear rates are normal.

Contamination

Fuel content negligible. There is no indication of any contamination in the oil.

Fluid Condition


The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.


ORMAL	NC							
	Apr2024	0ct2023	Apr2023	Nov2022	Mar2022	Aug2021	Jan2021	DZÓ


SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		KL0013548	KL0013573	KL0013285
Sample Date		Client Info		01 May 2024	09 Apr 2024	26 Jan 2024
Machine Age	hrs	Client Info		8527	0	0
Oil Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	NORMAL	NORMAL
CONTAMINATION	۸	method	limit/base	current	history1	history2
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>100	8	10	3
Chromium	ppm	ASTM D5185m	>20	0	0	<1
Nickel	ppm	ASTM D5185m	>4	0	<1	0
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m	>3	0	0	0
Aluminum	ppm	ASTM D5185m	>20	3	3	2
Lead	ppm	ASTM D5185m	>40	0	<1	0
Copper	ppm	ASTM D5185m	>330	3	0	0
Tin	ppm	ASTM D5185m	>15	<1	<1	<1
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		497	438	397
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		87	88	85
Manganese	ppm	ASTM D5185m		<1	<1	0
Magnesium	ppm	ASTM D5185m		399	434	415
Calcium	ppm	ASTM D5185m		1350	1328	1231
Phosphorus	ppm	ASTM D5185m		1042	965	950
Zinc	ppm	ASTM D5185m		1190	1124	1102
Sulfur	0.00					
Sullui	ppm	ASTM D5185m		3529	3756	3096
CONTAMINANTS		ASTM D5185m method	limit/base	3529 current	3756 history1	3096 history2
CONTAMINANTS Silicon Sodium		method		current	history1	history2
CONTAMINANTS Silicon	ppm	method ASTM D5185m		current 6	history1 6 2 2	history2 4
CONTAMINANTS Silicon Sodium	ppm ppm	method ASTM D5185m ASTM D5185m	>25 >20	current 6 2	history1 6 2	history2 4 <1
CONTAMINANTS Silicon Sodium Potassium	ppm ppm ppm	method ASTM D5185m ASTM D5185m ASTM D5185m	>25 >20	current 6 2 0	history1 6 2 2	history2 4 <1 0
CONTAMINANTS Silicon Sodium Potassium Fuel	ppm ppm ppm	method ASTM D5185m ASTM D5185m ASTM D5185m ASTM D3524	>25 >20 >5	current 6 2 0 0.9	history1 6 2 2 <1.0	history2 4 <1 0 <1.0
CONTAMINANTS Silicon Sodium Potassium Fuel INFRA-RED	ppm ppm ppm %	method ASTM D5185m ASTM D5185m ASTM D5185m ASTM D3524 method	>25 >20 >5 limit/base	current 6 2 0 0.9 current	history1 6 2 2 <1.0 history1	history2 4 <1 0 <1.0 history2
CONTAMINANTS Silicon Sodium Potassium Fuel INFRA-RED Soot %	ppm ppm ppm %	method ASTM D5185m ASTM D5185m ASTM D5185m ASTM D3524 method *ASTM D7844	>25 >20 >5 limit/base >3	current 6 2 0 0.9 current 0.4	history1 6 2 2 <1.0 history1 0.3	history2 4 <1 0 <1.0 history2 0.2
CONTAMINANTS Silicon Sodium Potassium Fuel INFRA-RED Soot % Nitration	ppm ppm ppm % % Abs/cm Abs/.1mm	method ASTM D5185m ASTM D5185m ASTM D3524 ASTM D3524 method *ASTM D7844 *ASTM D7624	>25 >20 >5 limit/base >3 >20	current 6 2 0 0.9 current 0.4 7.5	history1 6 2 <1.0 history1 0.3 7.5	history2 4 <1 0 <1.0 history2 0.2 6.7
CONTAMINANTS Silicon Sodium Potassium Fuel INFRA-RED Soot % Nitration Sulfation	ppm ppm ppm % % Abs/cm Abs/.1mm	method ASTM D5185m ASTM D5185m ASTM D5185m ASTM D3524 *ASTM D7844 *ASTM D7624 *ASTM D7415	>25 >20 >5 limit/base >3 >20 >30	current 6 2 0 0.9 current 0.4 7.5 21.1	history1 6 2 <1.0 history1 0.3 7.5 21.8	history2 4 <1 0 <1.0 history2 0.2 6.7 20.9




OIL ANALYSIS REPORT












VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
FLUID PROPERT	IES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445		12.3	13.2	13.1

GRAPHS







Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513 **RAMIREZ & SONS** Sample No. : KL0013548 Received : 16 May 2024 3404 N ENTERPRISE DR £ Lab Number : 06182307 Tested : 21 May 2024 HOBBS, NM Unique Number : 11033633 Diagnosed : 21 May 2024 - Wes Davis US 88240 Test Package : FLEET (Additional Tests: FuelDilution, PercentFuel) Contact: Rick Davidson Certificate 12367 To discuss this sample report, contact Customer Service at 1-800-237-1369. rickdavidson.rsi@gmail.com * - Denotes test methods that are outside of the ISO 17025 scope of accreditation. T: Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012) F:

Mar4/22

Vov11/22

Apr21/23

.nr9/24

12

Apr17/20

Jan 28/21

10/8/DI

Report Id: RAMHOB [WUSCAR] 06182307 (Generated: 05/21/2024 09:30:16) Rev: 1

Submitted By: Mike Richardson Page 2 of 2