


OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id

JOHN DEERE 624L 624L UNIT 9

Hydraulic System

{not provided} (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. Please note that this is a corrected copy for laboratory data updates.

All component wear rates are normal.

Contamination

The amount and size of particulates present in the system are acceptable. There is no indication of any contamination in the fluid.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the fluid is suitable for further service.

| | | May2023 | Jul2023 | Mar2024 Apr2024 | May2024 | |
|-----------------|-------|--------------|------------|-----------------|-------------|-------------|
| SAMPLE INFORMA | NOITA | method | limit/base | current | history1 | history2 |
| Sample Number | | Client Info | | PE0003799 | PE0003821 | PE0003835 |
| Sample Date | | Client Info | | 14 May 2024 | 05 Apr 2024 | 07 Mar 2024 |
| Machine Age | hrs | Client Info | | 4014 | 3756 | 3473 |
| Oil Age | hrs | Client Info | | 3756 | 3473 | 1380 |
| Oil Changed | | Client Info | | N/A | N/A | N/A |
| Sample Status | | | | NORMAL | NORMAL | NORMAL |
| CONTAMINATION | | method | limit/base | current | history1 | history2 |
| Water | | WC Method | >0.1 | NEG | NEG | NEG |
| WEAR METALS | | method | limit/base | current | history1 | history2 |
| PQ | | ASTM D8184 | | 13 | 17 | 11 |
| Iron | ppm | ASTM D5185m | >20 | 2 | <1 | 2 |
| Chromium | ppm | ASTM D5185m | >10 | <1 | <1 | 1 |
| Nickel | ppm | ASTM D5185m | >10 | 0 | 0 | 0 |
| | ppm | ASTM D5185m | | <1 | 0 | <1 |
| | ppm | ASTM D5185m | | <1 | 0 | 0 |
| | ppm | ASTM D5185m | >10 | 1 | <1 | <1 |
| | ppm | ASTM D5185m | >10 | <1 | 0 | 1 |
| | ppm | ASTM D5185m | >75 | <1 | 0 | <1 |
| | ppm | ASTM D5185m | >10 | <1 | <1 | <1 |
| | ppm | ASTM D5185m | | 0 | 0 | <1 |
| | ppm | ASTM D5185m | | <1 | 0 | 0 |
| ADDITIVES | | method | limit/base | current | history1 | history2 |
| Boron | ppm | ASTM D5185m | | 0 | 0 | 0 |
| Barium | ppm | ASTM D5185m | | 0 | 0 | 0 |
| Molybdenum | ppm | ASTM D5185m | | <1 | 0 | <1 |
| Manganese | ppm | ASTM D5185m | | <1 | <1 | <1 |
| Magnesium | ppm | ASTM D5185m | | 23 | 6 | <1 |
| Calcium | ppm | ASTM D5185m | | 588 | 573 | 562 |
| Phosphorus | ppm | ASTM D5185m | | 687 | 699 | 745 |
| Zinc | ppm | ASTM D5185m | | 795 | 890 | 788 |
| Sulfur | ppm | ASTM D5185m | | 2218 | 2193 | 2205 |
| CONTAMINANTS | | method | limit/base | current | history1 | history2 |
| Silicon | ppm | ASTM D5185m | >20 | 3 | 3 | 3 |
| Sodium | ppm | ASTM D5185m | | <1 | 0 | 2 |
| Potassium | ppm | ASTM D5185m | >20 | 0 | 0 | 0 |
| FLUID CLEANLINE | SS | method | limit/base | current | history1 | history2 |
| Particles >4µm | | ASTM D7647 | >5000 | 1019 | 767 | 1018 |
| Particles >6µm | | ASTM D7647 | >1300 | 170 | 292 | 299 |
| Particles >14µm | | ASTM D7647 | >160 | 21 | 51 | 39 |
| Particles >21µm | | ASTM D7647 | >40 | 5 | 12 | 9 |
| Particles >38µm | | ASTM D7647 | >10 | 0 | 0 | 0 |
| Particles >71µm | | ASTM D7647 | >3 | 0 | 0 | 0 |
| 0'1 01 1' | | 100 4400 () | 1011=111 | | 1=11=110 | 4=44=440 |

ISO 4406 (c) >19/17/14

17/15/12

Oil Cleanliness

17/15/13

17/15/12



OIL ANALYSIS REPORT







Certificate 12367

Laboratory

Sample No.

Lab Number : 06182656

: PE0003799 Unique Number : 11033982

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 17 May 2024 **Tested** : 22 May 2024 Diagnosed

: 22 May 2024 - Don Baldridge Test Package : CONST (Additional Tests: ICP, KV40, PQ, PrtCount, SCREEN) To discuss this sample report, contact Customer Service at 1-800-237-1369.

 st - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Submitted By: ROCHELLE MENDOZA

801 FM 694

US 79022

T:

F:

DALHART, TX

Contact: JOHN DEVRIES

johnidevries@gmail.com