

OIL ANALYSIS REPORT

Sample Rating Trend



Machine Id

7030773 (S/N 1038)

Compressor Fluid KAESER SIGMA (OEM) S-460 (--- GAL)

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

The amount and size of particulates present in the system are acceptable. There is no indication of any contamination in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.


| SAMPLE INFORM | IATION | method | limit/base | current | history1 | history2 |
|------------------|----------|--------------|------------|-------------|-------------|---------------|
| Sample Number | | Client Info | | KCPA017811 | KCP47685D | KCP50032 |
| Sample Date | | Client Info | | 03 May 2024 | 30 Dec 2022 | 12 Aug 2022 |
| Machine Age | hrs | Client Info | | 20514 | 12409 | 10172 |
| Oil Age | hrs | Client Info | | 4880 | 4683 | 1738 |
| Oil Changed | | Client Info | | Not Changd | Not Changd | Not Changd |
| Sample Status | | | | NORMAL | ATTENTION | ABNORMAL |
| WEAR METALS | | method | limit/base | current | history1 | history2 |
| Iron | ppm | ASTM D5185m | >50 | <1 | 3 | <1 |
| Chromium | ppm | ASTM D5185m | >10 | <1 | 0 | 0 |
| Nickel | ppm | ASTM D5185m | >3 | <1 | 0 | 0 |
| Titanium | ppm | ASTM D5185m | >3 | <1 | 0 | 0 |
| Silver | ppm | ASTM D5185m | >2 | <1 | 0 | <1 |
| Aluminum | ppm | ASTM D5185m | >10 | 2 | 3 | 3 |
| Lead | ppm | ASTM D5185m | >10 | <1 | 0 | 0 |
| Copper | ppm | ASTM D5185m | >50 | 8 | 10 | 7 |
| Tin | ppm | ASTM D5185m | >10 | 1 | 0 | <1 |
| Antimony | ppm | ASTM D5185m | | | | |
| Vanadium | ppm | ASTM D5185m | | <1 | 0 | 0 |
| Cadmium | ppm | ASTM D5185m | | <1 | 0 | 0 |
| | ррш | | | | - | |
| ADDITIVES | | method | limit/base | current | history1 | history2 |
| Boron | ppm | ASTM D5185m | | 0 | 0 | 0 |
| Barium | ppm | ASTM D5185m | 90 | 0 | 1 | 0 |
| Molybdenum | ppm | ASTM D5185m | | <1 | 0 | 0 |
| Manganese | ppm | ASTM D5185m | | <1 | 0 | <1 |
| Magnesium | ppm | ASTM D5185m | 90 | 11 | <1 | 16 |
| Calcium | ppm | ASTM D5185m | 2 | 4 | 0 | 0 |
| Phosphorus | ppm | ASTM D5185m | | 5 | 2 | 28 |
| Zinc | ppm | ASTM D5185m | | 18 | 22 | 29 |
| Sulfur | ppm | ASTM D5185m | | 20329 | 18266 | 15671 |
| CONTAMINANTS | | method | limit/base | current | history1 | history2 |
| Silicon | ppm | ASTM D5185m | >25 | 1 | 2 | <1 |
| Sodium | ppm | ASTM D5185m | | 4 | <1 | 4 |
| Potassium | ppm | ASTM D5185m | >20 | 4 | <1 | 0 |
| Water | % | ASTM D6304 | >0.05 | 0.010 | 0.006 | 0.015 |
| ppm Water | ppm | ASTM D6304 | >500 | 103 | 63.7 | 153.0 |
| FLUID CLEANLIN | ESS | method | limit/base | current | history1 | history2 |
| Particles >4µm | | ASTM D7647 | | 806 | 3869 | 61378 |
| Particles >6µm | | ASTM D7647 | >1300 | 222 | 1290 | 1 6275 |
| Particles >14µm | | ASTM D7647 | >80 | 27 | 154 | 1 099 |
| Particles >21µm | | ASTM D7647 | >20 | 11 | 36 | A 237 |
| Particles >38µm | | ASTM D7647 | >4 | 1 | 1 | 2 |
| Particles >71µm | | ASTM D7647 | >3 | 0 | 0 | 0 |
| Oil Cleanliness | | ISO 4406 (c) | >/17/13 | 17/15/12 | 9/17/14 | ▲ 23/21/17 |
| FLUID DEGRADA | | method | limit/base | current | history1 | history2 |
| Acid Number (AN) | mg KOH/g | ASTM D8045 | | 0.43 | 0.43 | 0.35 |


Report Id: WASPHIKCP [WUSCAR] 06183343 (Generated: 05/21/2024 18:45:14) Rev: 1


Contact/Location: Service Manager - WASPHIKCP



OIL ANALYSIS REPORT








Sep 13/21

C/Lun

\$7

| VISUAL | | method | limit/base | current | history1 | history2 |
|------------------|--------|-----------|------------|---------|----------|----------|
| White Metal | scalar | *Visual | NONE | NONE | NONE | NONE |
| Yellow Metal | scalar | *Visual | NONE | NONE | NONE | NONE |
| Precipitate | scalar | *Visual | NONE | NONE | NONE | NONE |
| Silt | scalar | *Visual | NONE | NONE | NONE | NONE |
| Debris | scalar | *Visual | NONE | NONE | NONE | 🔺 MODER |
| Sand/Dirt | scalar | *Visual | NONE | NONE | NONE | NONE |
| Appearance | scalar | *Visual | NORML | NORML | NORML | NORML |
| Odor | scalar | *Visual | NORML | NORML | NORML | NORML |
| Emulsified Water | scalar | *Visual | >0.05 | NEG | NEG | NEG |
| Free Water | scalar | *Visual | | NEG | NEG | NEG |
| FLUID PROPERT | IES | method | limit/base | current | history1 | history2 |
| Visc @ 40°C | cSt | ASTM D445 | 46 | 44.5 | 45.47 | 44.4 |
| SAMPLE IMAGES | 3 | method | limit/base | current | history1 | history2 |
| Color | | | | • | | |
| Bottom | | | | | | |



Report Id: WASPHIKCP [WUSCAR] 06183343 (Generated: 05/21/2024 18:45:14) Rev: 1

Contact/Location: Service Manager - WASPHIKCP