

OIL ANALYSIS REPORT

Sample Rating Trend





Machine Id MACK 20142

Natural Gas Engine

PETRO CANADA DURON GEO LD 15W40 (--- GAL)

| | SAMPLE INFORM | ATION | method | limit/base | current | history1 | history2 |
|-------------------------------|------------------------|--------------------|----------------------------|-------------------|--------------|----------|----------|
| | Sample Number | | Client Info | | SBP0007345 | | |
| advise that you | Sample Date | | Client Info | | 16 May 2024 | | |
| nt leak. Oil and | Machine Age | hrs | Client Info | | 7862 | | |
| pling has been resample to | Oil Age | hrs | Client Info | | 424 | | |
| | Oil Changed | | Client Info | | Changed | | |
| | Sample Status | | | | ABNORMAL | | |
| rmal. | CONTAMINATION | | method | limit/base | current | history1 | history2 |
| e ne dežede | Water | | WC Method | >0.1 | NEG | | |
| are high. | WEAR METALS | | method | limit/base | current | history1 | history2 |
| ere is suitable | Iron | ppm | ASTM D5185m | >50 | 8 | | |
| | Chromium | ppm | ASTM D5185m | >5 | <1 | | |
| | Nickel | ppm | ASTM D5185m | >4 | 0 | | |
| | Titanium | ppm | ASTM D5185m | >5 | 0 | | |
| | Silver | ppm | ASTM D5185m | >3 | 0 | | |
| | Aluminum | ppm | ASTM D5185m | >25 | 2 | | |
| | Lead | ppm | ASTM D5185m | >40 | 2 | | |
| | Copper | ppm | ASTM D5185m | >150 | <1 | | |
| | Tin | ppm | ASTM D5185m | >4 | <1 | | |
| | Vanadium | ppm | ASTM D5185m | | 0 | | |
| | Cadmium | ppm | ASTM D5185m | | 0 | | |
| | ADDITIVES | | method | limit/base | current | history1 | history2 |
| | Boron | ppm | ASTM D5185m | 50 | 6 | | |
| | Barium | ppm | ASTM D5185m | 5 | 0 | | |
| | Molybdenum | ppm | ASTM D5185m | 50 | 69 | | |
| | Manganese | ppm | ASTM D5185m | 0 | <1 | | |
| | Magnesium | ppm | ASTM D5185m | 560 | 537 | | |
| | Calcium | ppm | ASTM D5185m | 1510 | 1672 | | |
| | Phosphorus | ppm | ASTM D5185m | 780 | 675 | | |
| | Zinc | ppm | ASTM D5185m | 870 | 961 | | |
| | Sulfur | ppm | ASTM D5185m | 2040 | 2834 | | |
| | CONTAMINANTS | | method | limit/base | current | history1 | history2 |
| | Silicon | ppm | ASTM D5185m | >25 | 17 | | |
| | Sodium | ppm | ASTM D5185m | | <u> </u> | | |
| | Potassium | ppm | ASTM D5185m | >20 | A 276 | | |
| | INFRA-RED | | method | limit/base | current | history1 | history2 |
| | | | **** | | 0 | | |
| | Soot % | % | *ASTM D7844 | | - | | |
| | Soot % Nitration | % Abs/cm | *ASTM D7844 *ASTM D7624 | >20 | 12.4 | | |
| | | | | | | | |
| | Nitration | Abs/cm Abs/.1mm | *ASTM D7624 | | 12.4 | | |
| | Nitration Sulfation | Abs/cm Abs/.1mm | *ASTM D7624 *ASTM D7415 | >30 limit/base | 12.4 20.7 | | |

DIAGNOSIS

Recommendation

Check for low coolant level. We advise that you check for the source of the coolant leak. Oil and filter change at the time of sampling has been noted. We recommend an early resample to monitor this condition.

Wear

All component wear rates are normal.

Contamination

Sodium and/or potassium levels are high.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil.



OIL ANALYSIS REPORT

