

OIL ANALYSIS REPORT

Area **Utility** Atlas Copco FHG82FK01 Main Fermentation Air, Compressor Air Compressor Fluid

MOBIL DTE OIL HVY MEDIUM (--- GAL)

Recommendation

Resample at the next service interval to monitor. (Customer Sample Comment: Was not running)

Wear


All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.




SAMPLE INFORM	1ATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0888625	WC0726024	WC0679870
Sample Date		Client Info		16 May 2024	23 Aug 2022	05 Apr 2022
Machine Age	yrs	Client Info		0	0	0
Oil Age	yrs	Client Info		0	0	0
Oil Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	NORMAL	NORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>70	0	<1	0
Chromium	ppm	ASTM D5185m	>15	0	0	0
Nickel	ppm	ASTM D5185m	>6	0	0	0
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m		0	<1	<1
Aluminum	ppm	ASTM D5185m	>10	0	<1	0
Lead	ppm	ASTM D5185m	>20	<1	<1	<1
Copper	ppm	ASTM D5185m	>80	<1	1	2
Tin	ppm	ASTM D5185m	>15	0	<1	<1
Antimony	ppm	ASTM D5185m				
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	<1	2
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		0	0	0
Manganese	ppm	ASTM D5185m		0	0	0
Magnesium	ppm	ASTM D5185m		1	0	0
Calcium	ppm	ASTM D5185m		<1	5	0
Phosphorus	ppm	ASTM D5185m		85	84	79
Zinc	ppm	ASTM D5185m		2	0	0
Sulfur	ppm	ASTM D5185m		1888	1589	1486
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>12	<1	<1	1
Sodium	ppm	ASTM D5185m		0	<1	0
Potassium	ppm	ASTM D5185m	>20	0	0	0
Water	%	ASTM D6304	>0.1	0.00	0.003	0.00
ppm Water	ppm	ASTM D6304	>1000	0	33.5	0.00
FLUID CLEANLIN	ESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>10000	1389	309	8867
Particles >6µm		ASTM D7647	>2500	305	88	1748
Particles >14µm		ASTM D7647	>320	24	14	37
Particles >21µm		ASTM D7647	>80	8	3	8
Particles >38µm		ASTM D7647	>20	0	0	0
Particles >71µm		ASTM D7647	>4	0	0	0
Oil Cleanliness		ISO 4406 (c)	>20/18/15	18/15/12	15/14/11	20/18/12
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN) :14:52) Rev: 1	mg KOH/g	ASTM D8045		0.27	0.26 Submitted By: (0.26 CHASE MCGE


Report Id: NOVFRANC [WUSCAR] 06184304 (Generated: 05/22/2024 14:14:52) Rev: 1


Submitted By: CHASE MCGEE Page 1 of 2




OIL ANALYSIS REPORT











VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	LIGHT
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
FLUID PROPERT	IES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	65.1	65.9	65.9	65.7
SAMPLE IMAGES	\$	method	limit/base	current	history1	history2
Color				•		
Bottom						





* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T: (919)494-3146 F: (919)494-3456

Report Id: NOVFRANC [WUSCAR] 06184304 (Generated: 05/22/2024 14:14:52) Rev: 1

Submitted By: CHASE MCGEE

brct@novozymes.com

Page 2 of 2