




OIL ANALYSIS REPORT

Sample Rating Trend



VISCOSITY



Machine Id

8104411214001 (S/N 810441214001)

Component

Gearbox

Fluid

SHELL OMALA 150 (2 GAL)

DIAGNOSIS

Recommendation

No corrective action is recommended at this time. Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

Viscosity of sample indicates oil is within ISO 220 range, advise investigate. Confirm oil type. The AN level is acceptable for this fluid.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		WC0884857	---	---
Sample Date	Client Info		04 Jan 2024	---	---
Machine Age	mths	Client Info	0	---	---
Oil Age	mths	Client Info	0	---	---
Oil Changed	Client Info		N/A	---	---
Sample Status			ATTENTION	---	---

CONTAMINATION

	method	limit/base	current	history1	history2
Water	WC Method	>0.2	NEG	---	---

WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>200	6	---
Chromium	ppm	ASTM D5185m	>15	<1	---
Nickel	ppm	ASTM D5185m	>15	<1	---
Titanium	ppm	ASTM D5185m		<1	---
Silver	ppm	ASTM D5185m		<1	---
Aluminum	ppm	ASTM D5185m	>25	2	---
Lead	ppm	ASTM D5185m	>100	<1	---
Copper	ppm	ASTM D5185m	>200	1	---
Tin	ppm	ASTM D5185m	>25	<1	---
Vanadium	ppm	ASTM D5185m		<1	---
Cadmium	ppm	ASTM D5185m		<1	---

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	6.2	<1	---
Barium	ppm	ASTM D5185m	0.0	4	---
Molybdenum	ppm	ASTM D5185m	0	<1	---
Manganese	ppm	ASTM D5185m		<1	---
Magnesium	ppm	ASTM D5185m	0	<1	---
Calcium	ppm	ASTM D5185m	0.0	15	---
Phosphorus	ppm	ASTM D5185m	512	193	---
Zinc	ppm	ASTM D5185m	3.8	23	---
Sulfur	ppm	ASTM D5185m	8167	12344	---

CONTAMINANTS


	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>50	2	---
Sodium	ppm	ASTM D5185m		1	---
Potassium	ppm	ASTM D5185m	>20	2	---

FLUID DEGRADATION

	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		0.44	---



OIL ANALYSIS REPORT







VISUAL	method	limit/base	current	history1	history2	
White Metal	scalar	*Visual	NONE	NONE	---	---
Yellow Metal	scalar	*Visual	NONE	NONE	---	---
Precipitate	scalar	*Visual	NONE	NONE	---	---
Silt	scalar	*Visual	NONE	NONE	---	---
Debris	scalar	*Visual	NONE	LIGHT	---	---
Sand/Dirt	scalar	*Visual	NONE	NONE	---	---
Appearance	scalar	*Visual	NORML	NORML	---	---
Odor	scalar	*Visual	NORML	NORML	---	---
Emulsified Water	scalar	*Visual	>0.2	NEG	---	---
Free Water	scalar	*Visual		NEG	---	---

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 40°C	cSt	ASTM D445	150	● 222.6	---	---

SAMPLE IMAGES	method	limit/base	current	history1	history2
---------------	--------	------------	---------	----------	----------

Color				no image	no image
Bottom				no image	no image

GRAPHS



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : WC0884857 **Received** : 20 May 2024
Lab Number : 06184502 **Tested** : 29 May 2024
Unique Number : 11035828 **Diagnosed** : 29 May 2024 - Jonathan Hester
Test Package : IND 2

SOLVAY SPARTANBURG
 399 SIMS CHAPEL RD
 SPARTANBURG, SC
 US 29306
 Contact: GREG BLACK
 gregory.black@syensqo.com
 T: (864)594-3270
 F: (864)573-6972

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)