

## **OIL ANALYSIS REPORT**

Sample Rating Trend



#### Area **NFDM** Machine Id **PT12PP01BB01** Component Bearing

Fluid MOBIL SHC 626 (--- GAL)

#### DIAGNOSIS

#### Recommendation

Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil.


### Fluid Condition

The condition of the oil is acceptable for the time in service.

| SAMPLE INFORM    | IATION                           | method      | limit/base | current     | history1    | history2 |  |
|------------------|----------------------------------|-------------|------------|-------------|-------------|----------|--|
| Sample Number    |                                  | Client Info |            | WC0934864   | WC0871161   |          |  |
| Sample Date      |                                  | Client Info |            | 05 May 2024 | 21 Oct 2023 |          |  |
| Machine Age      | hrs                              | Client Info |            | 0           | 0           |          |  |
| Oil Age          | hrs                              | Client Info |            | 0           | 0           |          |  |
| Oil Changed      |                                  | Client Info |            | Not Changd  | N/A         |          |  |
| Sample Status    |                                  |             |            | NORMAL      | NORMAL      |          |  |
| CONTAMINATION    | ٧                                | method      | limit/base | current     | history1    | history2 |  |
| Water            |                                  | WC Method   | >2         | NEG         | NEG         |          |  |
| WEAR METALS      |                                  | method      | limit/base | current     | history1    | history2 |  |
| Iron             | ppm                              | ASTM D5185m | >20        | 2           | <1          |          |  |
| Chromium         | ppm                              | ASTM D5185m | >20        | <1          | 0           |          |  |
| Nickel           | ppm                              | ASTM D5185m | >20        | <1          | 0           |          |  |
| Titanium         | ppm                              | ASTM D5185m |            | <1          | <1          |          |  |
| Silver           | ppm                              | ASTM D5185m |            | <1          | 0           |          |  |
| Aluminum         | ppm                              | ASTM D5185m | >20        | 2           | 1           |          |  |
| Lead             | ppm                              | ASTM D5185m | >20        | <1          | 0           |          |  |
| Copper           | ppm                              | ASTM D5185m | >20        | 2           | <1          |          |  |
| Tin              | ppm                              | ASTM D5185m | >20        | <1          | 0           |          |  |
| Vanadium         | ppm                              | ASTM D5185m |            | <1          | 0           |          |  |
| Cadmium          | ppm                              | ASTM D5185m |            | <1          | <1          |          |  |
| ADDITIVES        |                                  | method      | limit/base | current     | history1    | history2 |  |
| Boron            | ppm                              | ASTM D5185m |            | 0           | 0           |          |  |
| Barium           | ppm                              | ASTM D5185m |            | 0           | 0           |          |  |
| Molybdenum       | ppm                              | ASTM D5185m |            | <1          | 0           |          |  |
| Manganese        | ppm                              | ASTM D5185m |            | <1          | 0           |          |  |
| Magnesium        | ppm                              | ASTM D5185m |            | <1          | 0           |          |  |
| Calcium          | ppm                              | ASTM D5185m |            | 4           | <1          |          |  |
| Phosphorus       | ppm                              | ASTM D5185m |            | 434         | 478         |          |  |
| Zinc             | ppm                              | ASTM D5185m |            | 2           | 10          |          |  |
| Sulfur           | ppm                              | ASTM D5185m |            | 74          | 0           |          |  |
| CONTAMINANTS     |                                  | method      | limit/base | current     | history1    | history2 |  |
| Silicon          | ppm                              | ASTM D5185m | >15        | 1           | <1          |          |  |
| Sodium           | ppm                              | ASTM D5185m |            | 0           | 0           |          |  |
| Potassium        | ppm                              | ASTM D5185m | >20        | 1           | <1          |          |  |
| VISUAL           |                                  | method      | limit/base | current     | history1    | history2 |  |
| White Metal      | scalar                           | *Visual     | NONE       | NONE        | NONE        |          |  |
| Yellow Metal     | scalar                           | *Visual     | NONE       | NONE        | NONE        |          |  |
| Precipitate      | scalar                           | *Visual     | NONE       | NONE        | NONE        |          |  |
| Silt             | scalar                           | *Visual     | NONE       | NONE        | NONE        |          |  |
| Debris           | scalar                           | *Visual     | NONE       | NONE        | NONE        |          |  |
| Sand/Dirt        | scalar                           | *Visual     | NONE       | NONE        | NONE        |          |  |
| Appearance       | scalar                           | *Visual     | NORML      | NORML       | NORML       |          |  |
| Odor             | scalar                           | *Visual     | NORML      | NORML       | NORML       |          |  |
| Emulsified Water | scalar                           | *Visual     | >2         | NEG         | NEG         |          |  |
| Free Water       | scalar                           | *Visual     |            | NEG         | NEG         |          |  |
| 4:16:08) Rev: 1  | Submitted By: MICHAEL VILLASENOR |             |            |             |             |          |  |



# **OIL ANALYSIS REPORT**



| Visc @ 40°C cst ASTM D445 69.9 69.4 68.7<br>SAMPLE IMAGES method imit/base current history1 history2<br>Color no image no image<br>Bottom no image no image<br>no image<br>GRAPHS<br>Ferrous Alloys<br><br>Non-ferrous Metals<br><br>Mon-ferrous Metals | FLUID PROP   | PERTIES      | method                | limit/base  | current   | history1 | history2   |
|---|--|--------------|-----------------------|---|-----------|----------|--|
| Color no image no image<br>Bottom no image no image<br>rerous Alloys  | Visc @ 40°C  | cSt          | ASTM D445             | 69.9  | 69.4      | 68.7     |  |
| Bottom no image no image<br>CRAPHS<br>Ferrous Alloys  | SAMPLE IM  | AGES         | method                | limit/base  | current   | history1 | history2   |
| GRAPHS<br>Ferrous Alloys  | Color  |              |                       |   | •         | no image | no image   |
| Ferrous Alloys  | Bottom   |              |                       |   |           | no image | no image   |
| Non-ferrous Metals  | GRAPHS   |              |                       |   |           |          |  |
| <pre>9 ion<br/>ion<br/>ion<br/>ion<br/>ion<br/>ion<br/>ion<br/>ion</pre>  |  | 'S           |                       |   |           |          |  |
|   | A chromium<br>A chro |              |                       | Marj5/24 +  |           |          |  |
|   | 78<br>76<br>74<br>72   |              |                       |   |           |          |  |
| 76<br>74<br>72  | 66 - 64 - 64 - 64 - 64 - 66 - 64 - 66 - 6   |              |                       |   |           |          |  |
| 78 Abnormal   76 Abnormal   76 Base   70 Base   66 Abnormal   | 62 - Abnormal<br>60 - E2/17230   |              |                       | May5/24   |           |          |  |
| 78   Abnormal     76   Base     70   Base     868   Abnormal     664   Abnormal     62   Abnormal   | : WearCheck USA<br>: WC0934864<br>r : 06184810<br>r : 11036136<br>e : IND 1  | Rece<br>Test | eived : 20<br>ed : 21 | r, NC 27513<br>) May 2024<br>  May 2024<br>May 2024 - Sea | an Felton | ι        | DS-GREELE<br>1302 1ST AV<br>GREELEY, CO<br>IS 80631-590<br>ct: ERIC KLIN |



To discuss this sample report, contact Customer Service at 1-800-237-1369. \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

US 80631-5909 Contact: ERIC KLINE EKLINE@LEPRINOFOODS.COM T: F: (970)347-5190

Certificate L2367