

OIL ANALYSIS REPORT

Area Paper Side Machine Io PM 2 MAIN BOWSER

Bearing Lube Fluid SHELL PM S2 M 220 (3500 GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.



SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		PE0001497	PE0001493	PE0001599
Sample Date		Client Info		16 May 2024	16 Apr 2024	26 Mar 2024
Machine Age	hrs	Client Info		0	0	0
Oil Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	NORMAL	NORMAL
CONTAMINATION	J	method	limit/base	current	history1	history2
Water		WC Method	>0.2	NEG	NEG	NEG
WEAR METALS		method	limit/base	current	history1	history2
PQ		ASTM D8184		10	16	11
Iron	ppm	ASTM D5185m	>120	0	0	0
Chromium	ppm	ASTM D5185m	>5	0	0	0
Nickel	ppm	ASTM D5185m	>20	0	0	0
Titanium	ppm	ASTM D5185m		0	<1	0
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>4	0	0	0
Lead	ppm	ASTM D5185m	>30	0	0	0
Copper	ppm	ASTM D5185m	>17	3	3	<1
Tin	ppm	ASTM D5185m	>10	<1	0	0
Vanadium	ppm	ASTM D5185m		0	<1	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	0
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		0	0	0
Manganese	ppm	ASTM D5185m		<1	0	0
Magnesium	ppm	ASTM D5185m		2	<1	<1
Calcium	ppm	ASTM D5185m		133	118	111
Phosphorus	ppm	ASTM D5185m		891	802	837
Zinc	ppm	ASTM D5185m		1180	1139	1136
Sulfur	ppm	ASTM D5185m		7309	7014	7552
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	3	3	2
Sodium	ppm	ASTM D5185m		3	5	11
Potassium	ppm	ASTM D5185m	>20	0	0	1
FLUID CLEANLIN	ESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>2500	1095	2399	719
Particles >6µm		ASTM D7647	>640	259	419	107
Particles >14µm		ASTM D7647	>160	15	19	10

ASTM D7647 >40

ASTM D7647 >10

ASTM D7647 >3

ISO 4406 (c) >18/16/14

Particles >21µm

Particles >38µm

Particles >71µm

Oil Cleanliness

2

0

0

17/14/10

5

0

0

18/16/11

2

0

0

17/15/11



OIL ANALYSIS REPORT









FLUID DEGRADATION		method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		0.12	0.97	0.69
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
FLUID PROPERT	IES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	220	219	223	223
SAMPLE IMAGES		method	limit/base	current	history1	history2

Color



Bottom





Unique Number : 11036226 Test Package : PLANT (Additional Tests: ICP, KV40, PQ, PrtCount, SCREEN) Certificate 12367 To discuss this sample report, contact Customer Service at 1-800-237-1369.

Laboratory

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Report Id: MCKPOR [WUSCAR] 06184900 (Generated: 05/22/2024 14:28:38) Rev: 1

Submitted By: DUANE DENOTTA

Contact: JOSHUA HALL

T: (360)457-4474

joshua.hall@biopappel.com

Page 2 of 2

F: