


OIL ANALYSIS REPORT

Sample Rating Trend



Machine Id

GEA C-161

Screw Compressor

TULCO LUBSOIL SYN RL WI 100 (300 GAL)

DIAGNOSIS

Recommendation

We recommend you service the filters on this component. Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is a high amount of silt (particulates < 14 microns in size) present in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is acceptable for the time in service.

-)			Feb 2024	May2024		
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		TO90003205	TO90003221	
Sample Date		Client Info		01 May 2024	13 Feb 2024	
Machine Age	hrs	Client Info		35837	0	
Oil Age	hrs	Client Info		0	0	
Oil Changed		Client Info		Not Changd	N/A	
Sample Status				ABNORMAL	ABNORMAL	
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>60	10	6	
Chromium	ppm	ASTM D5185m	>4	0	<1	
Nickel	ppm	ASTM D5185m		0	0	
Titanium	ppm	ASTM D5185m		0	0	
Silver	ppm	ASTM D5185m		0	0	
Aluminum	ppm	ASTM D5185m	>5	<1	0	
Lead	ppm	ASTM D5185m	>10	0	0	
Copper	ppm	ASTM D5185m	>30	2	0	
Tin	ppm	ASTM D5185m	>15	5	4	
Vanadium	ppm	ASTM D5185m		0	0	
Cadmium	ppm	ASTM D5185m		0	0	
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	
Barium	ppm	ASTM D5185m		0	0	
Molybdenum	ppm	ASTM D5185m		0	0	
Manganese	ppm	ASTM D5185m		<1	<1	
Magnesium	ppm	ASTM D5185m		0	2	
Calcium		ASTM D5185m		36	37	
Phosphorus	ppm	ASTM D5185m	1500	386	326	
Zinc	ppm	ASTM D5185m	1300	15	17	
Sulfur	ppm	ASTM D5185m		33	0	
	ppm		1111-/1			
CONTAMINANTS	1	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>50	5	4	
Sodium	ppm	ASTM D5185m		1	0	
Potassium	ppm	ASTM D5185m	>20	2	0	
Water	%	ASTM D6304	>2.26	0.017	0.019	
ppm Water	ppm	ASTM D6304	>22600	173	194	
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>10000	<u>^</u> 20499	▲ 37788	
Particles >6μm		ASTM D7647	>2500	△ 3850	4 9443	
Particles >14μm		ASTM D7647	>320	182	191	
Particles >21µm		ASTM D7647	>80	43	17	
Particles >38μm		ASTM D7647	>20	1	1	
Particles >71µm		ASTM D7647	>4	0	1	
Oil Cleanliness		ISO 4406 (c)	>20/18/15	<u>22/19/15</u>	<u>22/20/15</u>	
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	0.04	0.042	0.045	



OIL ANALYSIS REPORT







Certificate 12367

Laboratory Sample No. Lab Number

: 06185071 Unique Number : 11036397

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 : TO90003205 Received : 20 May 2024

Tested : 29 May 2024 : 29 May 2024 - Don Baldridge Diagnosed

49 COUNTY RD 419 PECOS, TX US 79772

Contact: Service Manager

Test Package : IND 2 (Additional Tests: KF, KV100, PrtCount, VI) To discuss this sample report, contact Customer Service at 1-800-237-1369.

 st - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:

F: