

## **OIL ANALYSIS REPORT**

Sample Rating Trend



## Area SMART OIL Machine Id HERTZ VD018949 Component

Component Compressor

### DIAGNOSIS

### Recommendation

The filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

## Wear

All component wear rates are normal.

#### Contamination

Moderate concentration of visible dirt/debris present in the oil.

## Fluid Condition


The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORM	<b>IATION</b>	method	limit/base	current	history1	history2
Sample Number		Client Info		UHK06185114	UHK06068563	
Sample Date		Client Info		18 Mar 2024	18 Oct 2023	
Machine Age	hrs	Client Info		1341	974	
Oil Age	hrs	Client Info		370	974	
Oil Changed		Client Info		Not Changd	Changed	
Sample Status				NORMAL	NORMAL	
CONTAMINATIO	N	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG	NEG	
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	<1	<1	
Chromium	ppm	ASTM D5185m	>10	<1	0	
Nickel	ppm	ASTM D5185m		1	4	
Titanium	ppm	ASTM D5185m		<1	0	
Silver	ppm	ASTM D5185m		<1	0	
Aluminum	ppm	ASTM D5185m	>25	1	0	
Lead	ppm	ASTM D5185m	>25	<1	<1	
Copper	ppm	ASTM D5185m	>50	2	3	
Tin	ppm	ASTM D5185m	>15	<1	<1	
Vanadium	ppm	ASTM D5185m		<1	0	
Cadmium	ppm	ASTM D5185m		0	0	
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	
Barium	ppm	ASTM D5185m		0	0	
Molybdenum	ppm	ASTM D5185m		0	0	
Manganese	ppm	ASTM D5185m		0	<1	
Magnesium	ppm	ASTM D5185m		<1	8	
Calcium	ppm	ASTM D5185m	20	0	2	
Phosphorus	ppm	ASTM D5185m		541	134	
Zinc	ppm	ASTM D5185m		18	43	
Sulfur	ppm	ASTM D5185m		1352	311	
CONTAMINANTS	5	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	17	10	
Sodium	ppm	ASTM D5185m		0	2	
Potassium	ppm	ASTM D5185m	>20	1	0	
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		0.082	0.092	



# **OIL ANALYSIS REPORT**

VISUAL



	VISUAL		method	limit/base	current	history1	history2
	White Metal	scalar	*Visual	NONE	NONE	NONE	
	Yellow Metal	scalar	*Visual	NONE	NONE	NONE	
	Precipitate	scalar	*Visual	NONE	NONE	NONE	
	Silt	scalar	*Visual	NONE	NONE	NONE	
	Debris	scalar	*Visual	NONE	MODER	NONE	
	Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	
3/24	Appearance	scalar	*Visual	NORML	NORML	NORML	
Mar18/24	Odor	scalar	*Visual	NORML	NORML	NORML	
	Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	
	Free Water	scalar	*Visual		NEG	NEG	
				11 11 11			
	FLUID PROPERT		method	limit/base	current	history1	history2
	Visc @ 40°C	cSt	ASTM D445	46	47.5	45.1	
-	SAMPLE IMAGES	S	method	limit/base	current	history1	history2
Mar18/24 +	Color						no image
	Bottom						no image
	Non-ferrous Metal	S		824 Mar 18/24			
	Viscosity @ 40°C			Acid Number (mg K0H/q) 00 000 100	14		
	Abnormal				10		
	40 40 + 52 52 52 52 52 52 52 52 52 52			0.0 A H	0ct18/23		

Contact/Location: Service Manager - UCATLHER