

OIL ANALYSIS REPORT

Potassium

Area **NOT GIVEN** KAISHAN 111908814U

Component Compressor

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. Please specify the brand, type, and viscosity of the oil on your next sample.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORM	MATION	method				
Sample Number		Client Info		UHC06185138		
Sample Date		Client Info		19 May 2024		
Machine Age	hrs	Client Info		6431		
Oil Age	hrs	Client Info		3131		
Oil Changed		Client Info		Changed		
Sample Status				NORMAL		
CONTAMINATION		method	limit/base	current	history1	
Water		WC Method	>0.1	NEG		
WEAR METALS		method	limit/base	current	history1	
Iron	ppm	ASTM D5185m	>50	<1		
Chromium	ppm	ASTM D5185m	>10	<1		
Nickel	ppm	ASTM D5185m		0		

Titanium	ppm	ASTM D5185m		<1		
Silver	ppm	ASTM D5185m		<1		
Aluminum	ppm	ASTM D5185m	>25	1		
Lead	ppm	ASTM D5185m	>25	<1		
Copper	ppm	ASTM D5185m	>50	<1		
Tin	ppm	ASTM D5185m	>15	<1		
Vanadium	ppm	ASTM D5185m		<1		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0		
Barium	ppm	ASTM D5185m		0		

Molybdenum	ppm	ASTM D5185m		0		
Manganese	ppm	ASTM D5185m		0		
Magnesium	ppm	ASTM D5185m		<1		
Calcium	ppm	ASTM D5185m		0		
Phosphorus	ppm	ASTM D5185m		6		
Zinc	ppm	ASTM D5185m		6		
Sulfur	ppm	ASTM D5185m		0		
CONTAMINANTS	;	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	9		
Sodium	ppm	ASTM D5185m		0		

1

ASTM D5185m

ppm

FLUID DEGRADATION Acid Number (AN) mg KOH/g ASTM D8045 0.445


>20

Sample Rating Trend

ORMAL



OIL ANALYSIS REPORT



	VISUAL		method				history2
	White Metal	scalar	*Visual	NONE	NONE		
	Yellow Metal	scalar	*Visual	NONE	NONE		
	Precipitate	scalar	*Visual	NONE	NONE		
	Silt	scalar	*Visual	NONE	NONE		
	Debris	scalar	*Visual	NONE	MODER		
	Sand/Dirt	scalar	*Visual	NONE	NONE		
	Appearance Odor	scalar	*Visual	NORML	NORML		
		scalar	*Visual	NORML	NORML		
	Emulsified Water	scalar	*Visual	>0.1	NEG		
	Free Water	scalar	*Visual		NEG		
	FLUID PROPER	TIES	method	limit/base	current	history1	history2
	Visc @ 40°C	cSt	ASTM D445		47.4		
	SAMPLE IMAGE	S	method	limit/base	current	history1	history2
	F F200r					no image	no image
	Bottom			(no image	no image
	Non-ferrous Meta			May19/24			
	0+						
	udd 4 2 0 + b7061 kew			May19/24			
	Viscosity @ 40°C				Acid Number		
	Viscosity @ 40°C				Acid Number		
	Viscosity @ 40°C				Acid Number		
	Viscosity @ 40°C				Acid Number		
	Viscosity @ 40°C				Acid Number		
	Viscosity @ 40°C			(0.50 (0.40) (0.			
	Viscosity @ 40°C			(0.50 (0.40) (0.			
Unique Num	ry : WearCheck USA - 50 ber : UHC06185138 ber : 11036464)1 Madiso Recei Teste Diagn	ved : 20 d : 21	(5),0.50 (6),0.40 (7),0.40 (7),0.20 (7)	May19,24		NTS PARK D DSCHTON, G US 3054
Sample N Lab Numb Unique Num ate 12367 Test Packa	ry : WearCheck USA - 50 b. : UHC06185138 ber : 06185138	Recei Teste Diagn	ved : 20 d : 21 losed : 22	, NC 27513 May 2024 May 2024 - We	P2(61)Per es Davis	123 MERCHAI HC	OMPRESSO NTS PARK D DSCHTON, G US 3054 act: Derik Bra

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Report Id: UCATLHOS [WUSCAR] 06185138 (Generated: 05/22/2024 17:41:42) Rev: 1

Contact/Location: Derik Bray - UCATLHOS

F: x: