

OIL ANALYSIS RE

Area SYN-5 ATLAS COPCO ITJ099096 - FIRST CLASS SALES 8 Compressor

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. Please specify the brand, type, and viscosity of the oil on your next sample.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

	Sample Rating Trend									
Y	SIS REPO	RT		3		N	ORMAL			
5	S SALES & SEF			Aug2022	I _{Ap} 2024					
		IATION	method	limit/base	current	history1	history2			
	Sample Number		Client Info		UHC06185144	UCH05657485				
	Sample Date		Client Info		12 Apr 2024	26 Aug 2022				
	Machine Age	hrs	Client Info		10170	7508				
	Oil Age	hrs	Client Info		3000	277				
	Oil Changed		Client Info		Changed	Not Changd				
	Sample Status				NORMAL	NORMAL				
	CONTAMINATION	١	method	limit/base	current	history1	history2			
	Water		WC Method	>0.1	NEG	NEG				
	WEAR METALS		method	limit/base	current	history1	history2			
	Iron	ppm	ASTM D5185m	>50	4	3				
	Chromium	ppm	ASTM D5185m	>5	<1	0				
	Nickel	ppm	ASTM D5185m		2	0				
	Titanium	ppm	ASTM D5185m		<1	0				
	Silver	ppm	ASTM D5185m		<1	0				
	Aluminum	ppm	ASTM D5185m	>15	1	<1				
	Lead	ppm	ASTM D5185m	>65	<1	0				
	Copper	ppm	ASTM D5185m	>65	3	<1				
	Tin	ppm	ASTM D5185m	>10	<1	0				
	Vanadium	ppm	ASTM D5185m		<1	0				
	Cadmium	ppm	ASTM D5185m		0	0				
	ADDITIVES		method	limit/base	current	history1	history2			
	Boron	ppm	ASTM D5185m		0	0				
	Barium	ppm	ASTM D5185m		0	0				
	Molybdenum	ppm	ASTM D5185m		0	0				
	Manganaga	~~~~	ACTM DE10Em		0	.1				

Barium	ppm	ASTM D5185m		0	0	
Molybdenum	ppm	ASTM D5185m		0	0	
Manganese	ppm	ASTM D5185m		0	<1	
Magnesium	ppm	ASTM D5185m		<1	<1	
Calcium	ppm	ASTM D5185m		0	<1	
Phosphorus	ppm	ASTM D5185m		414	466	
Zinc	ppm	ASTM D5185m		91	41	
Sulfur	ppm	ASTM D5185m		647	831	
CONTAMINANTS	;	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>35	3	2	


Sodium	ppm	ASTM D5185m		<1	<1	
Potassium	ppm	ASTM D5185m	>20	1	1	
FLUID DEGRAD	ATION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		0.36	0.59	

Report Id: UCATLHOS [WUSCAR] 06185144 (Generated: 05/21/2024 17:29:37) Rev: 1



OIL ANALYSIS REPORT

VISUAL



	White Metal	scalar	*Visual	NONE	NONE	NONE	
A CONTRACTOR OF THE OWNER	Yellow Metal	scalar	*Visual	NONE	NONE	NONE	
	Precipitate	scalar	*Visual	NONE	NONE	NONE	
	Silt	scalar	*Visual	NONE	NONE	NONE	
	Debris	scalar	*Visual	NONE	NONE	LIGHT	
	Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	
/24 -	Appearance	scalar	*Visual	NORML	NORML	NORML	
Apr12/24	Odor	scalar	*Visual	NORML	NORML	NORML	
	Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	
	Free Water	scalar	*Visual	>0.1	NEG	NEG	
			VISUAI		NEG		
	FLUID PROPER	TIES	method	limit/base	current	history1	history2
	Visc @ 40°C	cSt	ASTM D445		48.9	47.0	
	SAMPLE IMAGE	S	method	limit/base	current	history1	history2
Apri 2/24	Color						no image
	Bottom						no image
	Non-ferrous Meta	ils		Apr12/24	Acid Number		
	Non-ferrous Meta	ıls		Apr12/24	Acid Number		
	Non-ferrous Meta	ıls		Apr12/24			
	Non-ferrous Meta	Ils		Apr12/24			
	Non-ferrous Meta	Ils		Apr12/24			
	Non-ferrous Meta	Ils		40.00 10.000			
	Non-ferrous Meta	ils		4pr12/24 Apr12/24 0.00 0.00 0.00 0.00			
	Non-ferrous Meta	lls		40.00 10.000			
Laboratory Sample No. Lab Number Unique Number Test Package	Non-ferrous Meta Non-ferrous Meta Non-ferrous Meta Copper Viscosity @ 40°C Copper Viscosity @ 40°C Copper Copp)1 Madisc Rece Teste	ived : 20 ed : 21	Apri12/24 340 Mumber (mg KOH/g) 210 0 Acid Number (mg KOH/g) 2000 Acid Number (mg KOH/g)	Aug26/22	ATLANTA AIR C 123 MERCHAI HC	

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Report Id: UCATLHOS [WUSCAR] 06185144 (Generated: 05/21/2024 17:29:37) Rev: 1

Contact/Location: Derik Bray - UCATLHOS

F: x: