

## **OIL ANALYSIS REPORT**

Sample Rating Trend



## Area SMART OIL 6000 Machine Id HERTZ VD011096 Component

Component Compressor

## DIAGNOSIS

## Recommendation

The filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

## Wear

All component wear rates are normal.

#### Contamination

Moderate concentration of visible dirt/debris present in the oil.


## **Fluid Condition**

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORM	<b>MATION</b>	method	limit/base	current	history1	history2
Sample Number		Client Info		UHK06185155		
Sample Date		Client Info		30 Apr 2024		
Machine Age	hrs	Client Info		1729		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		Not Changd		
Sample Status				NORMAL		
CONTAMINATIO	N	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	<1		
Chromium	ppm	ASTM D5185m	>10	<1		
Nickel	ppm	ASTM D5185m		1		
Titanium	ppm	ASTM D5185m		<1		
Silver	ppm	ASTM D5185m		<1		
Aluminum	ppm	ASTM D5185m	>25	1		
Lead	ppm	ASTM D5185m	>25	<1		
Copper	ppm	ASTM D5185m	>50	2		
Tin	ppm	ASTM D5185m	>15	1		
Vanadium	ppm	ASTM D5185m		<1		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0		
Barium	ppm	ASTM D5185m		0		
Molybdenum	ppm	ASTM D5185m		0		
Manganese	ppm	ASTM D5185m		0		
Magnesium	ppm	ASTM D5185m		<1		
Calcium	ppm	ASTM D5185m	20	0		
Phosphorus	ppm	ASTM D5185m		377		
Zinc	ppm	ASTM D5185m		8		
Sulfur	ppm	ASTM D5185m		953		
CONTAMINANTS	5	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	4		
Sodium	ppm	ASTM D5185m		0		
Potassium	ppm	ASTM D5185m	>20	1		
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		0.08		



# **OIL ANALYSIS REPORT**



	VISUAL		method	limit/base	current	history1	history2	
	White Metal	scalar	*Visual	NONE	NONE			
	Yellow Metal	scalar	*Visual	NONE	NONE			
	Precipitate	scalar	*Visual	NONE	NONE			
	Silt	scalar	*Visual	NONE	NONE			
	Debris	scalar	*Visual	NONE	MODER			
	Sand/Dirt	scalar	*Visual	NONE	NONE			
Apr30/24	Appearance	scalar	*Visual	NORML	NORML			
Api	Odor	scalar	*Visual	NORML	NORML			
	Emulsified Water	scalar	*Visual	>0.1	NEG			
	Free Water	scalar	*Visual		NEG			
	FLUID PROPERT	IES	method	limit/base	current	history1	history2	
	Visc @ 40°C	cSt	ASTM D445	46	49.4			
	SAMPLE IMAGES	S	method	limit/base	current	history1	history2	
Apr30/24	Color					no image	no image	
	Bottom					no image	no image	
	Non-ferrous Metal	5		Apr30.24				
	<sup>2</sup> <sup>470</sup> Viscosity @ 40°C			Apr30/24 -	Acid Number			
	(2-0+) 45 45 40 40 40			0/24 Acid Number (mg KOH/g) 10 0:0 0:0 0:0 0:0 0:0 0:0 0:0 0:0 0:0 0	10		a coore	
Laboratory Sample No. Lab Number Unique Number Test Package	: 11036481 Diagnosed : 22 May 2024 - Sean Felton US							
Denotes test methods that		7025 scc	ppe of accred	litation.	rulo (ICCM 106:	0010)	T: F:	

Report Id: UCATLHER [WUSCAR] 06185155 (Generated: 05/22/2024 17:46:37) Rev: 1

Contact/Location: Service Manager - UCATLHER