

OIL ANALYSIS REPORT

Sample Rating Trend



Area HC-SYN-5 INGERSOLL RAND CBV876952

Component Compressor

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. The fluid was not specified, however, a fluid match indicates that this fluid is (GENERIC) COMPRESSOR OIL (PAG) ISO 46. Please confirm.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.


Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORM	ATION	method	limit/base	current	history1	history2
Sample Number		Client Info		UHC06185165		
Sample Date		Client Info		21 Mar 2024		
Machine Age	hrs	Client Info		4609		
Oil Age	hrs	Client Info		4609		
Oil Changed		Client Info		Changed		
Sample Status				NORMAL		
CONTAMINATION	N	method	limit/base	current	history1	history2
Water	<u> </u>	WC Method	>0.8	NEG		
WEAR METALS		method	limit/base	current	history1	history2
					· · · · · · · · · · · · · · · · · · ·	
Iron	ppm	ASTM D5185m	>50	<1		
Chromium	ppm	ASTM D5185m	>10	<1		
Nickel	ppm	ASTM D5185m		0		
Titanium	ppm	ASTM D5185m		<1		
Silver	ppm	ASTM D5185m		<1		
Aluminum	ppm	ASTM D5185m	>25	1		
Lead	ppm	ASTM D5185m	>25	<1		
Copper	ppm	ASTM D5185m	>50	<1		
Tin	ppm	ASTM D5185m	>15	<1		
Vanadium	ppm	ASTM D5185m		<1		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	2	0		
Barium	ppm	ASTM D5185m	525	541		
Molybdenum	ppm	ASTM D5185m	10	0		
Manganese	ppm	ASTM D5185m		0		
Magnesium	ppm	ASTM D5185m	5	<1		
Calcium	ppm	ASTM D5185m	10	0		
Phosphorus	ppm	ASTM D5185m	250	4		
Zinc	ppm	ASTM D5185m	100	4		
Sulfur	ppm	ASTM D5185m	400	285		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	11		
Sodium	ppm	ASTM D5185m		26		
Potassium	ppm	ASTM D5185m	>20	4		
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		0.062		



OIL ANALYSIS REPORT



	VISUAL		method	limit/base	current	history1	history2	
	White Metal	scalar	*Visual	NONE	NONE			
	Yellow Metal	scalar	*Visual	NONE	NONE			
	Precipitate	scalar	*Visual	NONE	NONE			
	Silt	scalar	*Visual	NONE	NONE			
	Debris	scalar	*Visual	NONE	NONE			
	Sand/Dirt	scalar	*Visual	NONE	NONE			
Mar21/24	Appearance	scalar	*Visual	NORML	NORML			
Mar	Odor	scalar	*Visual	NORML	NORML			
	Emulsified Water	scalar	*Visual	>0.8	NEG			
1	Free Water	scalar	*Visual		NEG			
	FLUID PROPERT	TIES	method	limit/base	current	history1	history2	
	Visc @ 40°C	cSt	ASTM D445	46	51.3			
	SAMPLE IMAGE	S	method	limit/base	current	history1	history2	
Mai21/24 +	Color					no image	no image	
	Bottom					no image	no image	
	Non-ferrous Metal	ls		Mar21/24				
	Viscosity @ 40°C			90.00 90.00 90.00 90.00 90.00 900 900 90	Acid Number			
Laboratory	40 + Click wearCheck USA - 50	1 Madiso	n Ave., Cary	Mar21/24	Mar21/24	TLANTA AIR C	OMPRESSO	
Sample No. Lab Number Unique Number		Teste	Received: 20 May 2024Tested: 21 May 2024Diagnosed: 21 May 2024 - Wes Davisat 1-800-237-1369.5 scope of accreditation.			123 MERCHANTS PARK D HOSCHTON, G US 3054 Contact: Derik Bra Derik@atlantaaircompressor.co		

Report Id: UCATLHOS [WUSCAR] 06185165 (Generated: 05/21/2024 17:29:48) Rev: 1

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Contact/Location: Derik Bray - UCATLHOS

F: x: