


# **PROBLEM SUMMARY**


OKLAHOMA/3/EG - EXCAVATOR





20.69L [OKLAHOMA^3^EG - EXCAVATOR] Component Right Final Drive Fluid MOBIL DELVAC 1350 (--- GAL)


# COMPONENT CONDITION SUMMARY

Area









### RECOMMENDATION

We advise that you check all areas where dirt can enter the system. We recommend that you drain the oil from the component if this has not already been done. We advise that you inspect for the source(s) of wear. We recommend an early resample to monitor this condition.

PROBLEMATIC T	EST RE	SULTS				
Sample Status				SEVERE	NORMAL	SEVERE
Iron	ppm	ASTM D5185m	>800	<b>4</b> 350	5	<b>4</b> 2484
Chromium	ppm	ASTM D5185m	>10	<b>1</b> 4	1	7
Copper	ppm	ASTM D5185m	>75	<b>4</b> 364	<1	<b>A</b> 262
Tin	ppm	ASTM D5185m	>8	🔺 16	<1	<b>1</b> 2
Silicon	ppm	ASTM D5185m	>400	<b>▲</b> 1427	2	<b>9</b> 36

Customer Id: SHEWIC Sample No.: WC0935185 Lab Number: 06185314 Test Package: CONST



To manage this report scan the QR code

To discuss the diagnosis or test data: Don Baldridge +1 don.b505@comcast.net

To change component or sample information: Customer Service +1 1-800-237-1369 customerservice@wearcheck.com

RECOMMENI	

Action Inspect Wear Source	Status	Date	Done By ?	<b>Description</b> We advise that you inspect for the source(s) of wear.
Change Fluid			?	We recommend that you drain the oil from the component if this has not already been done.
Resample			?	We recommend an early resample to monitor this condition.
Check Dirt Access			?	We advise that you check all areas where dirt can enter the system.

### HISTORICAL DIAGNOSIS

#### 13 Feb 2024 Diag: Wes Davis

Resample at the next service interval to monitor.All component wear rates are normal. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.





WEAR

# 31 Jan 2024 Diag: Don Baldridge

We advise that you check all areas where dirt can enter the system. We recommend that you drain the oil from the component if this has not already been done. We advise that you inspect for the source(s) of wear. We recommend an early resample to monitor this condition.Bearing and/or gear wear is indicated. Elemental levels of silicon (Si) and aluminum (Al) indicate alumina-silicate (coarse dirt) ingress. The oil is no longer serviceable due to the presence of contaminants.





#### 19 Oct 2023 Diag: Jonathan Hester

We advise that you check all areas where dirt can enter the system. The oil change at the time of sampling has been noted. We advise that you inspect for the source(s) of wear. We recommend an early resample to monitor this condition.Bearing and/or gear wear is indicated. Elemental levels of silicon (Si) and aluminum (AI) indicate alumina-silicate (coarse dirt) ingress. The oil is no longer serviceable due to the presence of contaminants.






# **OIL ANALYSIS REPORT**

Sample Rating Trend



DIAGNOSIS Recommendation OKLAHOMA/3/EG - EXCAVATOR 20.69L [OKLAHOMA^3^EG - EXCAVATOR]





WEAR

SAMPLE INFORM	ATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0935185	WC0887008	WC0886945
Sample Date		Client Info		12 May 2024	13 Feb 2024	31 Jan 2024
Machine Age	hrs	Client Info		12977	12603	12603
Oil Age	hrs	Client Info		12320	241	241
Oil Changed		Client Info		N/A	N/A	N/A
Sample Status				SEVERE	NORMAL	SEVERE
CONTAMINATION		method	limit/base	current	history1	history2
Water		WC Method	>0.2	NEG	NEG	NEG
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>800	<b>4</b> 350	5	<b>2</b> 484
Chromium	ppm	ASTM D5185m	>10	<u> </u>	1	7
Nickel	ppm	ASTM D5185m	>5	8	<1	4
	ppm	ASTM D5185m	>15	19	0	11
Silver	ppm	ASTM D5185m	>2	<1	0	0
	ppm	ASTM D5185m	>75	<mark> </mark> 258	10	62
Lead	ppm	ASTM D5185m	>10	1	0	2
Copper	ppm	ASTM D5185m	>75	<b>à</b> 364	<1	▲ 262
	ppm	ASTM D5185m	>8	<b>1</b> 6	<1	<b>1</b> 2
	ppm	ASTM D5185m		1	1	0
Cadmium	ppm	ASTM D5185m		<1	<1	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		15	<1	9
Barium	ppm	ASTM D5185m		0	13	<1
Molybdenum	ppm	ASTM D5185m		7	<1	3
Manganese	ppm	ASTM D5185m		35	<1	19
Magnesium	ppm	ASTM D5185m		156	<1	95
Calcium	ppm	ASTM D5185m		5826	8	3653
Phosphorus	ppm	ASTM D5185m		1532	32	938
Zinc	ppm	ASTM D5185m		1719	<1	1100
Sulfur	ppm	ASTM D5185m		18587	1151	10846
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>400	<b>1427</b>	2	<b>9</b> 36
Sodium	ppm	ASTM D5185m		28	25	21
Potassium	ppm	ASTM D5185m	>20	81	5	51
VISUAL		method	limit/base	current	history1	history2
	scalar	*Visual	NONE	NONE	NONE	NONE
	scalar	*Visual	NONE	NONE	NONE	NONE
	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	MODER	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG

enter the system. We recommend that you drain the oil from the component if this has not already been done. We advise that you inspect for the source(s) of wear. We recommend an early resample to monitor this condition.

We advise that you check all areas where dirt can

## A Wear

Bearing and/or gear wear is indicated.

#### Contamination


Elemental levels of silicon (Si) and aluminum (Al) indicate alumina-silicate (coarse dirt) ingress.

### Fluid Condition

The oil is no longer serviceable due to the presence of contaminants.



# **OIL ANALYSIS REPORT**



Report Id: SHEWIC [WUSCAR] 06185314 (Generated: 05/22/2024 18:02:37) Rev: 1

Submitted By: GARRETT ADAMS

Page 4 of 4

F: x:

US 67213