

# **OIL ANALYSIS REPORT**

Sample Rating Trend



Machine Id **71-PC-24 (S/N 60C)** Component Hydraulic System Fluid Skydrol (--- LTR)

#### DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable.

## Fluid Condition


The AN level is acceptable for this fluid. The condition of the oil is suitable for further service. Chlorine 301 ppm.

SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0938108		
Sample Date		Client Info		14 May 2024		
Machine Age	hrs	Client Info		0		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		N/A		
Sample Status				NORMAL		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>20	1		
Chromium	ppm	ASTM D5185m	>20	0		
Nickel	ppm	ASTM D5185m	>20	0		
Titanium	ppm	ASTM D5185m	0	0		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>20	0		
Lead	ppm	ASTM D5185m	>20	0		
		ASTM D5185m		1		
Copper Tin	ppm	ASTM D5185m		0		
Vanadium	ppm		>20	0		
Cadmium	ppm ppm	ASTM D5185m ASTM D5185m		0		
ADDITIVES	lele	method	limit/base	current	history1	history2
Boron	0000	ASTM D5185m	mmbase	0		
Barium	ppm	ASTM D5185m		0		
	ppm			-		
Molybdenum	ppm	ASTM D5185m		0		
Manganese	ppm	ASTM D5185m		0		
Magnesium	ppm	ASTM D5185m		0		
Calcium	ppm	ASTM D5185m	110	2		
Phosphorus	ppm	ASTM D5185m	37	30420		
Zinc	ppm	ASTM D5185m		0		
Sulfur	ppm	ASTM D5185m	220	2175		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>15	0		
Sodium	ppm	ASTM D5185m		0		
Potassium	ppm	ASTM D5185m	>20	12		
Chlorine Content	ppm	ASTM D5185m		301		
Water	%	ASTM D6304	>0.750	NEG		
FLUID CLEANLIN	ESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>5000	2023		
Particles >6µm		ASTM D7647	>1300	694		
Particles >14µm		ASTM D7647	>160	93		
Particles >21µm		ASTM D7647	>40	25		
Particles >38µm		ASTM D7647	>10	1		
Particles >71µm		ASTM D7647	>3	0		
Oil Cleanliness		ISO 4406 (c)	>19/17/14	18/17/14		
FLUID DEGRADA		method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	0.04	0.354		

Contact/Location: REYNARD GOLDMAN - WOOSANCA Page 1 of 2



# **OIL ANALYSIS REPORT**



						,	
	White Metal	scalar	*Visual	NONE	NONE		
1	Yellow Metal	scalar	*Visual	NONE	NONE		
	Precipitate	scalar	*Visual	NONE	NONE		
	Silt	scalar	*Visual	NONE	NONE		
	Debris	scalar	*Visual	NONE	NONE		
					-		
*	Sand/Dirt	scalar	*Visual	NONE	NONE		
May14/24	Appearance	scalar	*Visual	NORML	NORML		
Ma	Odor	scalar	*Visual	NORML	NORML		
	Emulsified Water	scalar	*Visual	>0.750	NEG		
	Free Water	scalar	*Visual		NEG		
				12 . 14 /1		1.1.1.4	
1	FLUID PROPERT	IES	method	limit/base	current	history1	history2
	Visc @ 40°C	cSt	ASTM D445	10.55	7.74		
	Visc @ 100°C	cSt	ASTM D445	3.57	3.07		
	Viscosity Index (VI)	Scale	ASTM D2270	320	341		
			NOTWI DELTO	OLO	041		
24	SAMPLE IMAGES	\$	method	limit/base	current	history1	history2
May142	Color					no image	no image
	Bottom					no image	no image
May14/24	8 iron						
	Non-ferrous Metals	5		May14/24 May14/24 150 perticles (per 1 m) 150	Severe Abnormal		
	Non-ferrous Metals	5		30,72 7,68 7,69 7,69 820 Jule U and 192 48 48 48 48 48 48 48 48 48 48 48 48 48	Abnormal Abnormal	14μ 21μ	-22 -20 -18 -16 -14 -12
	Non-ferrous Metals	5		30,72 7,68 7,69 7,69 820 Jule U and 192 48 48 48 48 48 48 48 48 48 48 48 48 48	Abnormal Abnormal		-22 -20 -18 -16 -14 -14 -12 -10 -8 -8 -6
	Non-ferrous Metals	5		30,72 7,68 7,69 7,69 820 Jule U and 192 48 48 48 48 48 48 48 48 48 48 48 48 48	Abnormal Abnormal		-22 -20 -18 -16 -14 -14 -12 -10 -8 -8 -6
	Non-ferrous Metals	5		30,72 7,68 7,69 7,69 820 Jule U and 192 48 48 48 48 48 48 48 48 48 48 48 48 48	Abnormal Abnormal		-22 -20 -18 -16 -14 -14 -12 -10 -8 -8 -6
	Non-ferrous Metals	5		30.72 7.66 7.67 7.68 1.92 7.69 48 48 1.92 48 48 48 48 48 48 48 48 48 48 48 48 48	Abnomal Abnomal Acid Number		-22 -20 -18 -16 -14 -12 -10 -8 $-36\mu$ $71\mu$
Machine Market and M	Non-ferrous Metals	5		30,72 7,68 7,69 7,69 820 Jule U and 192 48 48 48 48 48 48 48 48 48 48 48 48 48	Abnormal Abnormal		-22 -20 -18 -16 -14 -14 -12 -10 -8 -8 -6
Laboratory Sample No. Lab Number Unique Number Tisicate L2367 rest Package discuss this sample report, Denotes test methods that	Non-ferrous Metals Non-ferrous Metals Viscosity @ 40°C Copper Viscosity @ 40°C Copper Viscosity @ 40°C Copper Viscosity @ 40°C Copper Viscosity @ 40°C Copper Viscosity @ 40°C Copper Viscosity @ 40°C Copper	I Madiso Recei Teste Diagr sts: CHL ce at 1-8 7025 sco	ived : 20 d : 29 nosed : 29 _ORINEXRF 800-237-1369 ope of accred	30.72 7.68 7.69 7.69 7.69 7.69 7.69 7.69 7.69 7.69	Abnormal Abnormal Abnormal Acid Number Acid Number	25200 W RYI SANT/ Contact: REYNA mard.goldman@ T:	-22 -20 -18 -16 -14 -12 -10 
Laboratory Sample No. Lab Number Unique Number Test Package discuss this sample report,	Non-ferrous Metals Non-ferrous Metals Viscosity @ 40°C Copper Viscosity @ 40°C Copper Viscosity @ 40°C Copper Viscosity @ 40°C Copper Viscosity @ 40°C Copper Viscosity @ 40°C Copper Viscosity @ 40°C Copper	I Madiso Recei Teste Diagr sts: CHL ce at 1-8 7025 sco	ived : 20 d : 29 nosed : 29 _ORINEXRF 800-237-1369 ope of accred	30.72 7.68 7.69 7.69 7.69 7.69 7.69 7.69 7.69 7.69	Abnormal Abnormal Abnormal Acid Number Acid Number	25200 W RYI SANT/ Contact: REYNA mard.goldman@ T:	-22 -20 -18 -16 -14 -14 -12 -10 

Report Id: WOOSANCA [WUSCAR] 06185642 (Generated: 05.

Page 2 of 2