

OIL ANALYSIS REPORT

Sample Rating Trend

Pillen Family Farms
Machine Id
LSTK 68

Diesel Engine

DIESEL ENGINE OIL SAE 40 (--- GAL)

-m2023 Apd023 Jun2023 Aug8023 G00023 Dec2023 Feb2024 Maylo22



DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. Please specify the component make and model with your next sample. Please specify the brand, type, and viscosity of the oil on your next sample.

Wear

Metal levels are typical for a new component breaking in.

Contamination

There is no indication of any contamination in the oil


Fluid Condition


The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.


SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		SBP0006876	SBP0006808	SBP0006823
Sample Date		Client Info		08 May 2024	15 Apr 2024	26 Feb 2024
Machine Age	mls	Client Info		12000	12000	12000
Oil Age	mls	Client Info		0	0	0
Oil Changed		Client Info		Not Changd	Not Changd	Not Changd
Sample Status				NORMAL	NORMAL	NORMAL
CONTAMINATION	V	method	limit/base	current	history1	history2
Fuel		WC Method	>5	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>100	7	8	15
Chromium	ppm	ASTM D5185m	>20	<1	0	<1
Nickel	ppm	ASTM D5185m	>4	0	0	<1
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m	>3	<1	0	0
Aluminum	ppm	ASTM D5185m	>20	<1	0	2
Lead	ppm	ASTM D5185m	>40	<1	1	0
Copper	ppm	ASTM D5185m	>330	0	0	<1
Tin	ppm	ASTM D5185m	>15	0	<1	<1
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	250	0	0	<1
Barium	ppm	ASTM D5185m	10	0	0	0
Molybdenum	ppm	ASTM D5185m	100	61	62	65
Manganese	ppm	ASTM D5185m		<1	0	0
Magnesium	ppm	ASTM D5185m	450	1085	1070	1037
Calcium	ppm	ASTM D5185m	3000	1226	1181	1095
Phosphorus	ppm	ASTM D5185m	1150	1154	1142	1091
Zinc	ppm	ASTM D5185m	1350	1445	1412	1327
Sulfur	ppm	ASTM D5185m	4250	4002	3841	3343
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	3	3	5
Sodium	ppm	ASTM D5185m	>216	<1	2	2
Potassium	ppm	ASTM D5185m	>20	<1	<1	2
INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>3	0.4	0.3	0.4
Nitration	Abs/cm	*ASTM D7624	>20	6.2	6.5	7.1
Sulfation	Abs/.1mm	*ASTM D7415	>30	18.6	19.0	19.2
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	13.9	14.2	14.7
Base Number (BN)	mg KOH/g	ASTM D2896	8.5	8.6	8.4	8.3



OIL ANALYSIS REPORT










VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG


FLUID PROPERTIES		method				history2
Visc @ 100°C	cSt	ASTM D445	14.4	13.9	13.7	13.7

GRAPHS













Laboratory Sample No.

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 : SBP0006876 Lab Number : 06193297 Unique Number : 11050049

Received : 28 May 2024 **Tested**

: 30 May 2024 Diagnosed

: 30 May 2024 - Wes Davis

Test Package : FLEET Certificate 12367 To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Pillen Family Farms - 722828

26741 NE-91 Humphrey, NE US 61357 Contact: Troy Runge

troyfr@pillenfamilyfarms.com

T: (308)390-6733