


OIL ANALYSIS REPORT

Area [24156671]

B21613 - 9 (S/N 69700024)Component
Gearbox

JAX MAGNA-PLATE 85W140-FG (--- GAL)



DIAGNOSIS

Recommendation

We recommend you service the filters on this component if applicable. Resample at the next service interval to monitor.

All component wear rates are normal.

Contamination

There is a high amount of particulates present in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0921323	WC0885464	WC0866690
Sample Date		Client Info		21 May 2024	07 Feb 2024	05 Nov 2023
Machine Age	yrs	Client Info		0	0	0
Oil Age	yrs	Client Info		1	0	0
Oil Changed		Client Info		Not Changd	N/A	N/A
Sample Status				ABNORMAL	ABNORMAL	ABNORMAL
CONTAMINATION	١	method	limit/base	current	history1	history2
Water		WC Method	>0.2	NEG	NEG	NEG
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>200	6	5	4
Chromium	ppm	ASTM D5185m	>15	0	0	0
Nickel	ppm	ASTM D5185m	>15	0	0	0
Titanium	ppm	ASTM D5185m		<1	0	0
Silver	ppm	ASTM D5185m		<1	0	0
Aluminum	ppm	ASTM D5185m	>25	<1	0	0
Lead	ppm	ASTM D5185m	>100	<1	0	0
Copper	ppm	ASTM D5185m	>200	9	8	10
Tin	ppm	ASTM D5185m	>25	<1	0	0
Vanadium	ppm	ASTM D5185m		<1	0	<1
Cadmium	ppm	ASTM D5185m		<1	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		1	2	1
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		3	2	2
Manganese	ppm	ASTM D5185m		<1	0	0
Magnesium	ppm	ASTM D5185m		<1	0	0
Calcium	ppm	ASTM D5185m		0	0	0
Phosphorus	ppm	ASTM D5185m		439	433	376
Zinc	ppm	ASTM D5185m		7	6	0
Sulfur	ppm	ASTM D5185m		6156	5431	4642
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>50	1	<1	1
Sodium	ppm	ASTM D5185m		<1	0	0
Potassium	ppm	ASTM D5185m	>20	2	0	0
FLUID CLEANLIN	ESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>20000	165090	<u>4</u> 240714	<u></u> 166707
Particles >6µm		ASTM D7647	>5000	62564	<u>▲</u> 59645	<u>▲</u> 56062
Particles >14µm		ASTM D7647	>640	802	1 790	▲ 778
Particles >21µm		ASTM D7647	>160	57	91	83
Particles >38µm		ASTM D7647	>40	1	2	3
Particles >71µm		ASTM D7647	>10	0	0	0
Oil Cloopliness		ISO 4406 (c)	>21/19/16	25/23/17	<u>\$\Delta\$ 25/23/17</u>	25/23/17
Oil Cleanliness		100 4400 (0)	<i>></i> 21/13/10	25/25/11	25/20/17	20/20/17


Acid Number (AN)


mg KOH/g ASTM D8045


0.66 0.57 Contact/Location: Craig Bennett - HORBEL




OIL ANALYSIS REPORT










VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
FLUID PROPERTIES		method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445		687	733	730
SAMPLE IMAGES		method	limit/base	current	history1	history2

Color			
3ottom			







Laboratory Sample No.

Lab Number : 06193957

: WC0921323

С

В

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Unique Number : 11056080

Received **Tested** Diagnosed

: 29 May 2024 : 30 May 2024

: 31 May 2024 - Angela Borella

Test Package : IND 2 (Additional Tests: PrtCount) Certificate 12367 To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

HORMEL FOODS-BELOIT

3000 KENNEDY DRIVE BELOIT, WI

US 53511 Contact: Craig Bennett cabennett@hormel.com

T: F: (608)365-8322