

# **OIL ANALYSIS REPORT**

Sample Rating Trend



Machine Id

# 6975195 (S/N 1169) Component Compressor

KAESER SIGMA (OEM) M-460 (--- GAL)

#### Recommendation

No corrective action is recommended at this time. Oil and filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

### Contamination

There is a moderate amount of particulates present in the oil.

#### **Fluid Condition**

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

			Aug2023	May2024		
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		KCPA012391	KCPA005663	
Sample Date		Client Info		09 May 2024	07 Aug 2023	
Machine Age	hrs	Client Info		30317	49808	
Oil Age	hrs	Client Info		3357	0	
Oil Changed		Client Info		Changed	N/A	
Sample Status				ATTENTION	ATTENTION	
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0	0	
Chromium	ppm	ASTM D5185m	>10	0	0	
Nickel	ppm	ASTM D5185m	>3	0	0	
Titanium	ppm	ASTM D5185m	>3	<1	0	
Silver	ppm	ASTM D5185m	>2	<1	0	
Aluminum	ppm	ASTM D5185m	>10	<1	<1	
Lead	ppm	ASTM D5185m	>10	<1	0	
Copper	ppm	ASTM D5185m	>50	2	4	
Tin	ppm	ASTM D5185m	>10	<1	0	
Vanadium	ppm	ASTM D5185m		<1	0	
Cadmium	ppm	ASTM D5185m		<1	0	
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	0	0	
Barium	ppm	ASTM D5185m	90	68	53	
Molybdenum	ppm	ASTM D5185m	0	0	0	
Manganese	ppm	ASTM D5185m		<1	0	
Magnesium	ppm	ASTM D5185m	100	62	54	
Calcium	ppm	ASTM D5185m	0	3	<1	
Phosphorus	ppm	ASTM D5185m	0	22	<1	
Zinc	ppm	ASTM D5185m	0	6	6	
Sulfur	ppm	ASTM D5185m	23500	22427	21750	
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	<1	<1	
Sodium	ppm	ASTM D5185m		35	27	
Potassium	ppm	ASTM D5185m	>20	8	6	
Water	%	ASTM D6304	>0.05	0.020	0.033	
ppm Water	ppm	ASTM D6304	>500	208	336.9	
FLUID CLEANLIN	ESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647		8289	2676	
Particles >6µm		ASTM D7647	>1300	<u> </u>	888	
Particles >14µm		ASTM D7647	>80	<b>9</b> 0	93	
Particles >21µm		ASTM D7647	>20	16	_ 22	
Particles >38µm		ASTM D7647	>4	0	1	
Particles >71µm		ASTM D7647	>3	0	0	
Oil Cleanliness		ISO 4406 (c)	>/17/13	<b>20/18/14</b>	19/17/14	
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	1.0	0.35	0.35	



## **OIL ANALYSIS REPORT**







Laboratory Sample No.

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 : KCPA012391 Lab Number : 06193975 Unique Number : 11056098

Received : 29 May 2024 **Tested** 

: 30 May 2024 Diagnosed : 31 May 2024 - Angela Borella

5187 CAMINO RUIZ CAMARILLO, CA US 93012

Contact: Service Manager

Test Package : IND 2 ( Additional Tests: KF, PrtCount ) Certificate 12367 To discuss this sample report, contact Customer Service at 1-800-237-1369.

 $^st$  - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Contact/Location: Service Manager - GOLCAMCA

T:

F: