

OIL ANALYSIS REPORT

Area **Refrigeration** 2 High Stage Compressor NCR (S/N 3235030) Component

Refrigeration Compressor

COLD STAR CS-2033-SC (150 GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.



Sample Rating Trend

SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0892829	WC0632331	WC0442191
Sample Date		Client Info		16 May 2024	15 Dec 2021	30 Jul 2021
Machine Age	hrs	Client Info		54550	0	35713
Oil Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Filtered	N/A	N/A
Sample Status				NORMAL	NORMAL	NORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>8	1	0	2
Chromium	ppm	ASTM D5185m	>2	<1	0	0
Nickel	ppm	ASTM D5185m		<1	0	0
Titanium	ppm	ASTM D5185m		<1	0	0
Silver	ppm	ASTM D5185m	>2	1	<1	0
Aluminum	ppm	ASTM D5185m	>3	1	0	0
Lead	ppm	ASTM D5185m	>2	<1	0	0
Copper	ppm	ASTM D5185m	>8	1	0	0
Tin	ppm	ASTM D5185m	>4	<1	0	0
Antimony	ppm	ASTM D5185m			0	0
Vanadium	ppm	ASTM D5185m		<1	0	0
Cadmium	ppm	ASTM D5185m		<1	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	0
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		<1	0	0
Manganese	ppm	ASTM D5185m		<1	0	0
Magnesium	ppm	ASTM D5185m		<1	0	0
Calcium	ppm	ASTM D5185m		0	0	0
Phosphorus	ppm	ASTM D5185m		8	16	8
Zinc	ppm	ASTM D5185m		0	0	0
Sulfur	ppm	ASTM D5185m		0	0	0
CONTAMINANTS	3	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>15	1	0	<1
Sodium	ppm	ASTM D5185m		0	0	0
Potassium	ppm	ASTM D5185m	>20	<1	0	0
Water	%	ASTM D6304	>0.01	0.004	0.003	0.002
ppm Water	ppm	ASTM D6304		40	27.2	19.7
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>10000	3043	9389	8841
Particles >6µm		ASTM D7647	>2500	326	1638	1393
Particles >14µm		ASTM D7647	>320	6	38	20
Particles >21µm		ASTM D7647	>80	1	7	2
Particles >38µm		ASTM D7647	>20	0	0	0
Particles >71µm		ASTM D7647	>4	0	0	0
Oil Cleanliness		ISO 4406 (c)	>20/18/15	19/16/10	20/18/12	20/18/11
FLUID DEGRADA		method	limit/base	current	history1	history2
Acid Number (AN)	ma KOU/a			0.014	0.012	0.014


Acid Number (AN) mg KOH/g ASTM D974


0.014 0.013 0.014 Contact/Location: STEVE RIEDEL - TROBRA


Report Id: TROBRA [WUSCAR] 06194052 (Generated: 05/31/2024 19:35:04) Rev: 1




OIL ANALYSIS REPORT










VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	LIGHT	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.01	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
FLUID PROPER	TIES	method	limit/base	current	history1	history
Visc @ 40°C	cSt	ASTM D445		65.0	63.8	64.0
SAMPLE IMAGES		method	limit/base	current	history1	history
Color						
00.01						and the second second

Bottom

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.



Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012) Report Id: TROBRA [WUSCAR] 06194052 (Generated: 05/31/2024 19:35:04) Rev: 1

Certificate 12367

Contact/Location: STEVE RIEDEL - TROBRA

Page 2 of 2

T: (941)742-2992

F: (941)749-3980