

## **OIL ANALYSIS REPORT**

Sample Rating Trend



### Area **NOT** GIVEN ATLAS COPCO CAI712467 - MB COMPANIES (S/N API712467) Component Compressor

#### Recommendation

Resample at the next service interval to monitor. Please specify the brand, type, and viscosity of the oil on your next sample.

### Wear

All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil.


#### Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORM	<b>NATION</b>	method	limit/base	current	history1	history2
Sample Number		Client Info		UCZ06194186		
Sample Date		Client Info		21 May 2024		
Machine Age	hrs	Client Info		15050		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		N/A		
Sample Status				NORMAL		
CONTAMINATION		method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	1		
Chromium	ppm	ASTM D5185m	>5	۔ <1		
Nickel	ppm	ASTM D5185m		<1		
Titanium	ppm	ASTM D5185m		<1		
Silver	ppm	ASTM D5185m		1		
Aluminum	ppm	ASTM D5185m	>15	1		
Lead	ppm	ASTM D5185m	>65	<1		
Copper	ppm	ASTM D5185m	>65	2		
Tin	ppm	ASTM D5185m	>10	<1		
Vanadium	ppm	ASTM D5185m		<1		
Cadmium	ppm	ASTM D5185m		<1		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0		
Barium	ppm	ASTM D5185m		0		
Molybdenum	ppm	ASTM D5185m		<1		
Manganese	ppm	ASTM D5185m		1		
Magnesium	ppm	ASTM D5185m		2		
Calcium	ppm	ASTM D5185m		0		
Phosphorus	ppm	ASTM D5185m		19		
Zinc	ppm	ASTM D5185m		30		
Sulfur	ppm	ASTM D5185m		0		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>35	6		
Sodium	ppm	ASTM D5185m		<1		
Potassium	ppm	ASTM D5185m	>20	1		
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		0.18		



# **OIL ANALYSIS REPORT**



	VISUAL		method	limit/base	current	history1	history2	
	White Metal	scalar	*Visual	NONE	NONE			
	Yellow Metal	scalar	*Visual	NONE	NONE			
	Precipitate	scalar	*Visual	NONE	NONE			
	Silt	scalar	*Visual	NONE	NONE			
	Debris	scalar	*Visual	NONE	NONE			
	Sand/Dirt	scalar	*Visual	NONE	NONE			
May21/24	Appearance	scalar	*Visual	NORML	NORML			
Ma	Odor	scalar	*Visual	NORML	NORML			
	Emulsified Water	scalar	*Visual	>0.1	NEG			
	Free Water	scalar	*Visual		NEG			
	FLUID PROPERT		method	limit/base	current	history1	history2	
	Visc @ 40°C	cSt	ASTM D445		49.9			
	SAMPLE IMAGES	5	method	limit/base	current	history1	history2	
May21/24 +	Color				a.	no image	no image	
	Bottom					no image	no image	
	Non-ferrous Metal			May21/24				
				24				
	Viscosity @ 40°C			57/12/keW (b)	Acid Number			
	50 - 9 			(B) 0.20 (B) 0.15 (B) 0.015 (B) 0.015 (B) 0.00 Void Void Void Void Void Void Void Void	24			
Laboratory Sample No. Lab Number	FOTOTORY FOTOTORY FOTOTORY   : WearCheck USA - 501 Madison Ave., Cary, NC 27513 ZORN COMP & EQUIPMENT CO   : UCZ06194186 Received : 29 May 2024 733 POTTS   : 06194186 Tested : 30 May 2024 GREEN BAY   : 11056309 Diagnosed : 30 May 2024 - Wes Davis US 54   : IND 2 Contact: DEAN SC : 20 May 2024 - Wes Davis Contact: DEAN SC							

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Contact/Location: DEAN SCHAD - UCZORGRE

F: (920)499-1168