

FUEL REPORT

[W156258] **IAD2-A-GEN-02 IAD2-A-GEN-02**

Diesel Fuel

DIESEL FUEL No. 2 (--- GAL)

Sample Rating Trend



Recommendation

All laboratory tests indicate that this sample meets specifications for No.2 ultra-low-sulfur diesel fuel.

Corrosion

All metal levels are normal indicating no corrosion in the system.

Contaminants

There is no bacteria or fungus (yeast and/or mold) indicated in the sample. The water content is negligible. There is no indication of any contamination in the fuel.


Fuel Condition


Sulfur value derived by ASTM D5453 method for ULSD validation. Sulfur level is acceptable for ULSD specification.

| | | | 1 | May2024 | | |
|---------------|--------|-------------|------------|-------------|----------|----------|
| SAMPLE INFORM | MATION | method | limit/base | current | history1 | history2 |
| Sample Number | | Client Info | | WC0911272 | | |
| Sample Date | | Client Info | | 13 May 2024 | | |
| Machine Age | hrs | Client Info | | 0 | | |
| Sample Status | | | | NORMAL | | |
| PHYSICAL PROP | ERTIES | method | limit/base | current | history1 | history2 |
| ASTM Color | scalar | *ASTM D1500 | | L4.5 | | |
| Visc @ 40°C | cSt | ASTM D445 | 4.1 | 2.46 | | |
| SULFUR CONTE | NT | method | limit/base | current | history1 | history2 |
| Sulfur | ppm | ASTM D5185m | | 0 | | |
| Sulfur (UVF) | ppm | ASTM D5453 | | 10 | | |
| | | | 11 11 11 | | 12.4 | |
| CONTAMINANTS | | method | limit/base | current | history1 | history2 |
| Silicon | ppm | ASTM D5185m | <1.0 | <1 | | |
| Sodium | ppm | ASTM D5185m | < 0.1 | 2 | | |
| Potassium | ppm | ASTM D5185m | <0.1 | <1 | | |
| Water | % | ASTM D6304 | < 0.05 | 0.001 | | |
| ppm Water | ppm | ASTM D6304 | <500 | 9 | | |
| % Gasoline | % | *In-House | < 0.50 | 0.0 | | |
| % Biodiesel | % | *In-House | <20.0 | 0.0 | | |
| HEAVY METALS | | method | limit/base | current | history1 | history2 |
| Aluminum | ppm | ASTM D5185m | < 0.1 | 0 | | |
| Nickel | ppm | ASTM D5185m | <0.1 | 0 | | |
| Lead | ppm | ASTM D5185m | <0.1 | <1 | | |
| Vanadium | ppm | ASTM D5185m | < 0.1 | <1 | | |
| Iron | ppm | ASTM D5185m | <0.1 | 0 | | |
| Calcium | ppm | ASTM D5185m | | 0 | | |
| Magnesium | ppm | ASTM D5185m | <0.1 | 0 | | |
| Phosphorus | ppm | ASTM D5185m | <0.1 | <1 | | |
| Zinc | ppm | ASTM D5185m | <0.1 | 0 | | |
| SAMPLE IMAGES | 6 | method | limit/base | current | history1 | history2 |
| Color | | | | | no image | no image |
| Bottom | | | | | no image | no image |



FUEL REPORT







Certificate 12367

Laboratory

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 **Sample No.** : WC0911272 Lab Number : 06194549 Unique Number : 11056672

Test Package: DF-5 (Additional Tests: PrtCount, Screen)

Received Tested Diagnosed

: 29 May 2024 : 12 Jun 2024

: 12 Jun 2024 - Doug Bogart

4541 PRESLYN DR RALEIGH, NC US 27616

NATIONAL POWER CORP

Contact: Brandon Daniels Brandon.Daniels@natpow.com

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

To discuss this sample report, contact Customer Service at 1-800-237-1369.

F: (919)790-9714 Contact/Location: Brandon Daniels - NATRAL