

OIL ANALYSIS REPORT

Sample Rating Trend





MINING ME-45 CATERPILLAR 938 P5K02655 Diesel Engine

SHELL ROTELLA T3 15W40 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Area

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is acceptable for the time in service.

SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0938185		
Sample Date		Client Info		22 May 2024		
Machine Age	hrs	Client Info		5700		
Oil Age	hrs	Client Info		255		
Oil Changed		Client Info		Changed		
Sample Status				NORMAL		
CONTAMINATION	١	method	limit/base	current	history1	history2
Fuel		WC Method	>5	<1.0		
Water		WC Method	>0.2	NEG		
Glycol		WC Method		NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>100	4		
Chromium	ppm	ASTM D5185m	>20	<1		
Nickel	ppm	ASTM D5185m	>2	<1		
Titanium	ppm	ASTM D5185m	>2	<1		
Silver	ppm	ASTM D5185m	>2	0		
Aluminum	ppm	ASTM D5185m	>25	11		
Lead	ppm	ASTM D5185m	>40	<1		
Copper	ppm	ASTM D5185m	>330	<1		
Tin	ppm	ASTM D5185m	>15	<1		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		<1		
ADDITIVES		method	limit/base	current	history1	history2
ADDITIVES Boron	ppm	method ASTM D5185m	limit/base	current 74	history1	history2
	ppm ppm					
Boron		ASTM D5185m	10	74		
Boron Barium	ppm	ASTM D5185m ASTM D5185m	10 0	74 1		
Boron Barium Molybdenum	ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m	10 0	74 1 86		
Boron Barium Molybdenum Manganese	ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	10 0 10	74 1 86 0		
Boron Barium Molybdenum Manganese Magnesium	ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	10 0 10 10	74 1 86 0 69		
Boron Barium Molybdenum Manganese Magnesium Calcium	ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	10 0 10 10 2600	74 1 86 0 69 2021	 	
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus	ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	10 0 10 10 2600 1050	74 1 86 0 69 2021 1070	 	
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS	ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	10 0 10 2600 1050 1250 3900	74 1 86 0 69 2021 1070 1114 3692 current	 	
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon	ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m method	10 0 10 2600 1050 1250 3900	74 1 86 0 69 2021 1070 1114 3692 current 6		
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium	ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m method ASTM D5185m	10 0 10 2600 1050 1250 3900 limit/base	74 1 86 0 69 2021 1070 1114 3692 <u>current</u> 6 51	 history1	 history2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium	ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m	10 0 10 2600 1050 1250 3900 limit/base >25	74 1 86 0 69 2021 1070 1114 3692 current 6	 history1 	 history2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium INFRA-RED	ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m	10 0 10 2600 1050 1250 3900 limit/base >25	74 1 86 0 69 2021 1070 1114 3692 current 6 51 32 current	 history1	 history2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium INFRA-RED Soot %	ppm	ASTM D5185m ASTM D5185m	10 0 10 2600 1050 1250 3900 limit/base >25 >20 limit/base >3	74 1 86 0 69 2021 1070 1114 3692 <u>current</u> 6 51 32 <u>current</u> 0.2	 history1 	 history2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium INFRA-RED Soot % Nitration	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m	10 0 10 2600 1050 1250 3900 <i>limit/base</i> >25 20 <i>limit/base</i> >3 >20	74 1 86 0 69 2021 1070 1114 3692 <u>current</u> 6 51 32 <u>current</u> 0.2 8.5	 history1 history1	history2 history2 history2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium INFRA-RED Soot %	ppm	ASTM D5185m ASTM D5185m	10 0 10 2600 1050 1250 3900 limit/base >25 >20 limit/base >3	74 1 86 0 69 2021 1070 1114 3692 <u>current</u> 6 51 32 <u>current</u> 0.2	 history1 history1	 history2 history2 history2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium INFRA-RED Soot % Nitration	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m	10 0 10 2600 1050 1250 3900 <i>limit/base</i> >25 20 <i>limit/base</i> >3 >20	74 1 86 0 69 2021 1070 1114 3692 <u>current</u> 6 51 32 <u>current</u> 0.2 8.5	 history1 history1 	history2 history2 history2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium INFRA-RED Soot % Nitration Sulfation	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m	10 0 10 2600 1050 1250 3900 imit/base >25 imit/base >3 >20 >30	74 1 86 0 69 2021 1070 1114 3692 <u>current</u> 6 51 32 <u>current</u> 0.2 8.5 18.4	 history1 history1	 history2 history2 history2



OIL ANALYSIS REPORT

FT-IR (Direct Tren	d)	VISUAL		method	limit/base	current	history1	history2
30 - Oxidation		White Metal	scalar	*Visual	NONE	NONE		
25 - Conorma Sulfation		Yellow Metal	scalar	*Visual	NONE	NONE		
ш»20-		Precipitate	scalar	*Visual	NONE	NONE		
15-		Silt	scalar	*Visual	NONE	NONE		
10-		Debris	scalar	*Visual	NONE	NONE		
5	-	Sand/Dirt	scalar	*Visual	NONE	NONE		
May22/24	May22/24	Appearance	scalar	*Visual	NORML	NORML		
May	May	Odor	scalar	*Visual	NORML	NORML		
Base Number		Emulsified Water	scalar	*Visual	>0.2	NEG		
12.0 Base		Free Water	scalar	*Visual		NEG		
(10.0		FLUID PROPER	TIES	method	limit/base	current	history1	history2
ے۔ بے 6.0 -		Visc @ 100°C	cSt	ASTM D445	15.5	13.1		
4.0		GRAPHS						
2.0 -		Ferrous Alloys						
0.0		10iron 1						
May22/24		8 - chromium						
Mar	- WA	inckci						
Viscosity @ 100°C		6						
19 18 Abnormal		4						
17-		2						
© 16 - Base 0 15 -								
215 3 14		0						
13 Abnormal		May22/24			May22/24			
12 -		_	la		W			
114	2	Non-ferrous Meta	15					
May22/2 [,]	CC	copper						
Rea.	-	8 - management tin						
		6-						
		E .						
		4						
		2						

		2/24			ay22/24			
		May2			May2			
		Viscosity @ 100°C	2			Base Number		
		19			12.0	,		
		18 - Abnormal			10.0	Base		
		17			(B/HO			
		O 15 Base			y Bu			
		Co ¹⁶ Base 0015 314			(D/H0) 8.0- 			
		10			N 958 4.0			
		13 Abnormal			2.0			
		11			0.0			
		May22/24			May22/24	May22/24		May22/24
		May			May	May		Mavi
	To discuss this sample report, - Denotes test methods that	: 11057125 : CONST (Additional T contact Customer Serv are outside of the ISO 1	Recei Teste Diagr Tests: TBI vice at 1-8	ived : 30 id : 31 nosed : 31 N) 200-237-1369 ope of accrea) May 2024 May 2024 May 2024 - Sea 9. Jitation.	ma	107 M M Contact: M arty.beacham@ T: (CINTYRE - 028 MACON ROAD CINTYRE, GA US 31504 Marty Beacham coviacorp.com (478)946-8965
	Statements of conformity to sp		on the sin	nple accepta	nce decision r	rule (JCGM 106	:2012) Submitted D	F:

Submitted By: Rodney Arnold

Page 2 of 2