


OIL ANALYSIS REPORT

Sample Rating Trend



Machine Id

KAESER 7122712

Component Compressor

KAESER SIGMA (OEM) M-460 (--- GAL)

DIAGNOSIS

Recommendation

Oil and filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is a high amount of particulates present in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is acceptable for the time in service.

		Jun2020 -	Jul2021 Jan2022 Sep20	22 Nov2022 Apr2023 0ct2023	May2024	
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		KCPA017845	KCPA006799	KCP40331D
Sample Date		Client Info		15 May 2024	20 Oct 2023	12 Apr 2023
Machine Age	hrs	Client Info		11581	8189	5923
Oil Age	hrs	Client Info		3392	0	2332
Oil Changed		Client Info		Changed	N/A	Changed
Sample Status				ABNORMAL	ABNORMAL	ABNORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	<1	0	0
Chromium	ppm	ASTM D5185m	>10	<1	<1	0
Nickel	ppm	ASTM D5185m	>3	0	0	0
Titanium	ppm	ASTM D5185m	>3	<1	<1	0
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum	ppm	ASTM D5185m	>10	2	3	0
Lead	ppm	ASTM D5185m	>10	<1	0	0
Copper	ppm	ASTM D5185m	>50	2	3 0	4
Tin	ppm	ASTM D5185m	>10	 <1	0	0
Vanadium	ppm	ASTM D5185m		<1	<1	0
Cadmium	ppm	ASTM D5185m		<1	0	0
ADDITIVES	PPIII	method	limit/base	current		history2
					history1	
Boron	ppm	ASTM D5185m	0	0	0	0
Barium	ppm	ASTM D5185m	90	4	0	6
Molybdenum	ppm	ASTM D5185m	0	<1	0	0
Manganese	ppm	ASTM D5185m		0	0	<1
Magnesium	ppm	ASTM D5185m	100	50	5	31
Calcium	ppm	ASTM D5185m	0	3	<1	2
Phosphorus	ppm	ASTM D5185m	0	16	0	1
Zinc	ppm	ASTM D5185m	0	5	31	33
Sulfur	ppm	ASTM D5185m	23500	13602	22777	21590
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	2	0	0
Sodium	ppm	ASTM D5185m		25	0	49
Potassium	ppm	ASTM D5185m	>20	5	2	4
Water	%	ASTM D6304	>0.05	0.009	0.014	0.019
ppm Water	ppm	ASTM D6304	>500	96	145.9	197.9
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4μm		ASTM D7647		19837	29077	12117
Particles >6µm		ASTM D7647	>1300	<u>A</u> 6172	△ 9447	<u>▲</u> 6129
Particles >14μm		ASTM D7647	>80	<u>^</u> 528	<u></u> 894	126
Particles >21µm		ASTM D7647	>20	<u> </u>	<u>^</u> 218	9
Particles >38μm		ASTM D7647	>4	4	<u>^</u> 6	1
Particles >71µm		ASTM D7647	>3	0	0	0
Oil Cleanliness		ISO 4406 (c)	>/17/13	<u>^</u> 21/20/16	<u>22/20/17</u>	<u>\$\text{21/20/14}\$</u>
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	1.0	0.34	0.32	0.31



OIL ANALYSIS REPORT







Certificate 12367

Laboratory Sample No.

Lab Number Unique Number : 11057549

: KCPA017845

: 06195426

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 30 May 2024 **Tested** : 31 May 2024

: 31 May 2024 - Angela Borella

Diagnosed

Test Package : IND 2 (Additional Tests: KF, PrtCount) To discuss this sample report, contact Customer Service at 1-800-237-1369.

 st - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

US 75125 Contact: Service Manager

WASTE MANAGEMENT

1251 N CENTRAL ST

T: F:

FERRIS, TX