


OIL ANALYSIS REPORT

Sample Rating Trend



Machine Id

KAESER AS 25T 3378330 (S/N 1444)

Compressor

KAESER SIGMA (OEM) S-460 (--- QTS)

DIAGNOSIS

Recommendation

Oil and filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

All component wear rates are normal.

Contamination

There is a high amount of particulates present in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is acceptable for the time in service.

SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		KCPA012992	KCP44269	KCP25169
Sample Date		Client Info		15 May 2024	17 Mar 2022	16 Mar 2020
Machine Age	hrs	Client Info		21220	18038	14775
Oil Age	hrs	Client Info		0	3000	2315
Oil Changed		Client Info		Changed	Changed	Changed
Sample Status				ABNORMAL	ATTENTION	ABNORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	<1	<1	0
Chromium	ppm	ASTM D5185m	>10	<1	0	0
Nickel	ppm	ASTM D5185m	>3	0	<1	<1
Titanium	ppm	ASTM D5185m	>3	<1	0	0
Silver	ppm	ASTM D5185m	>2	0	1	0
Aluminum	ppm	ASTM D5185m	>10	2	<1	<1
Lead	ppm	ASTM D5185m	>10	<1	0	<1
Copper	ppm	ASTM D5185m	>50	13	11	12
Tin	ppm	ASTM D5185m	>10	<1	<1	0
Antimony	ppm	ASTM D5185m				0
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		<1	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	27
Barium	ppm	ASTM D5185m	90	<1	0	0
Molybdenum	ppm	ASTM D5185m		<1	0	0
Manganese	ppm	ASTM D5185m		0	<1	<1
Magnesium	ppm	ASTM D5185m	90	4	23	29
Calcium	ppm	ASTM D5185m	2	1	0	<1
Phosphorus	ppm	ASTM D5185m		16	2	2
Zinc	ppm	ASTM D5185m		18	2	0
Sulfur	ppm	ASTM D5185m		14812	15429	15517
CONTAMINANTS	}	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	<1	<1	0
Sodium	ppm	ASTM D5185m		7	7	10
Potassium	ppm	ASTM D5185m	>20	2	0	<1
Water	%	ASTM D6304	>0.05	0.018	0.010	0.017
ppm Water	ppm	ASTM D6304	>500	186	109.2	173.7
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4μm		ASTM D7647		8666	3950	44884
Particles >6µm		ASTM D7647	>1300	<u>^</u> 2529	1109	<u>▲</u> 15108
Particles >14μm		ASTM D7647	>80	<u>^</u> 243	112	<u> </u>
Particles >21μm		ASTM D7647	>20	<u>^</u> 70	3 4	▲ 232
Particles >38μm		ASTM D7647	>4	3	3	<u> </u>
Particles >71μm		ASTM D7647	>3	0	0	<u>4</u>
Oil Cleanliness		ISO 4406 (c)	>/17/13	<u>^</u> 20/19/15	17/14	▲ 21/17
FLUID DEGRADA	TION	method	limit/base	current	history1	history2



OIL ANALYSIS REPORT







Certificate 12367

Sample No.

Lab Number : 06195427 Unique Number : 11057550

: KCPA012992

Received **Tested** Diagnosed Test Package : IND 2 (Additional Tests: KF, PrtCount)

: 30 May 2024 : 31 May 2024

: 31 May 2024 - Angela Borella

1000 LOFLAND DR WAXAHACHIE, TX

US 75165 Contact: SERVICE MANAGER

To discuss this sample report, contact Customer Service at 1-800-237-1369.

 st - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Report Id: AUTWAX [WUSCAR] 06195427 (Generated: 05/31/2024 16:58:06) Rev: 1

Contact/Location: SERVICE MANAGER ? - AUTWAX

T:

F: