


# **OIL ANALYSIS REPORT**

**RGS 20** RGS 20 X-Z AXIS (S/N 16-4310-0145)

Gearbox

{not provided} (--- QTS)



## DIAGNOSIS

#### Recommendation

Little or no information is provided as to the component and lubricant being tested. Recommendations are therefore generic in nature and may not apply to the current application. Please forward information as to equipment type, reservoir capacity, lubricant type and any pertinent information to allow for a more accurate assessment. Resample at the next service interval to monitor. NOTE: Please provide information regarding reservoir capacity, filter type and micron rating with next sample. Please specify the brand, type, and viscosity of the oil on your next sample.

#### Wear

All component wear rates are normal.

#### Contamination

The water content is negligible. There is no indication of any contamination in the oil.

### **Fluid Condition**

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

| SAMPLE INFORM    | MATION   | method      | limit/base | current     | history1    | history2      |
|------------------|----------|-------------|------------|-------------|-------------|---------------|
| Sample Number    |          | Client Info |            | RP0044269   | RP0038517   | RP0035557     |
| Sample Date      |          | Client Info |            | 29 May 2024 | 12 Jan 2024 | 19 Jul 2023   |
| Machine Age      | hrs      | Client Info |            | 0           | 0           | 0             |
| Oil Age          | hrs      | Client Info |            | 0           | 0           | 0             |
| Oil Changed      |          | Client Info |            | N/A         | N/A         | N/A           |
| Sample Status    |          |             |            | NORMAL      | NORMAL      | ABNORMAL      |
| WEAR METALS      |          | method      | limit/base | current     | history1    | history2      |
| PQ               |          | ASTM D8184  |            | 15          | 17          | 44            |
| Iron             | ppm      | ASTM D5185m | >200       | 2           | 0           | 8             |
| Chromium         | ppm      | ASTM D5185m | >15        | 0           | 0           | 0             |
| Nickel           | ppm      | ASTM D5185m | >15        | 0           | 0           | 0             |
| Titanium         | ppm      | ASTM D5185m |            | 0           | 0           | 0             |
| Silver           | ppm      | ASTM D5185m |            | 0           | 0           | <1            |
| Aluminum         | ppm      | ASTM D5185m | >25        | 0           | <1          | 0             |
| Lead             | ppm      | ASTM D5185m | >100       | 0           | 0           | <1            |
| Copper           | ppm      | ASTM D5185m | >200       | 0           | 1           | <1            |
| Tin              | ppm      | ASTM D5185m | >25        | <1          | 0           | 0             |
| Vanadium         | ppm      | ASTM D5185m |            | 0           | 0           | 0             |
| Cadmium          | ppm      | ASTM D5185m |            | 0           | 0           | <1            |
| ADDITIVES        |          | method      | limit/base | current     | history1    | history2      |
| Boron            | ppm      | ASTM D5185m |            | 0           | 0           | 0             |
| Barium           | ppm      | ASTM D5185m |            | 0           | 0           | <1            |
| Molybdenum       | ppm      | ASTM D5185m |            | 0           | 0           | 0             |
| Manganese        | ppm      | ASTM D5185m |            | <1          | <1          | <1            |
| Magnesium        | ppm      | ASTM D5185m |            | 2           | 2           | <1            |
| Calcium          | ppm      | ASTM D5185m |            | 5           | 2           | 43            |
| Phosphorus       | ppm      | ASTM D5185m |            | 188         | 188         | 176           |
| Zinc             | ppm      | ASTM D5185m |            | 13          | 64          | 70            |
| CONTAMINANTS     | ;        | method      | limit/base | current     | history1    | history2      |
| Silicon          | ppm      | ASTM D5185m | >50        | 0           | 0           | 0             |
| Sodium           | ppm      | ASTM D5185m |            | 1           | 0           | 0             |
| Potassium        | ppm      | ASTM D5185m | >20        | <1          | 0           | <1            |
| Water            | %        | ASTM D6304  | >0.2       | 0.005       | 0.007       | ▲ 0.861       |
| ppm Water        | ppm      | ASTM D6304  | >2000      | 53          | 74          | <u>▲</u> 8610 |
| FLUID DEGRADA    | TION     | method      | limit/base | current     | history1    | history2      |
| Acid Number (AN) | mg KOH/g | ASTM D8045  |            | 0.35        | 0.33        | 0.59          |



## **OIL ANALYSIS REPORT**







Certificate 12367

Laboratory Sample No.

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 : RP0044269 Lab Number : 06195524 Unique Number : 11057647

Diagnosed

Test Package : IND 2 ( Additional Tests: PQ )

To discuss this sample report, contact Customer Service at 1-800-237-1369.  $^st$  - Denotes test methods that are outside of the ISO 17025 scope of accreditation. **OUTOKUMPU STAINLESS USA** 

HWY 43 N CALVERT, AL US 36513

Contact: MARIO JOHNSON Mario.johnson@outokumpu.com T: (251)321-4105

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Received

**Tested** 

: 30 May 2024

: 31 May 2024

: 31 May 2024 - Wes Davis

Report Id: OUTCALAL [WUSCAR] 06195524 (Generated: 05/31/2024 15:35:57) Rev: 1

Submitted By: DALE ROBINSON

F: x: