


OIL ANALYSIS REPORT

ACS-FG-4600 [419059]

ATLAS COPCO API862954 - DR PRAEGERS SENSIBLE FOODS

Component Compressor





Recommendation

Resample at the next service interval to monitor.

All component wear rates are normal.

Contamination

There is no indication of any contamination in the


Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.


SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		UCH06195549		
Sample Date		Client Info		17 May 2024		
Machine Age	hrs	Client Info		36951		
Oil Age	hrs	Client Info		5402		
Oil Changed		Client Info		Changed		
Sample Status				NORMAL		
CONTAMINATION		method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0		
Chromium	ppm	ASTM D5185m	>5	0		
Nickel	ppm	ASTM D5185m		0		
Titanium	ppm	ASTM D5185m		0		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>15	<1		
Lead	ppm	ASTM D5185m	>65	0		
Copper	ppm	ASTM D5185m	>65	0		
Tin	ppm	ASTM D5185m	>10	<1		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	1	0		
Barium	ppm	ASTM D5185m	0.3	5		
Molybdenum	ppm	ASTM D5185m	0	0		
Manganese	ppm	ASTM D5185m	0	<1		
Magnesium	ppm	ASTM D5185m	0	0		
Calcium	ppm	ASTM D5185m	0.5	0		
Phosphorus	ppm	ASTM D5185m	536	292		
Zinc	ppm	ASTM D5185m	0.2	0		
Sulfur	ppm	ASTM D5185m	649	848		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>35	0		
Sodium	ppm	ASTM D5185m		<1		
Potassium	ppm	ASTM D5185m	>20	<1		
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	0.337	0.50		





OIL ANALYSIS REPORT




VISUAL		method	limit/base	ourront	hiotonyl	history?			
VISUAL		memod	IIIIII/Dase	current	history1	history2			
White Metal	scalar	*Visual	NONE	NONE					
Yellow Metal	scalar	*Visual	NONE	NONE					
Precipitate	scalar	*Visual	NONE	NONE					
Silt	scalar	*Visual	NONE	NONE					
Debris	scalar	*Visual	NONE	LIGHT					
Sand/Dirt	scalar	*Visual	NONE	NONE					
Appearance	scalar	*Visual	NORML	NORML					
Odor	scalar	*Visual	NORML	NORML					
Emulsified Water	scalar	*Visual	>0.1	NEG					
Free Water	scalar	*Visual		NEG					
FLUID PROPERT	IEC	method	limit/base	ourront	hioton/1	hiotory?			
FLUID FROFERI	IES	memou	IIIIII/Dase	current	history1	history2			
Visc @ 40°C	cSt	ASTM D445	42.0	42.3					
SAMPLE IMAGES	3	method	limit/base	current	history1	history2			
Color					no image	no image			
Bottom					no image	no image			
GRAPHS									













Certificate 12367

Laboratory Sample No.

Test Package : IND 2

Lab Number : 06195549

: UCH06195549 Unique Number : 11057672

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 30 May 2024 Tested : 31 May 2024 Diagnosed

: 31 May 2024 - Wes Davis

AIRMATIC COMPRESSOR SYSTEMS 700 WASHINGTON AVE CARLSTADT, NJ US 07072

Contact: ELVIN DIAZ ediaz@airmaticcompressor.com;canastasio@wearcheckusa.com

To discuss this sample report, contact Customer Service at 1-800-237-1369. * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

T: (800)864-7621 F: (201)342-6241

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012) Report Id: UCAIRCAR [WUSCAR] 06195549 (Generated: 05/31/2024 20:19:43) Rev: 1

Contact/Location: ELVIN DIAZ - UCAIRCAR