


OIL ANALYSIS REPORT

•







9918
Component
Diesel Engine

Machine Id

DIESEL ENGINE OIL SAE 15W40 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. Please specify the component make and model with your next sample. Please specify the brand, type, and viscosity of the oil on your next sample.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the


Fluid Condition


The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.


		Jun 202	2 Mar2023	Nov2023 Ma	ay2024		
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2	
Sample Number		Client Info		HRE0000157	WC0860418	WC0790556	
Sample Date		Client Info		06 May 2024	17 Nov 2023	22 Mar 2023	
Machine Age	mls	Client Info		338397	332856	327442	
Oil Age	mls	Client Info		0	6000	6000	
Oil Changed		Client Info		Changed	Changed	Changed	
Sample Status				NORMAL	NORMAL	NORMAL	
CONTAMINATION	N	method	limit/base	current	history1	history2	
Fuel		WC Method	>5	<1.0	1.9	<1.0	
Water		WC Method	>0.2	NEG	NEG	NEG	
Glycol		WC Method		NEG	NEG	NEG	
WEAR METALS		method	limit/base	current	history1	history2	
Iron	ppm	ASTM D5185m	>100	9	12	16	
Chromium	ppm	ASTM D5185m	>20	<1	<1	1	
Nickel	ppm	ASTM D5185m	>4	0	<1	0	
Titanium	ppm	ASTM D5185m		6	<1	<1	
Silver	ppm	ASTM D5185m	>3	0	<1	0	
Aluminum	ppm			2	3	3	
Lead	ppm	ASTM D5185m	>40	3	16	<1	
Copper	ppm	ASTM D5185m		<1	2	2	
Tin	ppm	ASTM D5185m	>15	<1	0	0	
Vanadium	ppm	ASTM D5185m		0	<1	<1	
Cadmium	ppm	ASTM D5185m		0	0	0	
ADDITIVES		method	limit/base	current	history1	history2	
Boron	ppm	ASTM D5185m	250	83	28	20	
Barium	ppm			0	0	3	
Molybdenum	ppm	ASTM D5185m	100	46	62	78	
Manganese	ppm	ASTM D5185m	450	<1	<1	<1	
Magnesium	ppm	ASTM D5185m	450	546	414	219	
Calcium	ppm	ASTM D5185m	3000	1373	1735	1910	
Phosphorus Zinc	ppm	ASTM D5185m	1150 1350	965 1128	1022 1283	974 1173	
Sulfur	ppm	ASTM D5185m	4250	3562	3414	3288	
CONTAMINANTS		method	limit/base	current	history1	history2	
Silicon	ppm	ASTM D5185m	>25	5	4	6	
Sodium	ppm	ASTM D5185m	>158	8	2	4	
Potassium	ppm	ASTM D5185m	>20	5	<1	1	
INFRA-RED		method	limit/base	current	history1	history2	
Soot %	%	*ASTM D7844	>3	0.4	0.4	0.6	
Nitration	Abs/cm	*ASTM D7624	>20	9.8	9.7	10.5	
Sulfation	Abs/.1mm	*ASTM D7415	>30	21.3	21.9	22.8	
FLUID DEGRADATION method limit/base current history1 history2							
Oxidation	Abs/.1mm	*ASTM D7414	>25	19.5	19.8	18.8	
Base Number (BN)	mg KOH/g	ASTM D2896	8.5	6.8	6.2	5.7	



OIL ANALYSIS REPORT











VISUAL		method				history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG

FLUID PROPER	IIES	method	ilmit/base		nistory i	nistory2
Visc @ 100°C	cSt	ASTM D445	14.4	12.7	12.4	13.7













Sample No.

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 : HRE0000157 Lab Number : 06196198

Unique Number : 11058321

Received : 31 May 2024 **Tested** : 03 Jun 2024

Diagnosed : 03 Jun 2024 - Wes Davis

Test Package : FLEET Certificate 12367 To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

TOWN OF CHAPEL HILL

6900 MILLHOUSE RD CHAPEL HILL, NC US 27516

Contact: Lisa DePasqua Idepasqua@townofchapelhill.org

T: (919)696-4941

Report Id: TOWCHANC [WUSCAR] 06196198 (Generated: 06/03/2024 08:59:08) Rev: 1

Contact/Location: Lisa DePasqua - TOWCHANC